

DAVISON OIL CO INC -- PRIDE LITHIUM EP-2 GREASE,01450105 -- 9150-00-347-0471
===== Product Identification =====

Product ID:PRIDE LITHIUM EP-2 GREASE,01450105

MSDS Date:02/17/1992

FSC:9150

NIIN:00-347-0471

MSDS Number: CCLRF

=== Responsible Party ===

Company Name:DAVISON OIL CO INC

Address:8450 TANNER WILLIAMS RD

City:MOBILE

State:AL

ZIP:36608

Country:US

Info Phone Num:334-633-4444

Emergency Phone

Num:800-735-0587/800-424-9300(CHEMTREC)

CAGE:0AYH2

=== Contractor Identification ===

Company Name:DAVISON OIL CO INC

Address:8450 TANNER WILLIAMS RD

Box:City:MOBILE

State:AL

ZIP:36608

Country:US

Phone:334-633-4444

CAGE:0AYH2

===== Composition/Information on Ingredients =====

Ingred Name:ORGANOZINC COMPOUND (5115)

Fraction by Wt: 1 - 5%

Other REC Limits:NONE RECOMMENDED

Ingred Name:LITHIUM SOAP/LITHIUM CASTOR SOAP

Fraction by Wt: 5 - 20%

Other REC Limits:NONE RECOMMENDED

In

Ingredient Name: MINERAL OIL, HYDROTREATED (MILD), HEAVY NAPHTHENIC
DISTILLATE, PETROLEUM/PETROLEUM HYDROCARBON

CAS: 64742-52-5

RTECS #: PY8035000

Fraction by Wt: 20 - 50%

Other REC Limits: NONE RECOMMENDED

OSHA PEL: 5 MG/M3 AS OIL MIST

ACGIH TLV: 5 MG/M3 AS OIL MIST

Ingredient Name: MINERAL OIL, PETROLEUM DISTILLATE, SOLVENT DEWAXED
(SEVERE), HEAVY PARAFFINIC/PETROLEUM HYDROCARBON

CAS: 64742-65-0

RTECS #: PY8038501

Fraction by Wt: 20 - 50%

Other REC Limits: NONE RECOMMENDED

OSHA PEL: 5 MG/M3 AS OIL MIST

AC

GIH TLV: 5 MG/M3 AS OIL MIST

Ingredient Name: SOLVENT DEWAXED RESIDUAL OIL (PETROLEUM)/PETROLEUM
HYDROCARBON

CAS: 64742-62-7

Fraction by Wt: 20 - 50%

Other REC Limits: NONE RECOMMENDED

OSHA PEL: 5 MG/M3 AS OIL MIST

ACGIH TLV: 5 MG/M3 AS OIL MIST

===== Hazards Identification =====

LD50 LC50 Mixture: LD50 (ORAL, RAT) IS NOT KNOWN.

Routes of Entry: Inhalation: NO Skin: NO Ingestion: NO

Reports of Carcinogenicity: NTP: NO IARC: NO OSHA: NO

Health Hazards Acute and Chronic:

TARGET ORGANS: EYE, SKIN, RESPIRATORY

TRACT. ACUTE- MAY CAUSE EYE/SKIN IRRITATION. INJECTION UNDER SKIN
CAUSES LOCAL NECROSIS. INHALATION OF VAPORS/OIL MIST MAY CAUSE
IRRITATION. SLIGHTLY TOXIC IF INGESTED. MAY CAUSE IRRITATION,
NAUSEA, VOMITING. POSSIBLE ASPIRATION HAZARD. CHRONIC- UNKNOWN.

Explanation of Carcinogenicity: NONE.

Effects of Overexposure: IRRITATION, REDNESS, SWELLING, TISSUE DAMAGE,
NAUSEA, VOMITING

Medical Cond Aggravated by Exposure: INDIVIDUALS WITH PRE-EXISTING

NG SKIN

DISORDERS MAY BE MORE SUCCEPTIBLE TO THE EFFECTS FROM EXPOSURE TO THIS PRODUCT.

===== First Aid Measures =====

First Aid:GET MEDICAL HELP IF SYMPTOMS PERSIST. INHALED:REMOVE TO FRESH AIR. EYES:FLUSH WITH WATER FOR 15 MINUTES. HOLD EYELIDS OPEN. SKIN:WIPE OFF EXCESS & WASH SKIN WITH MILD SOAP & WATER OR WATERLESS CLEANER . IF INJECTED UNDER SKIN, REGARDLESS OFITS SIZE, CONTACT A PHYSICIAN IMMEDIATELY. DELAY MAY CAUSE LOSS OF AFFECTED PART OF BODY. ORAL:DO NOT INDUCE VOMITING. CALL PHYSICIAN.

===== Fire Fighting Measures =====

Extinguishing Media:USE FOAM, DRY CHEMICAL/CARBON DIOXIDE. DON'T USE DIRECT STREAM OF WATER. IT MAY SPREAD FIRE. COOL CONTAINER WITH WATER.

Fire Fighting Procedures:DO NOT ENTER ANY ENCLOSED OR CONFINED AREA WITHOUT PROPER PROTECTIVE EQUIPMENT AND NIOSH-APPROVED SELF-CONTAINED BREATHING APPARATUS.

Unusual Fire/Explosion Hazard:TOXIC GASES

===== Accidental Release Measures =====

Spill Release Procedures:SCOOP UP EXCESS GREASE. PICK-UP RESIDUE WITH NON-FLAMMABLE ABSORBENT MATERIAL SUCH AS DIATOMACEOUS EARTH, SAND OR VERMICULITE. SWEEP UP AND TRANSFER TO A CONTAINER FOR PROPER DISPOSAL. CLEAN AREA WITH MILD DETERGENT.

Neutralizing Agent:NOT RELEVANT

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN COOL, DRY, VENTILATED PLACE

AWAY FROM INCOMPATIBLES. KEEP CONTAINERS TIGHTLY CLOSED. KEEP OUT OF REACH OF CHILDREN. AVOID TEMPERATURES >120F.

Other Precautions:DO NOT GET IN EYES. MINIMIZE SKIN CONTACT. WASH THOROUGHLY AFTER HANDLING. LAUNDRER CONTAMINATED CLOTHING BEFORE REUSE. PROPERLY DISPOSE OF CONTAMINATED LEATHER ARTICLES INCLUDING SHOES THAT CANNOT BE DECONTAMINATED.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE NORMALLY NEEDED. IF WORKING IN CONFI

NED

AREAS, IF EXCESSIVE MISTING IS EXPECTED OR IF EXPOSURE MAY OR DOES EXCEED RECOMMENDED PERMISSIBLE EXPOSURE LIMITS, WEAR NIOSH-APPROVED ORGANIC VAPOR AND MIST RESPIRATOR (REFER TO 29 CFR 1910.134)

Ventilation:USE ADEQUATE VENTILATION TO KEEP OIL MISTS OF THIS MATERIAL BELOW APPLICABLE STANDARD(S).

Protective Gloves:NITRILES TO MINIMIZE SKIN CONTACT

Eye Protection:SAFETY GLASSES/CHEMICAL SPLASH GOGGLES

Other Protective Equipment:EYE WASH STATION AND SAFETY SHOWER.

INDUSTRI

AL-TYPE WORK CLOTHING AND APRON AS REQUIRED.

Work Hygienic Practices:OBSERVE GOOD PERSONAL HYGIENE PRACTICES AND RECOMMENDED PROCEDURES. DO NOT WEAR CONTAMINATED CLOTHING OR FOOTWEAR.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:V6

NRC/State Lic Num:NOT RELEVANT

Vapor Density:>1

Spec Gravity:0.89

Evaporation Rate & Reference: