

INTERNATIOAL LUBRICANTS CO INC -- MIL-L-26087 B GRADE II -- 9150-00-753-4636

===== Product Identification =====

Product ID:MIL-L-26087 B GRADE II

MSDS Date:03/01/1997

FSC:9150

NIIN:00-753-4636

MSDS Number: CCLSW

=== Responsible Party ===

Company Name:INTERNATIOAL LUBRICANTS CO INC

Address:10363 AIRLINE HIGHWAY

City:SAINT ROSE

State:LA

ZIP:70087

Country:US

Info Phone Num:504-469-0940

Emergency Pho

ne Num:504-469-0940

CAGE:JO811

=== Contractor Identification ===

Company Name:INTERNATIONAL LUBRICANTS INC

Address:10363 W AIRLINE HWY

Box:City:SAINT ROSE

State:LA

ZIP:70087

Country:US

Phone:504-469-0940(504-471-0104FAX)

CAGE:0W1H4

Company Name:INTERNATIONAL LUBRICATES INC

Address:10363 AIRLINE HIGHWAY

Box:City:SAINT ROSE

State:LA

ZIP:70087

Country:US

Phone:504-469-0940

CAGE:JO811

Company Name:SDB CONSULTANTS LTD

Address:401 WHITNEY AVE SUITE 120

Box:City:GRETNA

State:LA

ZIP:70056

Country:US

Pho

ne:504-366-9105
CAGE:0PGK2

=====
Composition/Information on Ingredients
=====

Ingred Name:PETROLEUM BASED LUBE
Fraction by Wt: 100%
Other REC Limits:NONE RECOMMENDED

=====
Hazards Identification
=====

LD50 LC50 Mixture:TLV FOR OIL MIST IS 5 MG/M3.
Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:TARGET ORGANS:EYE, SKIN, RESPIRATORY
TRACT. ACUTE-
PRACTICALLY NON-IRRITATING TO EYES. MAY CAUSE SLIGHT
IRRITATION TO SKIN. INHALATION OF VAPORS/OIL MIST MAY CAUSE
IRRITATION, COUGH. RELATIVELY NON-TO XIC. INGESTION OF LARGE
AMOUNTS MAY CAUSE LAXATIVE EFFECTS. CHRONIC- MAY CAUSE DRYING,
CRACKING OF SKIN, COUGH.
Explanation of Carcinogenicity:NONE
Effects of Overexposure:IRRITATION, NAUSEA, ABDOMINAL DISCOMFORT,
COUGHING
Medical Cond Aggravated by Exposure:PERSONS WITH PRE-EXISTING SKIN
DISORDERS, EYE PROBLEMS OR IMPAIRED
RESPIRATORY FUNCTION MAY BE
MORE SUSCEPTIBLE TO THE EFFECTS OF THIS PRODUCT.

=====
First Aid Measures
=====

First Aid:CALL A DOCTOR IF SYMPTOMS OCCUR. EYE:FLUSH WITH WATER. HOLD
EYELIDS OPEN. SKIN:WIPE EXCESS OFF. WASH SKIN WITH SOAP & WATER OR
A WATERLESS HAND CLEANER FOLLOWED BY SOAP & WATER. IF MATERIAL IS
INJECTE D UNDER SKIN, GET MEDICAL ATTENTION PROMPTLY. DO NOT WAIT
FOR SYMPTOMS TO DEVELOP. INHALED:REMOVE TO FRESH AIR. ORAL:DO N
OT
INDUCE VOMITING. GET MEDICAL ADVICE.

=====
Fire Fighting Measures
=====

Flash Point Method:COC
Flash Point:500F,260C
Autoignition Temp:Autoignition Temp Text:>600F
Extinguishing Media:USE CARBON DIOXIDE, FOAM/DRY CHEMICAL. DIRECTLY
SPRAYING WATER/FOAM ONTO BURNING OIL MAY CAUSE FROTHING.
Fire Fighting Procedures:WEAR FIRE FIGHTING PROTECTIVE EQUIPMENT AND
NIOSH-APPROVED SELF CONTAINED BREATHING APPARATUS. COOL FIRE
EXPOSED CONTAINERS WITH WA

TER SPRAY.

Unusual Fire/Explosion Hazard:DENSE SMOKE, CARBON MONOXIDE, CARBON DIOXIDE MAY BE FORMED.

===== Accidental Release Measures =====

Spill Release Procedures:WEAR PROTECTIVE EQUIPMENT. PROVIDE ADEQUATE VENTILATION. REMOVE SPILL WITH INERT ABORBENT SUCH AS SAND, CLAY, EARTH. TRANSFER TO PROPER CONTAINERS FOR DISPOSAL. PREVENT RUN-OFF TO ENTER SEWERS OR WATE RWAYS. REPORT SPILLS AS REQUIRED TO AUTHORITIES.

Neutralizing Agent:NOT RELEVANT

=

===== Handling and Storage =====

Handling and Storage Precautions:STORE AWAY FROM HIGH HEAT & STRONG OXIDANTS. KEEP CONTAINERS CLOSED WHEN NOT IN USE. KEEP OUT OF REACH OF CHILDREN.

Other Precautions:DO NOT GET IN EYES, ON SKIN OR ON CLOTHING. WASH THOROUGHLY AFTER HANDLING. AVOID BREATHING OIL MIST. DISCARD LUBRICANT-SOAKED SHOES. REMOVE LUBRICANT-SOAKED CLOTHING AND LAUNDRER BEFORE RE-USE.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE NORMALLY NEEDED. IF WORKING IN CONFINED AREAS, IF EXCESSIVE MISTING IS EXPECTED OR IF EXPOSURE MAY OR DOES EXCEED RECOMMENDED PERMISSIBLE EXPOSURE LIMITS, WEAR NIOSH-APPROVED ORGANIC VAPOR AND MI ST RESPIRATOR (REFER TO 29 CFR 1910.134)

Ventilation:USE ADEQUATE VENTILATION TO KEEP OIL MISTS OF THIS MATERIAL BELOW APPLICABLE STANDARD(S).

Protective Gloves:NITRILE/NEOPRENE FOR REPEATED CONTACT

Eye Protection:SAFETY GLASSES, FACE SHIELD RECOMMENDED

Other Protective Equipment:EYE WASH STATION AND SAFETY SHOWER. INDUSTRIAL-TYPE WORK CLOTHING AND APRON AS REQUIRED.

Work Hygienic Practices:OBSERVE GOOD PERSONAL HYGIENE PRACTICES AND RECOMMENDED PROCEDURES.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:V6

NRC/State Lic Num:NOT RELEVANT

Boiling Pt:B.P. Text:>500F,>260C

Melt/Freeze Pt:M.P/F.P Text:30.0F,-1.1C

Spec Gravity:0.93

Viscosity:280-320 CST

Appearance and Odo

r:AMBER LIQUID

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid: YES

STRONG OXIDIZING AGENTS

Stability Condition to Avoid: NONE

Hazardous Decomposition Products: MAY PRODUCE SMOKE, CARBON MONOXIDE,
CARBON DIOXIDE.

===== Disposal Considerations =====

Waste Disposal Methods: DISPOSE OF WASTE IN COMPLIANCE WITH ALL
APPLICABLE LOCAL, STATE AND FEDERAL LAWS AND REGULATIONS. RCRA
EMERGENCY NUMBER: 800

-424-9346. DO NOT CONTAMINATE ANY LAKES,
STREAMS, PONDS OR UNDERGROUND WATER SUPPLY. INCINERATION IS
RECOMMENDED.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.