

HENRY W W CO -- HENRY 430 CLEAR THIN-SPREAD FLOOR TILE ADHESIVE -- 8040-01-261-4187

=====  
Product Identification  
=====

Product ID:HENRY 430 CLEAR THIN-SPREAD FLOOR TILE ADHESIVE

MSDS Date:12/01/1995

FSC:8040

NIIN:01-261-4187

MSDS Number: CCLYZ

=== Responsible Party ===

Company Name:HENRY W W CO

Address:5608 SOTO ST

City:HUNTINGTON PARK

State:CA

ZIP:90255-2629

Country:US

Info Phone Num:213-583-4961

/ FAX 213-582-8451

Emergency Phone Num:800-424-9300(CHEMTREC)/213-583-4961

CAGE:11761

=== Contractor Identification ===

Company Name:HENRY W W CO

Box:3001

City:LANCASTER

State:PA

ZIP:17604

Country:US

Phone:717-396-2328;717-396-2935

CAGE:11761

=====  
Composition/Information on Ingredients  
=====

Ingred Name:VM & P NAPHTHA (PER MSDS:MAY VARY DEPENDING ON SOLVENT  
SUPPLIER)

CAS:64742-89-8

Fraction by Wt: 2%

Other REC Limits:NONE RECOMMENDED

Ingred Name:EXTRACTS, HEAVY NAPHTHE

NIC DISTILLATE SOLVENT

CAS:64742-11-6

RTECS #:PY8042000

Fraction by Wt: 24%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:300 PPM

ACGIH TLV:300 PPM

=====  
===== Hazards Identification =====

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:ACUTE:EYE:PROD/VAP MAY CAUSE

IRRIT,TEAR,REDNESS,BLUR VISION,CONJ.SKIN:BRIEF CONTACT MAY  
CUSE

IRRIT.PROL/REP MAY CAUSE

REDNESS,BURNING,DRYING,CRACKING.INHAL:MISUSE/USE W/INADEQU VENTI

MAY CAUSE RESP T RACT IRRIT,CNS EFFECTS.INGEST:MAY CAUSEGI

IRRIT,CNS EFFECTS.CHRONIC:INHAL:PERM BRAIN,NERVOUS SYS

DMG,ANEMIA,IRREG (SUP)

Explanation of Carcinogenicity:PER MSDS:CHRONIC OVEREXPO TO AROMATIC  
PROCESS OILS IS REPORTED TO HAVE CAUSE SKIN CANCER IN RATS.

Effects of Overexposure:INHAL:IDDZ,WEAKNESS,FTG,NAU,HEAD.INEST:GI

IRRIT,NAU,VOMIT,DIARRHEA.SYMTOMS OF OVEREXPO

:NOSE/THROAT

IRRIT,DIZZNDRUNKENNESS,WEAKNESS,NAUSEA,HEADACHE.

Medical Cond Aggravated by Exposure:PRE-EXISTING EYE/SKIN/CENTRAL

NERVOUS SYTEM/RESP DISORDERS. TARGET ORGANS:NERVOUS SYSTEM,KIDNEYS.

=====  
===== First Aid Measures =====

First Aid:EYE:IMMED FLUSH W/PLENTY OF WATER FOR @LEST 15MINS.REMOVE  
CONTACT LENSES.HOLD EYELIDS OPN.GET IMMED MED ATTN.SKIN:REMOVE  
CONTAMIN CLOTH/SHOES.WASH THOROUGHLY W/SOAP/WATER.IRRIT PERSISTS  
GET MED ATTN.I NH

AL:REMOVE TO FRESH AIR.BREATH DIFFICULT GIVE

OXY;STOP BREATH IMMED BEGIN ART RESP.KEEP WARM/QUIET.GET IMMED MED

ATTN.INGEST:GET IMMED MED ATTN.DROWSY/UNCONSC PLACE ON LEFT SIDE

W/HEAD DOWN.(SUPPLE)

=====  
===== Fire Fighting Measures =====

Flash Point:NA

Autoignition Temp:Autoignition Temp Text:NP

Lower Limits:NP

Upper Limits:NP

Extinguishing Media:USE EXTINGUISHING MEDIA APPROPRIATE FOR SURROUNDING  
FIRE.

Fire Fighting Procedures:WEAR SELF-CONTAINED B

REATHING APPARATUS & FULL

PROTECTIVE FEAR. USE WATER SPRAY TO COOL FIRE-EXPOSED CNTNRS.  
Unusual Fire/Explosion Hazard:WET MATL IS NOT COMBUSTIBLE.CLSD CNTNRS  
MAY RUPTURE DUE TO PRESSURE BUILDUP.

===== Accidental Release Measures =====

Spill Release Procedures:WEAR PPE AS SITUATION WARRANTS.COVER SPILL  
W/FLOOR ABSORBENT/OTHER INERT MATL.SCOOP MATL INTO DOT APPROVED  
CNTNR;REMOVE TO SAFE PALCE TO DRY.KEEP PRODUCT OUT OF SEWERS/OPEN  
BODIES OF WATER.U  
SE CUATION -FLOOR MAY BE SLIPPERY.  
Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

===== Handling and Storage =====

Handling and Storage Precautions:USE/STORE IN COOL DRY WELL VENTI AREA  
AWAY FROM INCOMP MATLS.KEEP OUT OF REACH OF CHILDREN.USE ONLY AS  
DIRECTED ON LABEL.CLS CNTNR AFT EA USE.  
Other Precautions:.DO NOT REUSE CNTNR.AVOID SKIN/EYE CONTACT.INITIALY  
MAY BE POT ADVERSE IMPACT ON INDOOR AIR QUALITY WH/IN GEN WORKAREA  
DURING INSTALL  
ATION PROCESS-ADVISE BLDG MNGR/APPROPRIATE  
PERSON.PERSONS SENS TO ODORS/CHEM ADVISE TO AVOID WORKAREA.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:WEAR NIOSH APPROVED RESP PROTECTION WHEN PEL OR  
COMFORT LEVEL MAY BE EXCEEDED.  
Ventilation:USE ONLY W/ADEQU VENTI.OPN DOORS/WINDOWS.PROVIDE SUFFI  
MECH(GEN &/OR LOC EXHAU)VEVTI TO KEEP VAP LEVELS BEL OSHA PEL.  
Protective Gloves:RUBBER GLVOES.  
Eye Protection:GOGGLES TO PREVENT EYE CONTACT.  
Ot  
her Protective Equipment:SOURCE OF CLEAN WATER SHOULD BE AVAILABLE IN  
WORKAREA FOR FLUSHING SKIN/EYES.WEAR IMPERVIOUS PROTECTIVE  
CLOTHING.  
Work Hygienic Practices:AVOID VAP BREATH,PROL/REP SKIN CONTACT.REMOVE  
CONTAM CLOTH/SHOES;CLEAN WELL BEF REUSE.WASH WELL AFT HNDLG  
W/SOAP/WATER.  
Supplemental Safety and Health  
HEALTH HAZ:HEART RHYTHM,BEHAVIORAL CHANGES. 1ST AID:DON'T GIVE ANYTHING  
BY MOUTH.DON'T INDUCE VOMIT UNLESS DIRECTED TO DO SO BY MED  
PERSONNEL;VOMIT OCCURS SPONS KE

EP HEAD BEL HIPS TO PREVENT  
ASPIRATION OF LIQ INTO LUNGS.

===== Physical/Chemical Properties =====

HCC:N1

Boiling Pt:B.P. Text:212F,100C

Melt/Freeze Pt:M.P/F.P Text:NA

Decomp Temp:Decomp Text:NP

Vapor Pres:18MM @68F

Vapor Density: