

THETFORD CORPORATION -- AQUA KEM -- 4510-00-339-2930

=====
===== Product Identification =====

Product ID:AQUA KEM
MSDS Date:05/31/1996
FSC:4510
NIIN:00-339-2930
MSDS Number: CCMQK
=== Responsible Party ===
Company Name:THETFORD CORPORATION
Address:7101 JACKSON RD
City:ANN ARBOR
State:MI
ZIP:48103
Country:US
Info Phone Num:313-769-6000
Emergency Phone Num:313-769-6000(CHEMTREC 800-424-9300)
CAGE:DO910

==

= Contractor Identification ===

Company Name:THETFORD CORP
Address:7101 JACKSON ROAD
Box:City:ANN ARBOR
State:MI
ZIP:48106
Phone:(734) 769-6000
CAGE:61431
Company Name:THETFORD CORPORATION
Address:7101 JACKSON ROAD
City:ANN ARBOR
State:MI
ZIP:48103
Country:US
Phone:734-769-6000
CAGE:DO910

=====
===== Composition/Information on Ingredients =====

Ingred Name:FORMALDEHYDE (SARA 302/313) (CERCLA)
CAS:50-00-0
RTECS #:LP8925000
Other REC Limits:NONE RECOMMENDED
OSHA PEL:SEE 1910.1048
ACG

IH TLV:C 0.3 PPM, A2; 9596
EPA Rpt Qty:100 LBS
DOT Rpt Qty:100 LBS

Ingrid Name:METHYL ALCOHOL (METHANOL) (SARA 313) (CERCLA)
CAS:67-56-1
RTECS #:PC1400000
Other REC Limits:NONE RECOMMENDED
OSHA PEL:S, 200 PPM
ACGIH TLV:S,200PPM/250STEL; 96
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

=====
===== Hazards Identification =====

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.
Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:YES I
ARC:YES OSHA:YES
Health Hazards Acute and Chronic:ACUTE: CAN PRODUCE EYE DAMAGE & SKIN
SENSITIZATION. HIGH INHALATION EXPOSURE MAY CAUSE BRONCHOPNEUMONIA,
RESPIRATORY IRRITATION. CHRONIC: NOT MUTAGENIC, NOT TERATOGENIC.
PROLONGED/REPEATED EXPOSURE TO VAPORS MAY CAUSE CANCER, CONTAINS
FORMALDEHYDE-A KNOWN CARCINOGEN.
Explanation of Carcinogenicity:CONTAINS F [50-00-0] WHICH IS
LISTED BY NTP AND IARC AND REGULATED BY OSHA AS A CARCINOGEN.
Effects of Overexposure:INHALATION-RESPIRATORY IRRITATION, NAUSEA,
WEAKNESS, HEADACHE. EYE-DAMAGE, SEVERE IRRITATION, BURNS.
SKIN-SENSITIZATION, DISCOMFORT, RASH. POSSIBLE CARCINOGEN.
Medical Cond Aggravated by Exposure:PERSONS WITH PRE-EXISTING DISEASES
OF LUNGS, SKIN, EYES MAY HAVE INCREASED SUSCEPTIBILITY TO HAZARDS
OF OVEREXPOSURE.

=====
===== First Aid Measures =====

First Aid:FLUSH AREA WITH LARGE AMOUNTS OF WATER. IRRIGATE EYES FOR A
MINIMUM OF 15 MINUTES. IF SWALLOWED, INDUCE VOMITING BY GIVING 2
GLASSES OF WATER & STICKING FINGER DOWN THROAT. FOR EYE CONTACT OR
INGESTION, CALL PHYSICIAN.

=====
===== Fire Fighting Measures =====

Flash Point Method:TCC
Flash Point:137F,58C
Extinguishing Media:WATER FOG, CARBON DIOXIDE, DRY CHEMICAL, FOAM FOR
USE ON ALCOHOL.
Fire Fighting Procedures:WEAR SELF-CONTAINED BREATHING APPARATUS.
Unusual Fire/Explosion Hazard:NONE.

=====
===== Accidental Release Measures =====

=====

Spill Release Procedures: VENTILATE AREA. WEAR PROPER PERSONAL PROTECTIVE GEAR TO INCLUDE RESPIRATORY PROTECTION. CLEAN UP SMALL SPILLS WITH WATER. ABSORB WITH INERT MATERIAL. NEUTRALIZE REMAINDER WITH AMMONIA/WATER MIXTURE. M OP AREA WITH PLENTY OF WATER.
Neutralizing Agent: WATER-AMMONIA MIXTURE.

===== Handling and Storage =====

Handling and Storage Precautions: DO NOT STORE ABOVE 110F. DO NOT FREEZE.
Other Precautions: DO NOT GET LIQUID IN EYES OR ON SKIN. DO NOT INHALE VAPORS. WASH THOROUGHLY AFTER HANDLING.

===== Exposure Controls/Personal Protection =====

Respiratory Protection: IF ENGINEERING CONTROLS FAIL OR NON-ROUTINE USE OR AN EMERGENCY OCCURS; WEAR AN MSHA/NIOSH APPROVED RESPIRATOR WITH ORGANIC VAPOR CARTRIDGE OR AN AIR-SUPPLIED RESPIRATOR OR SCBA, AS REQUIRED. USE IAW 29 CFR 1910.134.
Ventilation: USE LOCAL EXHAUST TO MAINTAIN EXPOSURE BELOW TLV(S).
Protective Gloves: RUBBER, PVC, NEOPRENE.
Eye Protection: SAFETY GLASSES/CHEMICAL SPLASH GOGGLES.
Other Protective Equipment: PROTECTIVE CLOTHING TO PREVENT SKIN CONTACT. EYE WASH STATION & SAFETY SHOWER.
Work Hygienic Practices: AVOID UNECESSARY AND PROLONGED EXPOSURE. AVOID BREATHING VAPORS.
Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC: F4
Boiling Pt: B.P. Text: 210F, 99C
Vapor Pres: 17-20
Vapor Density: 1.03
Spec Gravity: 1.08
pH: 3.5-5
Evaporation Rate & Refe

rence:>1 (N-BUTYL ACETATE=1)

Solubility in Water:COMPLETE

Appearance and Odor:BLUE LIQUID WITH PUNGENT ODOR.

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

PHENOLS, STRONG MINERAL ACIDS, STRONG OXIDIZING AGENTS, STRONG ALKALIS.

Stability Condition to Avoid:ELEVATED TEMPRTATURES.

Hazardous Decomposition Products:THERMAL DECOMPOSITION MAY PRODUCE
CARBON MONOXIDE AND CARBON DIOXIDE.

Conditions to Avoid Polymerization:WILL NOT OCC
UR.

===== Disposal Considerations =====

Waste Disposal Methods:INCINERATION OR BIOLOGICAL TREATMENT IN
STATE/FEDERAL APPROVED FACILITY.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any pers

on utilizing this

document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.