

POLY RESEARCH CORPORATION -- AMMONIUM HYDROXIDE,ZINC OXIDE -- 6810-01-386-5562

===== Product Identification =====

Product ID:AMMONIUM HYDROXIDE,ZINC OXIDE

MSDS Date:04/05/1993

FSC:6810

NIIN:01-386-5562

MSDS Number: CCVVN

=== Responsible Party ===

Company Name:POLY RESEARCH CORPORATION

Address:125 CORPORATE DRIVE

City:HOLTSVILLE

State:NY

ZIP:11742

Country:US

Info Phone Num:516-758-0460

Emergency Ph

one Num:516-758-0460

Chemtrec Ind/Phone:(800)424-9300

CAGE:64713

=== Contractor Identification ===

Company Name:POLY RESEARCH CORPORATION

Address:125 CORPORATE DRIVE

Box:City:HOLTSVILLE

State:NY

ZIP:11742-2007

Country:US

Phone:516-758-0460

CAGE:64713

Company Name:POLY SCIENTIFIC R&D CORP.

Address:70 CLEVELAND AVE

Box:City:BAY SHORE

State:NY

ZIP:11706

Country:US

Phone:516-586-0400

CAGE:67458

===== Composition/Information on Ingredients =====

Ingred Name:AMMONIUM HYDROXIDE (CER

CLA)
CAS:1336-21-6
RTECS #:BQ9625000
Fraction by Wt: 28 - 30%
Other REC Limits:NONE RECOMMENDED
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:ZINC OXIDE (SARA 313) (CERCLA)
CAS:1314-13-2
RTECS #:ZH4810000
Other REC Limits:NONE RECOMMENDED
OSHA PEL:15 MG/M3 TDUST
ACGIH TLV:10 MG/M3 TDUST; 9596

===== Hazards Identification =====

LD50 LC50 Mixture:LD50 (ORAL RAT) 350 MG/KG (RTECS, NH3)
Routes of Entry: Inhalation:YES Skin:NO Ingestion:YES
Reports of C
arcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:TARGET ORGANS:EYES, SKIN, RESPIRATORY
& GI TRACTS. ACUTE- CORROSIVE. MAY CAUSE SEVERE EYE IRRITATION, EYE
DAMAGE, BLINDNESS. CONTACT WITH SKIN MAY CAUSE SEVERE
IRRITATION/BURNS. INHALATION MAY CAUSE S EVERE IRRITATION/BURNS OF
RESPIRATORY SYSTEM, LUNG INFLAMMATION. INGESTION MAY BE FATAL.
CAUSES BURNS. CHRONIC- UNKNOWN.
Explanation of Carcinogenicity:NONE
Effects of Overexposure:SEVERE IRRITATION, SEVER
E BURNS, TEARING,
SEVERE COUGHING, DESTRUCTION OF TISSUE ON ANY EXPOSED PART OF THE
BODY, CHEST PAIN, NAUSEA, VOMITING, DIFFICULT BREATHING, DEATH,
BLINDNESS
Medical Cond Aggravated by Exposure:PRE-EXISTING EYE DISORDERS, SKIN
DISORDERS OR IMPAIRED RESPIRATORY FUNCTION MAY BE MORE SUSCEPTIBLE
TO THE EFFECTS OF THIS MATERIAL.

===== First Aid Measures =====

First Aid:GET MEDICAL ATTENTION IMMEDIATELY. SKIN:FLUSH WITH WATER,
THEN WASH

WITH SOAP & WATER. EYE:FLUSH WITH WATER FOR 15 MINUTES.
HOLD EYELIDS OPEN. INHALED:REMOVE TO FRESH AIR. PROVIDE OXYGEN/CPR
IF NEEDED . ORAL:IF CONSCIOUS, DRINK LARGE AMOUNT OF WATER FOLLOWED
BY LEMON JUICE, ORANGE JUICE, EGG WHITE, VEGETABLE OIL. DO NOT
INDUCE VOMITING. IF VOMITING OCCURS SPONTANEOUSLY, KEEP HEAD BELOW
HIPS.

===== Fire Fighting Measures =====

Flash Point:NONE
Lower Limits:NOT RELEVANT
Upper Limits:NOT RELEVANT
Extinguishing
Media:WATER SPRAY. USE WATER SPRAY TO COOL FIRE EXPOSED
CONTAINERS.
Fire Fighting Procedures:WEAR FIRE FIGHTING PROTECTIVE EQUIPMENT AND A
NIOSH-APPROVED FULL FACED SELF CONTAINED BREATHING APPARATUS.
Unusual Fire/Explosion Hazard:AMMONIUM HYDROXIDE IS NON-COMBUSTIBLE AND
NON-EXPLOSIVE, BUT AMMONIA VAPORS RELEASED FROM SOLUTION CAN FORM
EXPLOSIVE MIXTURE WITH AIR IN CONFINED AREAS.

===== Accidental Release Measures =====

Spill Release Procedures:VENT
ILATE AREA. WEAR PROTECTIVE CLOTHING AND
SCBA. RECOVER IF POSSIBLE. NEUTRALIZE WITH DILUTE HCL/SODIUM
BISULFATE. FLUSH TO SEWER WITH LARGE AMOUNT OF WATER, IF PERMITTED.
OTHERWISE, ABSORB WITH SAND. TRANSFER TO A SUITABLE CONTAINER
FOR DISPOS
Neutralizing Agent:DILUTE ACETIC ACID, HCL, H₂SO₄, SODIUM BISULFATE

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN COOL, WELL-VENTILATED AREA
AWAY FROM INCOMPATIBLE MATERIALS.
LS. STORE IN A CORROSIVE PROOF AREA,
BELOW 25C/77F.
Other Precautions:AVOID CONTACT WITH EITHER LIQUID OR VAPORS.
CONTAINERS SHOULD BE KEPT WELL SEALED WHEN NOT IN USE. MATERIAL MAY
ATTACK ZN, CU, HG, SN AND THEIR ALLOYS. KEEP OUT OF REACH OF
CHILDREN. FOR LABORATORY USE ONLY. DO NOT BREATHE VAPORS.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:WORK IN FUME HOOD OR WEAR A NIOSH-APPROVED
RESPIRATOR WITH AMMONIA CANISTER, IF NEEDED

D.
Ventilation:USE GENERAL OR LOCAL EXHAUST VENTILATION TO KEEP FUME OR VAPOR LEVELS AS LOW AS POSSIBLE.
Protective Gloves:RUBBER
Eye Protection:CHEMICAL GOGGLES AND FACE SHIELD
Other Protective Equipment:USE RUBBER SPLASH APRON. SAFETY SHOWER AND EYEWASH FOUNTAIN SHOULD BE LOCATED NEARBY.
Work Hygienic Practices:OBSERVE GOOD INDUSTRIAL HYGIENE PRACTICES AND RECOMMENDED PROCEDURES. WASH THOROUGHLY BEFORE EATING AND AFTER HANDLING.
Supplemental Safety and Health

=====

= Physical/Chemical Properties =====

HCC:B1
NRC/State Lic Num:NOT RELEVANT
Boiling Pt:=28.3C, 83.F
Melt/Freeze Pt:=-77.8C, -108.F
Vapor Pres:720 @ 80F
Vapor Density:1.2
Spec Gravity:0.90
pH:ALKALI
Solubility in Water:MISCIBLE
Appearance and Odor:LIQUID WITH STRONG ACRID SUFFOCATING ODOR
Percent Volatiles by Volume:100

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
STRONG ACIDS, STRONG OXIDIZING AGENTS, FOOD PRODUCT
S, DIMETHYL SULFATE,
BRASS, BRONZ
Stability Condition to Avoid:EXCESSIVE HEAT
Hazardous Decomposition Products:AMMONIA GAS AND NITROGEN OXIDES MAY BE FORMED.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOE OF IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS. CAREFULLY NEUTRALIZE WITH SODIUM BISULFATE AND FLUSH TO SEWER WITH LARGE AMOUNT OF WATER, IF PERMITTED.

Disclaimer (provided with this information by the compiling

agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.