

SENTRY PAINT CO -- ALUMINUM SILICONE-ALKYD, X-5767 -- 8010-00-664-7468

=====  
Product Identification  
=====

Product ID:ALUMINUM SILICONE-ALKYD, X-5767

MSDS Date:05/01/1995

FSC:8010

NIIN:00-664-7468

MSDS Number: CCXPP

=== Responsible Party ===

Company Name:SENTRY PAINT CO

Address:237 MILL ST

City:DARBY

State:PA

ZIP:19023

Country:US

Info Phone Num:215-522-1900

Emergency Phone Num:800-424-9300 (CHEMTR  
EC)

Preparer's Name:ALBERT FALCO

CAGE:IO235

=== Contractor Identification ===

Company Name:SENTRY PAINT AND CHEMICAL CO

Address:MILL AND LAWRENCE ST

Box:City:DARBY

State:PA

ZIP:19023

Country:US

CAGE:34346

Company Name:SENTRY PAINT CO

Address:MILL AND LAWRENCE ST

Box:City:DARBY

State:PA

ZIP:19023

Country:US

Phone:215-522-1900

CAGE:IO235

=====  
Composition/Information on Ingredients  
=====

Ingred Name:STODDARD SOLVENT. VP:2 @ 20C

CAS:8052-41-3

RTECS #:WJ8925000

Fraction by Wt: 56

.8%  
OSHA PEL:500 PPM  
ACGIH TLV:100 PPM

Ingred Name:VM & P NAPHTHA. VP:45 @ 25C  
CAS:64742-89-8  
Fraction by Wt: 14.5%  
OSHA PEL:300 PPM (MFR)  
ACGIH TLV:300 PPM (MFR)

Ingred Name:MATLS TO AVOID:REACTS W/WATER, ACIDS/ALKALIS TO FORM  
COMBUST HYDROGEN GAS. SEE NVPA#491M FOR SPECIFIC INCOMPAT (ING 5)  
RTECS #:9999999ZZ

Ingred Name:ING 4:MATLS. NATIONAL PROTECTION ASSOCIATION, BATTERYMARCH  
PARK, QUINCY MA 02269.  
RTECS #:9999999ZZ

Ingred Name:FIRST AID PROC:DUE TO VOMITING CAN CAUSE CHEMICAL  
PNEUMONITIS WHICH CAN BE FATAL.  
RTECS #:9999999ZZ

Ingred Name:SPILL RELEASE PROC:INERT MATL SUCH AS SAND/EARTH. TRANSFER  
LIQUIDS TO COVERED METAL CNTNRS FOR RECOVERY/DISP, (ING 8)  
RTECS #:9999999ZZ

Ingred Name:ING 7:OR REMOVE W/INERT ABSORBENT. USE ONLY NON-SPARKING  
TOOLS. PLACE ABSORBANT DIKING MATLS IN COVERED (ING 9)  
RTECS #:9999999ZZ

Ingred Name:ING 8:GROUNDWATER WITH SPILLED MATERIAL OR USED ABSORBENT.  
RTECS #:9999999ZZ

=====  
===== Hazards Identification =====  
=====

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.  
Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO  
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Health Hazards Acute and Chronic:ACUTE:EYES:IRRITATION, REDNESS,  
TEARING, BLURRED VISION. SKIN:DRYNESS, IRRITATION, DERMATITIS.  
INHALATION:NASAL AND RESPIRATORY IRRITATION, DIZZINESS, WEAKNESS,  
NAUSEA, HEADACHE. INGESTION:NAUSEA, VOM ITING, DIARRHEA. ASPIRATION  
OF MATERIAL INTO LUNGS CAN CAUSE CHEMICAL PNEUMONIT



LV LIMITS, USE NIOSH APPRVD VAPOR  
RESPIRATOR.

Ventilation:LOCAL EXHAUST MUST BE SUFFICIENT TO KEEP AIRBORNE VAPOR  
CONCENTRATION BELOW THE TLV LIMIT.

Protective Gloves:CHEMICAL RESISTANT GLOVES.

Eye Protection:ANSI APPRVD CHEM WORKERS GOGGLES .

Other Protective Equipment:ANSI APPRVD EYE WASH & DELUGE SHOWER . TO  
PVNT RPTD/PRLNGD SKIN CONT, WEAR IMPERVIOUS CLOTHING & BOOTS.

Work Hygienic Practices:NONE SPECIFIED BY MANUFACTURER.

Supplemental Safety and Health

EXPLO HAZ:IGNITED BY PILOT

LIGHTS, OTHER FLAMES, SPKS HEATERS, SMKNG,  
ELEC MOTORS, STATIC DISCHARGE/IGNIT SOURCES @ LOCATIONS DISTANT  
FROM MATL HNDLG. POINT. NEVER USE WELDING/CUTTING TORCH ON/NEAR DR  
UM (EVEN EMPTY) BECAUSE PROD (OR RESIDUE) CAN IGNITE EXPLOSIVELY.

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:>240F,>116C

Vapor Pres:SEE INGS

Vapor Density:3.9-5.0

Spec Gravity:0.9927(WATER=1)

VOC Pounds/Gallon:587

VOC Grams/Liter:4.9

Evaporation Rate & Referen  
ce:SLOWER THAN ETHER

Solubility in Water:NEGLIGIBLE,