

MINNESOTA MINING/ADH COATINGS/SEALERS -- 1751A ALUMINUM EPOXY ADHESIVE --
8040-00-123-6954

===== Product Identification =====

Product ID:1751A ALUMINUM EPOXY ADHESIVE

MSDS Date:07/20/1990

FSC:8040

NIIN:00-123-6954

Kit Part:Y

MSDS Number: CDCHR

=== Responsible Party ===

Company Name:MINNESOTA MINING/ADH COATINGS/SEALERS

Address:3M CTR

City:ST PAUL

State:MN

ZIP:55144-1000

Country:US

Info Phone Num:

612-733-1110

Emergency Phone Num:612-733-1110

Preparer's Name:C A EISENHARD

CAGE:76381

=== Contractor Identification ===

Company Name:3M MINNESOTA MINING AND MFG CO ADHESIVES SEALERS DIV

Address:3M CTR

Box:City:SAINT PAUL

State:MN

ZIP:55144-1000

Country:US

Phone:800-364-3577/651-737-6501(24 HOURS)

CAGE:04963

Company Name:MINNESOTA MINING AND MFG CO, DBA 3M

Address:3M CENTER BLDG 224-5S-04

Box:City:SAINT PAUL

State:MN

ZIP:55144-1000

Country:US

Phone:866-556 5712 / 612-733-1110

CAGE:76381

=====

=====
Composition/Information on Ingredients
=====

Ingred Name:POLYAMIDE OF C18 FATTY ACID PRIMERS & TETA; POLYAMIDE RESIN
96-3

CAS:68410-23-1

Fraction by Wt: 70-80%

Ingred Name:TRIETHYLENETETRAMINE, EPOXY HARDNER

CAS:112-24-3

RTECS #:YE6650000

Fraction by Wt: 6-15%

Ingred Name:QUATERNARY AMMONIUM COMPOUNDS, BIS(HYDROGENATED TALLOW
ALKYL) DIMETHYLAMMONIUM BENTONITE *96-3*

CAS:68953-58-2

RTECS #:UZ2996400

Ingred Name:AMORPHOUS SILICA GEL *96-3*

CAS:7631-86-9

Fra

ction by Wt: 1-10%

=====
Hazards Identification
=====

Routes of Entry: Inhalation:YES Skin:NO Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:EYES: MAY PRODUCE SEVERE IRRITATION.

SKIN: MAY PRODUCE MODERATE IRRITATION. INHALATION: IRRITATING TO

NOSE & THROAT. INGESTION: DIGESTIVE SYSTEM IRRITATION.

Explanation of Carcinogenicity:NONE

Effects of Overexposure:IRRITATION.

=====
First

Aid Measures
=====

First Aid:EYES: FLUSH W/PLENTY OF WATER FOR 10 MINS. SKIN: WASH W/SOAP
& WATER. INHALATION: REMOVE TO FRESH AIR. INGESTION: DON'T INDUCE
VOMITING. OBTAIN MEDICAL ATTENTION IN ALL CASES.

=====
Fire Fighting Measures
=====

Extinguishing Media:CO2, FOAM, DRY CHEMICALS.

Fire Fighting Procedures:WEAR SCBA.

Unusual Fire/Explosion Hazard:NONE

=====
Accidental Release Measures
=====

Spill Re

lease Procedures:VENTILATE AREA. COLLECT & DISPOSE.

=====
Handling and Storage
=====

Handling and Storage Precautions:KEEP CONTAINER TIGHTLY CLOSED WHEN NOT IN USE. KEEP OUT OF THE REACH OF CHILDREN.

=====
Exposure Controls/Personal Protection
=====

Ventilation:SUFFICIENT VENTILATION TO MAINTAIN VAPOR CONCENTRATIONS BELOW RECOMMENDED EXPOSURE LIMITS.

Protective Gloves:IMPERVIOUS

Eye Protection:SAFETY GLASSES/GOGGLES

Supplemental Sa
fety and Health

=====
Physical/Chemical Properties
=====

Spec Gravity:0.95

Solubility in Water:INSOLUBLE

Appearance and Odor:AMBER PASTE W/AMINE ODOR

Percent Volatiles by Volume:0

=====
Stability and Reactivity Data
=====

Stability Indicator/Materials to Avoid:YES

Hazardous Decomposition Products:THERMAL/BURNING: CO, CO2 & NITROGEN.

=====
Disposal Considerations
=====

Waste Disposal Methods:DISPOSE OF IAW
/FEDERAL, STATE & LOCAL
REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of thi

s information to their
particular situation.