

COURTAULDS AEROSPACE, INC -- POLYSULFIDE RUBBER COMPOUND, PRO SEAL 890 B2  
#0890B201 -- 8030-01-387-3196

===== Product Identification =====

Product ID:POLYSULFIDE RUBBER COMPOUND, PRO SEAL 890 B2 #0890B201

MSDS Date:05/28/1996

FSC:8030

NIIN:01-387-3196

Kit Part:Y

MSDS Number: CDJWQ

=== Responsible Party ===

Company Name:COURTAULDS AEROSPACE, INC

Address:5430 SAN FERNANDO RD.

Box:1800

City:GLENDALE

State:CA

ZIP:91209

Country:US

Info Phone Num:818-240-2060

Emergency Phone Num:800-424-9300 (CHEMTREC)

CAGE:83574

=== Contractor Identification ===

Company Name:PRC-DESOTO INTERNATIONAL, INC. A PPG INDUSTRIES COMPANY

Address:5430 SAN FERNANDO RD

Box:1800

City:GLENDALE

State:CA

ZIP:91209

Country:US

Phone:818-240-2060

CAGE:83574

===== Composition/Information on Ingredients =====

Ingred Name:CALCIUM CARBONATE LIMESTONE (AIRBORNE CONTAMINANT, FULLY  
ENCAPSULATED)

CAS:1317-65-3

RTECS #:EV9580000  
Fraction by Wt: 25.0%  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:15 MG/M3  
ACGIH TLV:10 MG/M3

Ingred Name:POLYSULFIDE POLYMER, (NONHAZARDOUS)  
CAS:68611-50-7  
Other REC Limits:NONE RECOMMENDED

Ingred Name:SILICA DERIVITIVES, (NONHAZARDOUS)  
CAS:67762-90-7  
Other REC Limits:NONE RECOMMENDED

Ingred Name:PHENOLIC RESIN POWDER (NONHAZARDOUS)  
Other REC Limits:NONE RECOMMENDED

Ingred Name:TOLUENE (SARA 313) (CERCLA) (VP = 23)  
CAS:108-88-3  
RTECS #:XS5250000  
Fraction by Wt: 5.0%  
Other  
REC Limits:NONE RECOMMENDED  
OSHA PEL:100 PPM; STEL 150  
ACGIH TLV:50 PPM  
EPA Rpt Qty:1000 LBS  
DOT Rpt Qty:1000 LBS

Ingred Name:TITANIUM DIOXIDE  
CAS:13463-67-7  
RTECS #:XR2275000  
Fraction by Wt: 120F. GROUNDING/BONDING PROCEDURE SHOULD BE FOLLOWED WHEN  
TRANSFERRING MTRIAL.  
Other Precautions:EMPTY DRUMS MAY CONTAIN EXPLOSIVE VAPORS. DON'T CUT,  
PUNCTURE, WELD ON/NEAR DRUM. VAPORS >AIR MAY COLLECT IN  
LOW/CONFINED AREA.

=====  
===== Exposure Controls/Personal Protection =====

Respiratory Protection:WHEN APPLYING IN ANY CIRCUMSTANCES LIKELY TO  
PRODUCE AIRBORNE LEVEL OF HAZARDOUS INGREDIENTS IN EXCESS OF TLV,  
USE ORGANIC VAPOR CARTRIDGE OR AIR-SUPPLIED RESPIRATOR.  
Ventilation:GENERAL TO MAINTAIN VAPORS AIR  
Spec Gravity:1.501  
VOC Pounds/Gallon:51  
Evaporation Rate & Reference:NOT AVAILABLE  
Appearance and Odor:WHITE THIXOTROPIC PASTE  
Percent Volatiles by Volume:12.0

=====  
===== Stability and Reactivity Data =====

Stability Indicator/Mat

erials to Avoid: YES

STRONG OXIDIZING AGENTS.

Hazardous Decomposition Products: OXIDES OF CARBON, SULFUR DIOXIDE,  
TRACES OF HYDROGEN SULFIDE.

===== Disposal Considerations =====

Waste Disposal Methods: NOT A HAZARDOUS WASTE ACCORDING TO EPA  
REGULATIONS. CONSULT STATE REGULATIONS PRIOR TO DISPOSAL OF SPILL.

===== Other Information =====

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.