

ARCADIAN CORP -- SULFURIC ACID -- 6810-01-031-4652

===== Product Identification =====

Product ID:SULFURIC ACID

MSDS Date:04/16/1996

FSC:6810

NIIN:01-031-4652

MSDS Number: CDMMZ

=== Responsible Party ===

Company Name:ARCADIAN CORP

Address:6750 POPLAR, SUITE 600

City:MEMPHIS

State:TN

ZIP:38138-7419

Country:US

Info Phone Num:800-524-0132

Emergency Phone Num:800-424-9300(CHEMTREC)/800-524-0132

CAGE:01

KQ2

=== Contractor Identification ===

Company Name:ARCADIAN CORP

Address:6750 POPLAR AVE

Box:City:MEMPHIS

State:TN

ZIP:38138

Country:US

Phone:800-654-4514

CAGE:01KQ2

Company Name:MAGNOLIA CHEMICALS & SOLVENTS,INC.

Address:1020 SAMS AVE

Box:10278

City:NEW ORLEANS

State:LA

ZIP:70181-0278

Phone:504-733-6600

CAGE:MAGNO

===== Composition/Information on Ingredients =====

Ingred Name:SULFURIC ACID (SARA 302/313) (CERCLA)

CAS:7664-93-9

RTECS #:WS5600000

Fraction by Wt: 93-99.5%

Other

REC Limits:NONE RECOMMENDED
OSHA PEL:1 MG/M3
ACGIH TLV:1 MG/M3/3 STEL; 9495
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

===== Hazards Identification =====

LD50 LC50 Mixture:PRODUCT'S LD50 (ORAL RAT) WAS NOT STATED
Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:EYE:IRRITATION, CORNEAL BURNS,
CONJUNCTIVIS, BLINDNESS. SKIN:CAN CAUSE SEVERE BURNS OR IRRITATION.
|
NHALATION:CAN CAUSE IRRITATION OR CORROSIVE BURNS TO RESPIRATORY
TRACT. INGESTION:CAN CAUSE IRRITATI ON, CORROSIVE BURNS TO MOUTH &
G/I TRACT. MAY BE FATAL IF SWALLOWED. CHRONIC-TOOTH EROSION,
LESIONS, CONJUNCTIVITIS.
Explanation of Carcinogenicity:MANUFACTURER GAVE NO INFORMATION ABOUT
CARCINOGENICITY. HMIS FOUND NO LISTING & DOES NOT EXPECT IT TO BE
CARCINOGENIC.
Effects of Overexposure:EYE:IRRITATION, CORNEAL BURNS, CONJUNCTIVIS,
BLINDNESS. SKIN:SEVERE BURNS OR IRRITAT
ION. INHALATION:IRRITATION
OR CORROSIVE BURNS TO RESPIRATORY TRACT. INGESTION:IRRITATION,
CORROSIVE BURNS TO MOUTH & G/I TRACT. MAY BE FATAL IF SWALLOWED.
Medical Cond Aggravated by Exposure:MFR GAVE NO INFORMATION OF MSDS.

===== First Aid Measures =====

First Aid:IF IRRITATION PERSISTS OR IS SEVERE, GET MEDICAL ATTENTION.
EYE:FLUSH W/WATER FOR 15 MIN. SKIN:WASH W/SOAP & WATER. REMOVE
CONTAMINATED CLOTHING & LAUNDER BEFORE REUSE. INHALED:RE
MOVE FROM
EXPOSURE. A ID OR RESTORE BREATHING AS NEEDED. INGESTED:DO NOT
INDUCE VOMITING. GIVE LARGE AMOUNTS OF MILK OR WATER TO DRINK. GET
IMMEDIATE MEDICAL ATTENTION. NOTHING BY MOUTH IF UNCONSCIOUS.

===== Fire Fighting Measures =====

Flash Point:N/A.
Autoignition Temp:Autoignition Temp Text:N/A.
Lower Limits:N/A.
Upper Limits:N/A.
Extinguishing Media:USE WATER SPRAY OR OTHER SUITABLE AGENT FOR FIRES
ADJACENT TO NON-LEAK,ING TANKS & OTHER CON

TAINERS OF SULFURIC ACID.

Fire Fighting Procedures:AT HIGH TEMPERATURES SULFURIC ACID MIST OR SO₃ GAS CAN BE RELEASED FROM VENTED OR RUPTURED CONTAINERS. IF WATER IS ADDED TO CONC.ACID, SPATTERING MAY OCCUR.

Unusual Fire/Explosion Hazard:FLAMMABLE & POTENTIALLY EXPLOSIVE
HYDROGEN GAS CAN BE GENERATED INSIDE METAL DRUMS & STORAGE
TANKS.CONCENTRATED ACID CAN IGNITE COMBUSTIBLE MATERIALS ON CONTACT

===== Accidental Release Measures =====

Spill Release

Procedures:DILUTE SMALL SPILL CAUTIOUSLY W/PLENTY OF
WATER. NEUTRALIZE RESIDUE. ADEQUATE VENTILATION IS REQUIRED. NO
SMOKING IN SPILL AREA. MAJOR SPILL:KEEP UNPROTECTED PEOPLE AWAY.

Neutralizing Agent:SODA ASH, LIME

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN COOL, WELL VENTILATED AREA
AWAY FROM COMBUSTIBLES & REACTIVE CHEMICALS. VENT METAL CONTAINER
WEEKLY. DIKING OF STORAGE TANKS RECOMMENDED.

Other Precautions:

VAPOR MAY CONTAIN EXPLOSIVE HYDROGEN. DO NOT PERMIT
SMOKING OR OTHER IGNITION SOURCES IN THE STORAGE AREA. CAUSES
SEVERE BURNS. LABEL SIGNAL WORK:DANGER!

===== Exposure Controls/Personal Protection =====

Respiratory Protection:WHERE REQUIRED USE A RESPIRATOR APPROVED BY NIOSH
FOR SULFURIC ACID MIST AS APPLICABLE. SOME EXPOSURES MAY REQUIRE
SELF-CONTAINED BREATHING APPARATUS W/FULL FACEPIECE OR SUPPLIED AIR
RESPIRATOR W/FULL FACEPIECE, HELMET OR HOOD.

Venti

lation:MFR GAVE NO INFORMATION OF MSDS..

Protective Gloves:ACID RESISTANT GAUNTLET .

Eye Protection:HARD HAT, CHEMICAL GOGGLES & FACE SHIELD

Other Protective Equipment:EYE WASH & QUICK DRENCH SHOWER PROTECTED
FROM FREEZING WHERE ACID IS STORED OR HANDLED. ACID RESISTANT
CLOTHING & BOOTS

Work Hygienic Practices:MFR GAVE NO INFORMATION OF MSDS..

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:C1

NRC/State Lic Num:NONE

Boiling Pt:B.P

. Text:534F,279C
Melt/Freeze Pt:M.P/F.P Text:N/A.
Vapor Pres:NEGLIGIBLE
Vapor Density:N/A.
Spec Gravity:1.835
Evaporation Rate & Reference:N/A.
Solubility in Water:100%
Appearance and Odor:OILY, COLORLESS TO SLIGHTLY YELLOW TO TURBID
LIQUID, ODORLESS
Percent Volatiles by Volume:N/A.

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
NITRO COMPOUNDS, CARBIDES DIENES, ALCOHOLS (WHEN HEATED) CAUSE
EXPLOSIONS. OXIDIZING AGENTS
CAUSE FIRES & POSSIBLE EXPLO
Stability Condition to Avoid:TEMPERATURES >300C YIELD SO3 GAS WHICH IS
TOXIC, CORROSIVE & AN OXIDIZER.
Hazardous Decomposition Products:SO3 GAS. ALSO FIRE RISK W/ORGANIC
MATERIALS.
Conditions to Avoid Polymerization:WILL NOT OCCUR.

===== Disposal Considerations =====

Waste Disposal Methods:CAUTIOUSLY DILUTE & NEUTRALIZE WASTE ACID.
DISPOSE OF I/A/W FEDERAL, STATE & LOCAL REGULATIONS. WASTE MAY HAVE
TO BE DISPOSED OF
BY AN APPROVED CONTRACTOR.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information
to their
particular situation.