

STOODY CO -- BUILD-UP LH, DYNAMANG LH, SELF HARDENING, 1027 -- 3439-00-334-4922

=====  
Product Identification  
=====

Product ID:BUILD-UP LH, DYNAMANG LH, SELF HARDENING, 1027

MSDS Date:04/16/1992

FSC:3439

NIIN:00-334-4922

MSDS Number: CDNXJ

=== Responsible Party ===

Company Name:STOODY CO

Box:9997

City:BOWLING GREEN

State:KY

ZIP:42102-4997

Country:US

Info Phone Num:502-781-9777

Emergency Phone Num:

502-781-9777

CAGE:57965

=== Contractor Identification ===

Company Name:STOODY CO

Box:90032

City:BOWLING GREEN

State:KY

ZIP:42102-9032

Country:US

Phone:502-781-9777

CAGE:57965

=====  
Composition/Information on Ingredients  
=====

Ingred Name:MANGANESE (SARA 313)

CAS:7439-96-5

RTECS #:OO9275000

Fraction by Wt: 0-20%

OSHA PEL:C 5 MG/M3 DUST

ACGIH TLV:5 MG/M3 DUST 9495

Ingred Name:SILICON

CAS:7440-21-3

RTECS #:VW0400000

Fraction by Wt: 0-10%

OSHA PEL:15 MG/M3 TDUST

ACGIH TLV:10 MG/

M3 TDUST; 9495

Ingred Name:CHROMIUM (SARA 313) (CERCLA)

CAS:7440-47-3

RTECS #:GB4200000

Fraction by Wt: 1-10%

OSHA PEL:1 MG/M3

ACGIH TLV:0.5 MG/M3; 9495

EPA Rpt Qty:1 LB

DOT Rpt Qty:1 LB

Ingred Name:NICKEL (SARA 313) (CERCLA)

CAS:7440-02-0

RTECS #:QR5950000

Fraction by Wt: 0-1%

OSHA PEL:1 MG/M3

ACGIH TLV:1 MG/M3; 9495

Ingred Name:MOLYBDENUM

CAS:7439-98-7

RTECS #:QA4680000

Fraction by Wt: 0-1%

OSHA PEL:10 PPM

ACGIH TLV:10 PPM

Ingred Name:IRON

CAS:7439-89-6

RTECS #:NO4565500

Fraction by Wt: 45

-90%

OSHA PEL:10 MG/M3 (MFR)

ACGIH TLV:5 MG/M3 (MFR)

Ingred Name:TITANIUM OXIDE; (TITANIUM DIOXIDE)

CAS:13463-67-7

RTECS #:XR2275000

Fraction by Wt: 0-10%

OSHA PEL:15 MG/M3 TDUST

ACGIH TLV:10 MG/M3 TDUST; 9495

Ingred Name:CALCIUM FLUORIDE; (FLUORIDE)

CAS:7789-75-5

RTECS #:EW1760000

Fraction by Wt: 0-5%

OSHA PEL:2.5 (MFR)

ACGIH TLV:2.5 AS F (MFR)

Ingred Name:CALCIUM CARBONATE

CAS:1317-65-3

RTECS #:EV9580000

Fraction by Wt: 0-10%

OSHA PEL:15 MG/M3 TDUST

ACGIH TLV:10 MG/M3 TDUST; 9495

Ingred Na

me:GRAPHITE  
CAS:7782-42-5  
RTECS #:MD9659600  
Fraction by Wt: 0-3%  
OSHA PEL:15 MPPCF; Z-3  
ACGIH TLV:2 MG/M3 RDUST; 9495

Ingred Name:EFTS OF OVEREXP:PULM FUNCTION. LONG TERM OVEREXP TO  
MANGANESE CMPDS MAY AFFECT CNS. SYMPS INCL MUSCULAR WEAK(ING 12)  
RTECS #:9999999ZZ

Ingred Name:ING 11:& TREMORS SIMILAR TO PARKINSON'S DISEASE. BEHAVIORAL  
CHANGES & CHANGES IN HANDWRITING MAY ALSO APPEAR. (ING 13)  
RTECS #:9999999ZZ

Ingred Name:ING 12:EMPLOYEES EXPOSED TO MANGANESE CMPDS SHOULD GET  
QUAR  
TERLY MED EXAMS FOR EARLY DETECTION OF (ING 14)  
RTECS #:9999999ZZ

Ingred Name:ING 13:MANGANISM. STUDIES HAVE SHOWN THAT PRODUCTION  
WORKERS EXPOSED TO HEXAVALENT CHROMIUM CMPDS HAVE AN INCR (ING 15)  
RTECS #:9999999ZZ

Ingred Name:ING 14:INCIDENCE OF LUNG CANCER. CHROMATES MAY CAUSE AN  
ULCERATION & PERFORATION OF NASAL SEPTUM. LIVER DMG (ING 16)  
RTECS #:9999999ZZ

Ingred Name:ING 15:& ALLERGIC SKIN RASH HAVE BEEN RPTD. CHROMIUM VI  
CMPDS ARE REQ BY OSHA TO BE CONSIDERED CARCIN. LONG TE  
RM(ING 17)  
RTECS #:9999999ZZ

Ingred Name:ING 16:OVEREXP TO NICKEL CMPDS MAY CAUSE  
FIBROSIS/PNEUMOCONIOSIS. STUDIES OF NICKEL REFINERY WORKERS  
INDICATED (ING 18)  
RTECS #:9999999ZZ

Ingred Name:ING 17:A HIGHER INCIDENCE OF LUNG & NASAL CANCER. RPTD  
OVEREXP TO FLUORIDE FUMES MAY CAUSE SERIOUS BONE EROSION (ING 19)  
RTECS #:9999999ZZ

Ingred Name:ING 18:& EXCESS CALCIFICATION OF BONES & LIGAMENTS OF RIBS,  
PELVIS & SPINAL COLUMN. FLUORIDES MAY ALSO CAUSE (ING 20)  
RTECS #:9999999ZZ

In

Ingredient Name: ING 19: SKIN RASH. SHIELDING GASES SUCH AS ARGON, HELIUM & CARBON DIOXIDE ARE ASPHYXICANT & ADEQ VENT MUST BE PROVIDED. (ING 21)  
RTECS #: 9999999ZZ

Ingredient Name: ING 20: ARC RAYS: CAN INJURE EYES & BURN SKIN. HEAT RAYS (INFRARED RADIATION FROM FLAME/HOT METAL) CAN INJURE EYES. (ING 22)  
RTECS #: 9999999ZZ

Ingredient Name: ING 21: ELECTRIC SHOCK CAN KILL. NOISE CAN DAMAGE HEARING. FOR MORE SPECIFIC INFORMATION CONTACT NEHC.  
RTECS #: 9999999ZZ

Ingredient Name: HAZ DECOMP PROD: SECONDARILY COMPLEX OXIDES OF CHROMIUM, NICKEL, MOLYBDENUM & TITANIUM, CALCIUM, SODIUM & (ING 24)  
RTECS #: 9999999ZZ

Ingredient Name: ING 23: POTASSIUM. GASEOUS REACTION PRODUCTS MAY INCLUDE CARBON MONOXIDE AND CARBON DIOXIDE. OZONE AND NITROGEN (ING 25)  
RTECS #: 9999999ZZ

Ingredient Name: ING 24: OXIDES MAY BE FORMED BY THE RADIATION FROM THE ARC. FOR MORE INFORMATION, CONTACT NEHC.  
RTECS #: 9999999ZZ

===== Hazards Identification =====

LD50 LC50 Mixture: NONE SPECIFIED BY MANUFACTURER.

Routes

Routes of Entry: Inhalation: YES Skin: YES Ingestion: YES

Reports of Carcinogenicity: NTP: YES IARC: YES OSHA: NO

Health Hazards Acute and Chronic: ELECTRIC ARC WELDING/OXY FUEL WELDING MAY CREATE ONE/MORE OF THE FOLLOWING HEALTH HAZARD: FUMES & GASES-CAN BE DANGEROUS TO YOUR HEALTH. COMMON ENTRY IS BY INHALATION. ACUTE: OVEREXPOSURE TO WELDING FUMES MAY RESULT IN DISCOMFORT SUCH AS DIZZINESS, NAUSEA/DRYNESS/IRRITATION OF NOSE, THROAT/EYES. CHROMIATES PRESENT IN THE FUME CAN CAUSE EFFECTS OF OVEREXPOSURE

Explanation of Carcinogenicity:

NICKEL: IARC MONOGRAPH ON EVALUATION OF CARCINOGENIC RISK OF CHEMICALS TO MAN, VOL 49, PG 257, 1990: GROUP 2B. NTP 7TH ANNUAL REPORT ON (SUPPORTING DATA)

Effects of Overexposure: HEALTH HAZARD: CAUSE IRRITATION OF THE RESPIRATORY SYSTEM, DAMAGE TO LUNGS & ASTHMA LIKE SYMPTOMS. NICKEL COMPOUNDS IN THE FUME CAN CAUSE A METALLIC TASTE, NAUSEA, TIGHTNESS IN THE CHEST, FEVER & ALLERGIC REACTIONS. FLUORIDE CAN CAUSE PULMONARY EDEMA BRONCHITIS. CHRONIC: OVEREXPOSURE TO WELDING FUMES CAN LEAD TO SIDEROSIS (IRON DEPOSITS IN THE LUNG) & AFFECT (INGESTION)

11)

Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

=====  
First Aid Measures  
=====

First Aid:CALL FOR MEDICAL AID. EMPLOY FIRST AID TECHNIQUES RECOMMENDED BY THE AMERICAN RED CROSS. INGEST: CALL MD IMMEDIATELY . INHAL: REMOVE TO FRESH AIR. SUPPORT BREATHING (GIVE O\*2/ARTF RESP) . EYES: IMMEDIATELY FLUSH W/POTABLE WATERFOR A MINIMUM OF 15 MINUTES, SEEK ASSISTANCE FROM MD . SKIN: FLUSH W/COPIOUS AMOUNTS OF WATER.  
CAL  
L MD .

=====  
Fire Fighting Measures  
=====

Extinguishing Media:MEDIA SUITABLE FOR SURROUNDING FIRE .  
Fire Fighting Procedures:USE NIOSH APPROVED SCBA & FULL PROTECTIVE EQUIPMENT .  
Unusual Fire/Explosion Hazard:(NONFLAMM) WELDING ARC & SPARKS CAN IGNITE COMBUST & FLAMM. REFER TO AMERICAN NATIONAL STANDARD Z49.1 FOR FIRE PVNT DURING THE USE OF WELDING & ALLIED PROC.

=====  
Accidental Release Measures  
=====

Spill Release Pr  
cedures:NOT APPLICABLE.  
Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

=====  
Handling and Storage  
=====

Handling and Storage Precautions:READ AND UNDERSTAND THE MANUFACTURER'S INSTRUCTIONS & THE PRECAUTIONARY LABEL ON THE PRODUCT.  
Other Precautions:SEE AMERICAN NATIONAL STANDARD Z49.1, SAFETY IN WELDING & CUTTING PUBLISHED BY THE AMERICAN WELDING SOCIETY, P.O. BOX 351040, MIAMI, FL 33135 & OSHA PUBLICATION 2206 (29CFR1910). US GOVERNMENT  
PRINTI NG OFFICE, WASHINGTON, D.C.

=====  
Exposure Controls/Personal Protection  
=====

Respiratory Protection:USE NIOSH APPROVED RESPIRABLE FUME RESPIRATOR OR AIR SUPPLIED RESPIRATOR WHEN WELDING IN CONFINED SPACE OR WHERE LOCAL EXHAUST OR VENTILATION DOES NOT KEEP EXPOSURE BELOW TLV.  
Ventilation:USE ENOUGH VENT, LOCAL EXHAUST AT ARC/BOTH, TO KEEP FUMES & GASES BELOW TLV'S IN WORKER'S BRTHG ZONE & GENERAL AREA.  
Protective Gloves:WELDERS GLOVES.  
Eye Protection:ANSI

APPRVD CHEM WORKERS GOGGLES(SUPDAT)

Other Protective Equipment:ANSI APPRVD EMER EYE WASH & DELUGE SHOWER .

WEAR HEAD, HAND & BODY PROT WHICH HELP TO PVNT INJURY FROM (SUPDAT)

Work Hygienic Practices:TRAIN WELDER TO KEEP HEAD OUT OF FUMES, NOT TO TOUCH LIVE ELEC PARTS & INSULATE (SUPDAT)

Supplemental Safety and Health

EXPLAN OF CARCIN:CARCIN, 1994:ANTIC TO BE CARCIN. EYE PROT:& FULL LENGTH FACESHIELD W/FILTER LENS. AS A RULE OF THUMB, START W/SHADE TOO DARK TO SEE WELD ZONE. THEN

GO TO NEXT LIGHTER SHADE WHI CH

GIVES SUFF VIEW OF WELD ZONE. OTHER PROT EQUIP:RADIA, SPARKS, & ELEC SHOCK. HYGIENE PRACT:HIMSELF FROM WORK & GROUND.

===== Physical/Chemical Properties =====

HCC:T6

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:NO

NONE SPECIFIED BY MANUFACTURER.

Stability Condition to Avoid:NONE SPECIFIED BY MANUFACTURER.

Hazardous Decomposition Products:REASONABLY EXPECTED FUME CONSTITUENTS

WOULD INCL:PRIMARILY FLUORIDES & COMPLEX OXIDES OF IRON, MANGANESE & (ING 23)

===== Disposal Considerations =====

Waste Disposal Methods:PREVENT WASTE FROM CONTAMINATING SURROUNDING ENVIRONMENT. DISCARD ANY PRODUCT, RESIDUE, DISPOSABLE CONTAINER OR LINER IN AN ENVIRONMENTALLY ACCEPTABLE MANNER, IN FULL COMPLIANCE WITH FEDERAL, STATE AN D LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.