

WORLD ASPHALT COMPANY -- ASPHALT PRIMER #24 -- 5610-00-171-4722

=====
Product Identification
=====

Product ID: ASPHALT PRIMER #24
MSDS Date: 01/01/1990
FSC: 5610
NIIN: 00-171-4722
Kit Part: Y
MSDS Number: CDPFQ
=== Responsible Party ===
Company Name: WORLD ASPHALT COMPANY
Address: 10144 WATERMAN ROAD
City: ELK GROVE
State: CA
ZIP: 95624
Country: US
Info Phone Num: 916-685-2000
Emergency Phone Num: 916-685-2000
0
CAGE: 5P717
=== Contractor Identification ===
Company Name: WORLD ASPHALT CO
Address: 10144 WATERMAN RD
Box: City: ELD GROVE
State: CA
ZIP: 95624
Country: US
Phone: 916-685-2000
CAGE: 5P717

=====
Composition/Information on Ingredients
=====

Ingred Name: ASPHALT (PETROLEUM)
CAS: 8052-42-4
RTECS #: CI9900000
Fraction by Wt: 70.0%
Other REC Limits: NONE RECOMMENDED
ACGIH TLV: 5 MG/M3; (FUME); 9495

Ingred Name: MINERAL SPIRITS
CAS: 8052-41-3
RTECS #: WJ8925000
Fraction by Wt: 30.0%
Other REC Lim

its:NONE RECOMMENDED

=====
===== Hazards Identification =====

LD50 LC50 Mixture:125 PEL ESTIMATED

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:INHALATION: HEADACHE/DIZZINESS/NAUSEA.

SKIN: IRRITATION. INGESTION: MILD GI IRRITATION. RESPIRATORY TRACT IRRITATION.

=====
===== First Aid Measures =====

First Aid:INGESTION: DON'T INDUC

E VOMITING. GIVE 2 OZ OLIVE OIL, 1 OZ

ACTIVATED CHARCOAL. CALL DR. REMOVE FROM SKIN BY WIPING THEN SOAP & WATER. FLUSH EYES W/WATER.

=====
===== Fire Fighting Measures =====

Flash Point Method:TCC

Flash Point:105F,41C

Lower Limits:NA

Upper Limits:NA

Extinguishing Media:SODIUM BICARBONATE, DRY CHEMICAL.

Fire Fighting Procedures:PETROLEUM PROCEDURES.

Unusual Fire/Explosion Hazard:NONE

=====
===== Accidental Release Measures =====

Spill

Release Procedures:AVOID OPEN SPARKS/FLAMES. PROVIDE ADEQUATE

VENTILATION. ABSORB ON SAWDUST/OTHER ABSORBENT. WASH DOWN RESIDUE.

=====
===== Handling and Storage =====

Handling and Storage Precautions:DO NOT STORE NEAR OPEN FLAME OR SPARK.

PROVIDE ADEQUATE VENTILATION.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:ORGANIC CANISTER, MASK OR AIR PACK REQUIRED.

Ventilation:LOCAL EXHAUST.

Protective Gloves:PLASTIC

OR RUBBER AS REQUIRED
Eye Protection:CONVENTIONAL
Other Protective Equipment:NONE
Supplemental Safety and Health
NK

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:314F,157C
Vapor Pres:NA
Vapor Density:1.0
Spec Gravity:0.9
Evaporation Rate & Reference:NA
Solubility in Water:NONE
Appearance and Odor:BLACK LIQUID, SOLVENT ODOR
Percent Volatiles by Volume:35.0

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
NK
Hazardous Decomposition Products:CO, CO2.

===== Disposal Considerations =====

Waste Disposal Methods:STANDARD TRASH DISPOSAL. PLACE IN CONTAINER.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.