Box:KK

City:FAIRFIELD

State:CA

ZIP:94533-0659 Country:US

Info Phone Num :707-422-1880

Emergency Phone Num:707-422-1880

Preparer's Name: S SCHOOLFIELD/J KOHRING

CAGE:17610

=== Contractor Identification ===

Company Name: OEA AEROSPACE INC

Address:3530 BRANSCOMBE RD

Box:KK

City:FAIRFIELD

State:CA

ZIP:94533-0659 Country:US

Phone:707-422-1880

CAGE:17610

======= Composition/Information on Ingredients ========

Ingred Name: X-CHORD, 2.5 GRAINS/FT, SILVER SHEATH

ACGIH TLV:0.1 MG/CUM

Ingred Name: HEXANITROSTILBENE I

ACGIH TLV:10.0 MG/CUM

======= Ha

zards Identification ===========
Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:INHALATION: IRRITATION TO THE NOSE, THROAT & MUCOUS MEMBRANE, ALLERGIC REACTIONS. SKIN: IRRITATION & ABSORPTION, ALLERGIC REACTIONS. EYES: IRRITATION. INGESTION: TOXIC, MAY CAUSE DEATH. Explanation of Carcinogenicity:NONE Effects of Overexposure:IRRITATION, NAUSEA, REDNESS.
First Aid Measures ====================================
First Aid:EYES: FLUSH W/WATER FOR 15 MINS. SKIN: WASH W/SOAP & WATER. INHALATION: REMOVE TO FRESH AIR. OBTAIN MEDICAL ATTENTION IN ALL CASES.
======================================
Fire Fighting Procedures:DON'T ATTEMPT TO EXTINGUISH. EVACUATE AREA. USE SCBA TO CONTAIN RESULTING FIRE. Unusual Fire/Explosion Hazard:IF EXPOSED TO FIRE, THE UNIT MAY ACTUATE/EXPLODE.
========= Accidental Release Measures ====================================
Spill Release Procedures:CALL LOCAL HAZARDOUS MATERIALS TEAM. REMOVE IGNITION SOURCES. COVER ANY EXPOSED MATERIAL W/VEGETABLE OIL & REMOVE FOR APPROVED DISPOSAL. USE FLAME RETARDANT CLOTHING, SAFETY GLASSES & NON-SPARKING TOO LS.
======================================
Handling and Storage Precautions:ANTI-STATIC ARE TO BE USED FOR STORAGE & SHIPPING.
Other Precautions:THIS MSDS ISN'T INTENDED TO BE AN ORDNANCE HANDLING DOCUMENT.
====== Exposure Controls/Personal Protection ========
Respiratory Protection:USE A NIOSH APPROVED HEPA RESPIRATOR IF PEL/TLV IS EXCEEDED. Ventilation:LOCAL EXHAUST: REQUIRED FOR TEST FIRING. Protective Gloves:POLY-BENZ IMMIDAZOLE/LEATHER FOR CLEANUP Eye Protection:SAFETY GLASSES AS A MINIMUM Other Protective Equipment:FLAME RETARDANT COAT & GROUNDING STRAPS TO PREVENT ELECTROSTATIC DISCHARGE. Supplemental Safety and Health ===================================

========== Stability and Reactivity Data =========
Stability Indicator/Materials to Avoid:YES ALKALIS, ACIDS, BRONZE, CORROSIVES & OXIDIZERS. Stability Condition to Avoid:MECHANICAL SHOCK, STATIC ELECTRICITY, HEAT, FLAME/SPARKS.
Hazardous Decomposition Products:CO, NITROGEN, NITROUS OXIDES, HYDROGEN, CARBON, CO2 & WATER.

====== Disposal Considera tions ==========

cal Properties ========

Appearance and Odor:SMDC: SILVER; ODORLESS

Solubility in Water: INSOLUBLE

Waste Disposal Methods:UNFIRED UNITS/WASTE SHOULD BE DISPOSED AS REACTIVE (D003) & TOXIC (D011) HAZARDOUS WASTE, IAW/FEDERAL, STATE & LOCAL REGULATIONS. UN-0367.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liabili

ty for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.