

GIBSON-HOMANS CO -- FIBERED ROOF COATING -- 5610-00-171-4722

===== Product Identification =====

Product ID:FIBERED ROOF COATING

MSDS Date:10/10/1990

FSC:5610

NIIN:00-171-4722

MSDS Number: CDVFP

=== Responsible Party ===

Company Name:GIBSON-HOMANS CO

Address:1755 ENTERPRISE PARKWAY

City:TWINSBURG

State:OH

ZIP:44087

Country:US

Info Phone Num:216-425-3255 OR 216-467-8128

Emergency Phone Num:216-425

-3255 OR 216-467-8128

CAGE:33394

=== Contractor Identification ===

Company Name:GIBSON-HOMANS CO

Address:1623 E EUCLID AVE

Box:City:DES MOINES

State:IA

ZIP:50316

Country:US

Phone:515-262-9396

CAGE:33394

===== Composition/Information on Ingredients =====

Ingred Name:MINERAL SPIRITS

CAS:8052-41-3

RTECS #:WJ8925000

Fraction by Wt: 40-70%

Other REC Limits:NONE SPECIFIED

OSHA PEL:100 PPM

ACGIH TLV:100 PPM

Ingred Name:VOC = >300 G/L

RTECS #:9999999VO

Other REC Limits:NONE RECOMM

ENDED  
OSHA PEL:NOT EST.

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES  
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Health Hazards Acute and Chronic:ACUTE-SKIN: MAY CAUSE IRRITATION.  
EYES: MAY CAUSE IRRITATIONBLURRED VISION. INHAL: EXCESSIVE  
BREATHING OF HIGH VAPOR CONCENTRATIONS CAN CAUSE NASAL &  
RESPIRATORY IRRITATION, DIZZINESS, NAUSEA, POSSIBL E  
UNCONSCIOUSNESS, ASPHYXIATION. INGEST: CAN  
CAUSE GI IRRIT, NAUSEA,  
VOMIT, DIARRHEA.

===== First Aid Measures =====

First Aid:SKIN: WASH WITH SOAP & WATER. EYES: FLUSH WITH LARGE AMOUNTS  
OF WATER. INHAL: REMOVE FROM AFFECTED AREA. IF BREATHING IS  
DIFFICULT, GIVE OXYGEN. IF BREATHING HAS STOPPED, GIVE ARTIF RESP.  
INGEST: DONT INDUCE VOMIT. SEE A DOCTOR IMMEDIATELY.

===== Fire Fighting Measures =====

Flash Point Method:PMCC  
Flash Point:105F,41C  
Lowe  
r Limits:0.8  
Upper Limits:7.0  
Extinguishing Media:USE CARBON DIOXIDE, FOAM, OR DRY CHEMICAL.  
Fire Fighting Procedures:WEAR A SELF CONTAINED BREATHING APPARATUS.  
WATER MAY CAUSE FROTHING, APPLY CAUTIOUSLY.  
Unusual Fire/Explosion Hazard:KEEP AWAY FROM SOURCES OF IGNITION.

===== Accidental Release Measures =====

Spill Release Procedures:DIKE SPILL AREA. RECOVER FREE LIQUID. ADD  
ABSORBENT TO SPILL AREA. REMOVE SOURCES OF IGNITION. VENTILATE AREA  
IF NEEDED.

N

neutralizing Agent:NA

===== Handling and Storage =====

Handling and Storage Precautions:KEEP AWAY FROM IGNIT SOURCES. USE ONLY WITH ADEQUATE VENT. AVOID PROLONGED/REPEATED CONTACT W/SKIN.  
Other Precautions:KEEP OUT OF REACH OF CHILDREN.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:IF TLV IS EXCEEDED, USE NIOSH/MSHA APPROVED BREATHING APPARATUS.  
Ventilation:MAINTAIN EXPOSURE BELOW TLV LEVEL.  
Protective Gloves:SOLVENT RESISTANT.  
Eye Protection:CHEMICAL GOGGLES.  
Other Protective Equipment:NA  
Work Hygienic Practices:REMOVE CONTAMINATED CLOTHING. LAUNDER BEFORE REUSE.  
Supplemental Safety and Health  
NK

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:300 TO 315F  
Vapor Pres:2MM  
Vapor Density:>1  
Spec Gravity:1.0  
pH:NA  
Evaporation Rate & Reference: