

HENTZEN COATINGS, INC -- OLIVE DRAB HIGH SOLIDS HEAT RESISTANT COATING #02366GML --
8010-00-616-4009

=====
Product Identification
=====

Product ID:OLIVE DRAB HIGH SOLIDS HEAT RESISTANT COATING #02366GML

MSDS Date:02/14/1996

FSC:8010

NIIN:00-616-4009

MSDS Number: CDVLL

=== Responsible Party ===

Company Name:HENTZEN COATINGS, INC

Address:6937 WEST MILL ROAD

City:MILWAUKEE

State:WI

ZIP:53218

Country

:US

Info Phone Num:414-353-4200

Emergency Phone Num:414-353-4200/CHEMTREC 800-424-9300

Preparer's Name:JANE FREEMAN

CAGE:09225

=== Contractor Identification ===

Company Name:HENTZEN COATINGS INC

Address:6937 WEST MILL ROAD

Box:18749

City:MILWAUKEE

State:WI

ZIP:53218

Country:US

Phone:414-353-4200

CAGE:09225

=====
Composition/Information on Ingredients
=====

Ingred Name:BUTYL ALCOHOL SOLVENT (SARA III)

CAS:71-36-3

RTECS #:EO1400000

Fraction by Wt: 3.442%

Other REC Limits:NONE R

ECOMMENDED
OSHA PEL:50 PPM (CEILING)
ACGIH TLV:50 PPM (CEILING)
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:TITANIUM DIOXIDE PIGMENT
CAS:13463-67-7
RTECS #:XR2275000
Fraction by Wt: 10-15%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:10 MG/M3
ACGIH TLV:10 MG/M3

Ingred Name:TALC PIGMENT
CAS:14807-96-6
RTECS #:WW2710000
Fraction by Wt: 1-5%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:2 MG/M3
ACGIH TLV:2 MG/M3

Ingred Name:NICKEL COMPOUNDS (INSOLUBLE COMPOUNDS) (SARA III)
CAS:7440-02-0
RTE
CS #:QR5950000
Fraction by Wt: 0.658%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:1 MG/M3
ACGIH TLV:1 MG/M3

Ingred Name:ISOBUTYL ALCOHOL SOLVENT (SARA III)
CAS:78-83-1
RTECS #:NP9625000
Fraction by Wt: 1.159%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:50 PPM
ACGIH TLV:50 PPM
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:ETHYL BENZENE SOLVENT (SARA III)
CAS:100-41-4
RTECS #:DA0700000
Fraction by Wt: 2.044%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:100 PPM;STEL 125 PPM
ACGIH TLV:100 PPM;

STEL 125 PPM
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:XYLENE SOLVENT (SARA III)
CAS:1330-20-7
RTECS #:ZE2100000
Fraction by Wt: 18.617%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:100 PPM;STEL 150 PPM
ACGIH TLV:100 PPM;STEL 150 PPM
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:SILICEOUS EXTENDER PIGMENT
CAS:66402-68-4
Fraction by Wt: 1-5%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:15 MG/M3
ACGIH TLV:10 MG/M3

Ingred Name:MICA PIGMENT
CAS:12001-26-2
RTECS #:VV8760000
Fraction
by Wt: 5-10%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:20 MPPCF
ACGIH TLV:3 MG/M3 (RESP DUST)

Ingred Name:BARIUM COMPOUND
Fraction by Wt: 1.937%
Other REC Limits:NUISANCE DUST

Ingred Name:FRITS
Fraction by Wt: 15-20%
Other REC Limits:NUISANCE DUST

Ingred Name:AROMATIC HYDROCARBONS (MIXTURE OF C8'S TO C10'S)
CAS:64742-95-6
Fraction by Wt: 1.846%
Other REC Limits:MFR'S LIMIT: 100 PPM

Ingred Name:TRIVALIENT CHROME (INSOLUBLE) (SARA 313) (CERCLA)
CAS:7440-47-3
RTECS #:GB4200000
Fraction by W

t: 7.079%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:0.5 MG/M3
ACGIH TLV:0.5 MG/M3
EPA Rpt Qty:1 LB
DOT Rpt Qty:1 LB

=====
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:NO
Health Hazards Acute and Chronic:INHAL: ANESTHETIC. RESPIRATORY TRACT
IRRITATION OR ACUTE NERVOUS SYSTEM DEPRESSION (HEADACHE, DIZZINESS,
STAGGERING, CONFUSION OR COMA). SKIN: IRRITATION, DE
FATTING,
DERMATITIS. EYE: IRRITATION. CHRON IC: BRAIN/NS/LIVER/KIDNEY
DAMAGE, DERMATITIS, DELAYED RESPIRATORY SYSTEM EFFECTS.
Explanation of Carcinogenicity:IARC & NTP LIST NICKEL AS PROBABLY
CARCINOGENIC TO HUMAN.
Medical Cond Aggravated by Exposure:ASTHMA AND OTHER RESPIRATORY
AILMENTS; CHEMICAL SENSITIZATION.

=====
===== First Aid Measures =====

First Aid:INHAL: REMOVE FROM EXPOSURE. RESTORE BREATHING. KEEP WARM &
QUIET. NOTIFY A PHYSICIAN
. EYES: FLUSH IMMEDIATELY WITH LARGE
AMOUNTS OF RUNNING WATER FOR AT LEAST 15 MINUTES. LIFT LIDS. TAKE
TO PHYSICIAN FOR MEDICAL TREATMENT. SKIN: WASH WITH SOAP & WATER.
REMOVE CONTAM CLOTHES, WASH BEFORE REUSE, CALL DR. INGEST: CALL
DR/POISON CONTROL CENTER IMMED.

=====
===== Fire Fighting Measures =====

Flash Point Method:TCC
Flash Point:81.0F,27.2C
Autoignition Temp:Autoignition Temp Text:NA
Lower Limits:1.0
Upper Limits:11.2
Extinguishing Media:FO

AM, DRY CHEMICAL, CO2

Fire Fighting Procedures:WEAR PROTECT EQUIP INCLUDING SCBA. WATER MAY BE INEFFECTIVE, USE WATER (FOG NOZZLES PREFERRED) COOL CLOSED CNTNR TO PREVENT PRESSURE BLDUP,AUTOIGNITN,EXPLOSION.

Unusual Fire/Explosion Hazard:KEEP CONTAINER TIGHTLY CLOSED. KEEP FROM HEAT/IGNIT SOURCE. CLOSED CNTNR MAY EXPLODE W/HEAT. DON'T APPLY TO HOT SRFCS. NEVER USE WELD/CUT TORCH ON/NEAR DRUM.

===== Accidental Release Measures =====

Spill Release Proc

edures:REMOVE ALL SOURCES OF IGNITION. VENTILATE AREA. USE APPROPRIATE PROTECTIVE EQUIPMENT. AVIOD BREATHING VAPORS/SKIN CONTACT. PREVENT ENTRY TO DRAINS/SEWERS/WATERWAYS. NOTIFY AUTHORITIES. CONTAIN & REMOV E WITH INERT ABSORBENT AND NONSPARKING TOOLS.

===== Handling and Storage =====

Handling and Storage Precautions:DONT STORE @>120F. LARGE AMTS IN BUILDINGS DESIGNED (OSHA 1910.106). NO IGNITS. KEEP CLOSED/UPRIGHT/TIGHT WHEN NOT IN U SE. EMPTY CNTNR HAZARDOUS.

Other Precautions:SOAK SOILED RAGS/WASTES IN H2O FILLED CLOSED CNTNR. USE W/ADEQUATE VENT, AVOID VAPOR BREATHING/SKIN CONTACT, GROUND/BOND WHEN TRANSFERRING, AVOID FREEFALL OF LIQ >FEW INCHES, USE SPARKPROOF TOOLS/EXPL OSION PROOF EQUIPMENT.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:OUTDOOR/SANDING/GRINDING: NIOSH MECHANICAL FILTER RESPRTR. CONFINED AREA: NIOSH AIR SUPPLIED RESPIRATOR/HOOD. AIR MONI

TORING MAY BE REQUIRED.

Ventilation:GENERAL DILUTION/LOCAL EXHAUST TO KEEP BELOW PEL/TLV.

Protective Gloves:CHENICAL RESISTANT

Eye Protection:SAFETY EYEWEAR W/SPLASH GUARDS/SIDE SHLD

Other Protective Equipment:APPROPRIATE TO PREVENT PROLONGED SKIN CONTACT.

Work Hygienic Practices:WASH HANDS BEFORE EATING OR SMOKING. SMOKE IN DESIGNATED SMOKING AREAS ONLY.

Supplemental Safety and Health
MORE INFORMATION ON FILE.

===== Physical/Chemical Properties =====

Boilin

g Pt:B.P. Text:220 TO 418F
Melt/Freeze Pt:M.P/F.P Text:NA
Vapor Pres:9.00 @ 68F
Vapor Density:> AIR
Spec Gravity:1.41
pH:NA
VOC Grams/Liter:3.38
Evaporation Rate & Reference:SLOWER THAN BUTYL ACETATE
Solubility in Water:NEGLIGIBLE
Appearance and Odor:OPAQUE LIQUID, SOLVENT ODOR

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
STRONG OXIDIZERS
Hazardous Decomposition Products:MAY PRODUCE HAZARDOUS FUMES WHEN
HEATED TO DECOMPO
SITION AS IN WELDING. MAY CONTAIN CARBON MONOXIDE
& CARBON DIOXIDE.

===== Disposal Considerations =====

Waste Disposal Methods:RECYCLE OR INCINERATE IN ACCORDANCE WITH LOCAL,
STATE, & FEDERAL REGULATIONS.

===== Other Information =====

=====

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use
by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.