View NSN Online: https://aerobasegroup.de/nsn/8040-00-273-8697

CLIFTON ADHESIVE INC. -- FA1076 ADHESIVE, RUBBER BASE, GENERAL PURPOSE 8040-00-273-8697

============= Product Identification =================

Product ID:FA1076 ADHESIVE, RUBBER BASE, GENERAL PURPOSE

MSDS Date:03/09/1995

FSC:8040

NIIN:00-273-8697

MSDS Number: CDXRR === Responsible Party ===

Company Name: CLIFTON ADHESIVE INC.

Address:BURGESS PLACE

City:WAYNE State:NJ ZIP:07470 Country:US

CAGE:79833 === Contractor I

dentification ===

Company Name: CLIFTON ADHESIVE INC

Address:BURGESS PL

Box:City:WAYNE

State:NJ ZIP:07470 Country:US

Phone:201-694-0845; 973-694-0845

CAGE:79833

Company Name: RALRUBE INC.

Address:36977 FOX GLEN Box:City:FARMINGTON HILLS

State:MI ZIP:48331 Country:US

Phone:248-661-0260, FAX 248-661-3941

CAGE:6X798

======= Composition/Information on Ingredients ========

Ingred Name:METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA 313) (CERCLA)

CAS:78-93-3

RTECS #:EL6475000

Fraction by Wt:

65.0%

Other REC Limits: NONE RECOMMENDED

OSHA PEL:200 PPM ACGIH TLV:200 PPM EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS

Ingred Name: TETRAHYDROFURAN (CERCLA)

CAS:109-99-9

RTECS #:LU5950000 Fraction by Wt: 4.0%

Other REC Limits: NONE RECOMMENDED

OSHA PEL:200 PPM ACGIH TLV:200 PPM EPA Rpt Qty:1000 LBS DOT Rpt Qty:1000 LBS

Ingred Name: METHYL ISOBUTYL KETONE (HEXONE) (SARA 313) (CERCLA)

CAS:108-10-1

RTECS #:SA9275000 Fraction by Wt: 4.0%

Other REC Limits: NONE RECOMMENDED

OSHA PEL:50 PPM ACGIH TLV:50

PPM

EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS

Ingred Name: ACRYLONITRILE BUTADIENE POLYMER

CAS:9003-18-3

Other REC Limits: NONE RECOMMENDED

Ingred Name:TRADESECRET #1397250002-5004P

Other REC Limits: NONE RECOMMENDED

========= Hazards Identification ==============

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic: ACUTE: NAUSEA/NARCOSIS. CHRONIC:

LIVER/KIDNEY DAMAGE/NS DAMAGE. WE

AKNESS IN HANDS/FEET. LIVER/KIDNEY ABNORMALITIES
Medical Cond Aggravated by Exposure:RESPIRATORY AILMENTS, LIVER/KIDNEY INJURIES.
======================================
First Aid:SKIN: WASH W/SOAP & WATER. CALL DR. EYE: FLUSH ABUNDANTLY W/CLEAN WATER. CALL DR. INGESTION: DON'T INDUCE VOMITING. CALL DR. INHALATION: MOVE TO FRESH AIR OR GIVE OXYGEN. USE CPR IF NEEDED. CALL DR.
======================================
Flash Point Method:OC Flash Point:4F,-16C Autoignition Temp:Autoignition Temp Text:610F Lower Limits:1.4 Upper Limits:11.8
Extinguishing Media:CO2, FOAM, DRY CHEMICAL. Fire Fighting Procedures:NIOSH/MSHA APPROVED SCBA. USE WATER SPRAY TO COOL FIRE-EXPOSED STRUCTURES/DISPERSE VAPORS. Unusual Fire/Explosion Hazard:VAPORS HEAVIER THAN AIR. MAY TRAVEL LONG DISTANCES TO IGNITION SOURCES & FLASH BACK.
========= Accidental Release Measures ==========
Spill Release Procedur es:ABSORB/SHOVEL INTO STEEL CONTAINER & COVER.
============= Handling and Storage =============
Handling and Storage Precautions:KEEP CONTAINERS TIGHTLY CLOSED. STORE IN APPROVED SOLVENT STORAGE AREA. KEEP AWAY FROM IGNIT SOURCES/OXIDIZING AGENTS. Other Precautions:NA
====== Exposure Controls/Personal Protection ========
Respiratory Protection:USE NIOSH APPROVED ATMOSPHERE-SUPPLYING OR AIR-PURIFYING RESPIRATOR FOR ORGANIC VAPORS. Ventilation:LOCAL

Eye Protection:SAFETY GLASSES Other Protective Equipment:PROTECTIVE CLOTHING AS REQUIRED TO PREVENT SKIN CONTACT.
Work Hygienic Practices:KEEP AREA CLEAN. CLEAN SPILLS IMMEDIATELY. PRACTICE GOOD PERSONAL HYGIENE.
Supplemental Safety and Health NK
========= Physical/Chemical Properties ==========
Boiling Pt:B.P. Text:132F,56C Vapor Pres:71.3 Vapor Density:2.55 Spec Gravity:0.867 VOC Grams/Liter:5.4
3 Appearance and Odor:LIGHT AMBER, SWEET PUNGENT ODOR
========= Stability and Reactivity Data =========
Stability Indicator/Materials to Avoid:YES NA Stability Condition to Avoid:HEAT. Hazardous Decomposition Products:OXIDES OF CARBON, NITROGEN, ZINC,
SULFUR, HYDROGEN CHLORIDE
======== Disposal Considerations ===========
Waste Disposal Methods:ACCORDING TO FEDERAL/STATE/LOCAL CHEMICAL/SOLVENT REGULATIONS.
======================================
Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this

EXHAUST OR MECHANICAL EXHAUST, EXPLOSION PROOF.

Protective Gloves:PBA

document should seek competent professional advice to verify and assume responsibility for the suitability of this informat

ion to their particular situation.