

CLIFTON ADHESIVE INC. -- FA1053 ADHESIVE, RUBBER BASE, GENERAL PURPOSE --
8040-00-281-1972

=====
Product Identification
=====

Product ID:FA1053 ADHESIVE, RUBBER BASE, GENERAL PURPOSE

MSDS Date:02/06/1995

FSC:8040

NIIN:00-281-1972

MSDS Number: CDXRS

=== Responsible Party ===

Company Name:CLIFTON ADHESIVE INC.

Address:BURGESS PLACE

City:WAYNE

State:NJ

ZIP:07470

Country:US

CAGE:79833

=== Contractor

Identification ===

Company Name:CLIFTON ADHESIVE INC

Address:BURGESS PL

Box:City:WAYNE

State:NJ

ZIP:07470

Country:US

Phone:201-694-0845; 973-694-0845

CAGE:79833

Company Name:RALRUBE INC.

Address:36977 FOX GLEN

Box:City:FARMINGTON HILLS

State:MI

ZIP:48331

Country:US

Phone:248-661-0260, FAX 248-661-3941

CAGE:6X798

=====
Composition/Information on Ingredients
=====

Ingred Name:HEXANE (N-HEXANE) (CERCLA)

CAS:110-54-3

RTECS #:MN9275000

Fraction by Wt: 60.0%

Other REC Limits:NONE R

ECOMMENDED
OSHA PEL:50 PPM
ACGIH TLV:50 PPM
EPA Rpt Qty:1 LB
DOT Rpt Qty:1 LB

Ingred Name:STYRENE POLYMER WITH 1,3-BUTADIENE
CAS:9003-55-8
RTECS #:WL6478000
Other REC Limits:NONE RECOMMENDED

Ingred Name:NATURAL RUBBER
CAS:9006-04-6
Other REC Limits:NONE RECOMMENDED

Ingred Name:RESIN
Other REC Limits:NONE RECOMMENDED
OSHA PEL:NOT EST.
ACGIH TLV:NOT EST.

Ingred Name:TRADESECRET #1397250002-5053P
Other REC Limits:NONE RECOMMENDED

=====
===== Hazards Identification =====
=====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:ACUTE: NAUSEA &/OR NARCOSIS. CHRONIC:
MAY CAUSE NERVE DAMAGE. CNS EFFECTS. MAY DAMAGE PERIPHERAL NERVE
TISSUE. EYE: IRRITATION. INHALATION: MUCOUS MEMBRANE IRRITATION.
SKIN: DRYNESS. INGEST: VOMIT. NU MBNESS/TINGLING/WEAKNESS IN
ARMS/LEGS.
Medical Cond Aggravated by Exposure:RESPIRATORY AILMENTS.

=====
===== First Aid M
asures =====

First Aid:SKIN: WASH W/SOAP & WATER. CALL DR. EYE: FLUSH ABUNDANTLY
W/CLEAN WATER. CALL DR. INGESTION: DON'T INDUCE VOMITING. CALL DR.
INHALATION: MOVE TO FRESH AIR OR GIVE OXYGEN. USE CPR IF NEEDED.
CALL DR.

=====
===== Fire Fighting Measures =====

Flash Point Method:TCC
Flash Point:-25F,-32C
Autoignition Temp:Autoignition Temp Text:510F
Lower Limits:1.0
Upper Limits:7.5
Extinguishing Media:CO2, FOAM, DRY CHEMICAL.
Fire

Fighting Procedures:NIOSH/MSHA APPROVED SCBA. USE WATER SPRAY TO COOL FIRE-EXPOSED STRUCTURES/DISPERSE VAPORS.
Unusual Fire/Explosion Hazard:VAPORS HEAVIER THAN AIR. MAY TRAVEL LONG DISTANCES TO IGNITION SOURCES & FLASH BACK.

===== Accidental Release Measures =====

Spill Release Procedures:ABSORB/SHOVEL INTO STEEL CONTAINER & COVER.

===== Handling and Storage =====

Handling and Storage Precautions:KEEP CONTAINERS TIGHTLY CLOSED. STORE IN APPROVED SOLVENT STORAGE AREA. KEEP AWAY FROM IGNIT SOURCES/OXIDIZING AGENTS.

Other Precautions:NA

===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE NIOSH APPROVED ATMOSPHERE-SUPPLYING OR AIR-PURIFYING RESPIRATOR FOR ORGANIC VAPORS.

Ventilation:LOCAL EXHAUST OR MECHANICAL EXHAUST, EXPLOSION PROOF.

Protective Gloves:PBA

Eye Protection:SAFETY GLASSES

Other Protective Equipment:PROTECTIVE CLOTHING AS REQUIRED TO PREVENT

SKIN CONTACT.

Work Hygienic Practices:KEEP AREA CLEAN. CLEAN SPILLS IMMEDIATELY. PRACTICE GOOD PERSONAL HYGIENE.

Supplemental Safety and Health

NK

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:132F,56C

Vapor Pres:125.0

Vapor Density:3.0

Spec Gravity:0.816

VOC Grams/Liter:3.9

Appearance and Odor:AMBER, MILD HYDROCARBON ODOR

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

NA

Stabili

ty Condition to Avoid:HEAT.

Hazardous Decomposition Products:OXIDES OF CARBON

===== Disposal Considerations =====

Waste Disposal Methods:ACCORDING TO FEDERAL/STATE/LOCAL
CHEMICAL/SOLVENT REGULATIONS.

===== Other Information =====

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no m
anner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.