

CLIFTON ADHESIVE INC. -- 1460, 2020 - OIL BASED CAULK -- 8030-00-577-4740

=====
Product Identification
=====

Product ID:1460, 2020 - OIL BASED CAULK

MSDS Date:10/12/1990

FSC:8030

NIIN:00-577-4740

MSDS Number: CDXSQ

=== Responsible Party ===

Company Name:CLIFTON ADHESIVE INC.

Address:BURGESS PLACE

City:WAYNE

State:NJ

ZIP:07470

Country:US

CAGE:79833

=== Contractor Identification ===

Company Name:CL

IFTON ADHESIVE INC

Address:BURGESS PL

Box:City:WAYNE

State:NJ

ZIP:07470

Country:US

Phone:201-694-0845; 973-694-0845

CAGE:79833

Company Name:RALRUBE INC.

Address:36977 FOX GLEN

Box:City:FARMINGTON HILLS

State:MI

ZIP:48331

Country:US

Phone:248-661-0260, FAX 248-661-3941

CAGE:6X798

=====
Composition/Information on Ingredients
=====

Ingred Name:MINERAL SPIRITS

CAS:8052-41-3

RTECS #:WJ8925000

Fraction by Wt: 3-7.0%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:100 PPM

ACGIH TLV:100 P

PM

Ingred Name:VOC = 130 G/L MAXIMUM
RTECS #:9999999VO
Other REC Limits:NONE RECOMMENDED
OSHA PEL:NOT RELEVANT
ACGIH TLV:NOT RELEVANT

=====
Hazards Identification
=====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:CHRONIC: SKIN: DERMATITIS. ACUTE:
SKIN: IRRITATION. EYE: SLIGHT IRRITATION. INHAL: HEADACHE,
DIZZINESS, NAUSEA. INGEST: NAUSEA, VOMIT, HEADACHE
, DIZZINESS.
Medical Cond Aggravated by Exposure:PREEXISTING LUNG & SKIN DISORDERS.

=====
First Aid Measures
=====

First Aid:SKIN: WASH W/SOAP & WATER. EYES: FLUSH W/LARGE AMOUNTS OF
WATER. INHAL: REMMOVE TO FRESH AIR, IF BREATHING IS DIFFICULT, GIVE
OXYGEN, IF BREATHING STOPPED, GIVE ARTIFICIAL RESPIRATION, GET MED
AID. IN GEST: DO NOT INDUCE VOMIT, CALL DR. IMMED.

=====
Fire Fighting Measures
=====

Flash Po
int Method:PMCC
Flash Point:105F,41C
Autoignition Temp:Autoignition Temp Text:254F
Lower Limits:.8
Upper Limits:7.0
Extinguishing Media:FOAM, CARBON DIOXIDE, DRY CHEMICAL.
Fire Fighting Procedures:WATER MAY CAUSE FROTHING, APPLY CAUTIOUSLY.
Unusual Fire/Explosion Hazard:NA

=====
Accidental Release Measures
=====

Spill Release Procedures:DIKE, ADD ABSORBENT, REMOVE IGNITION SOURCES,
VENT AREA.

=====
Handling and Storage
=====

Handling and Storage Precautions:KEEP AWAY FROM IGNITS, STORE IN COOL,
DRY AREA, KEP CONTAINER CLOSED WHEN NOT IN USE, USE W/ADEQUATE
VENT, AVOID CHRONIC SKIN CONTACT.

Other Precautions:KEEP AWAY FROM CHILDREN.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:NOT NORMALLY REQUIRED, NIOSH/MESA APPROVED
BREATHING APPARATUS RECOMMENDED IF TLV EXCEEDED.

Ventilation:AS NECESSARY TO MAINTAIN EXPOSURE BELOW TLV.

Protective Gloves:SOLVENT RESISTANT

Eye Protection:NOT NORMALLY NEEDED.

Other Protective Equipment:SOLVENT RESISTANT APRON & BOOTS.

Work Hygienic Practices:REMOVE CONTAM CLOTHES, LAUNDER BEFORE REUSE.

Supplemental Safety and Health

NK

=====
===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:300 TO 315F

Melt/Freeze Pt:M.P/F.P Text:NA

Vapor Pres:2.0

Vapor Density:>1.0

Spec Gravity:1.6

pH:NE

Evaporation Rate & Reference:>1 (BUAC)

Solubility in Water:INSOLUBLE

Appearance and Odor:LIGHT COLORED

PAST, SLIGHT SOLVENT ODOR

Percent Volatiles by Volume:30-40

=====
===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

HEAT, STRONG OXIDIZERS.

Hazardous Decomposition Products:CARBON DIOXIDE, CARBON MONOXIDE.

=====
===== Disposal Considerations =====

Waste Disposal Methods:IN ACCORDANCE W/FEDERAL/STATE/LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is f

ormulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.