

CAL WESTERN PAINTS, INC. -- PROTECTIVE TOP COAT SPI-3 -- 8010-01-367-2377

=====  
Product Identification  
=====

Product ID:PROTECTIVE TOP COAT SPI-3

MSDS Date:05/01/1996

FSC:8010

NIIN:01-367-2377

Kit Part:Y

MSDS Number: CDZZT

=== Responsible Party ===

Company Name:CAL WESTERN PAINTS, INC.

Address:11748 SLAUSON AVENUE

City:SANTA FE SPRINGS

State:CA

ZIP:90670

Country:US

Info Phone Num:310-693-0872

Emer

gency Phone Num:310-693-0872

Preparer's Name:JOHN WALTMAN

CAGE:4B672

=== Contractor Identification ===

Company Name:CAL WESTERN PAINTS,INC

Address:11748 SLAUSON AVE

Box:City:SANTA FE SPRINGS

State:CA

ZIP:90670

Country:US

Phone:213-723-6362

CAGE:4B672

Company Name:PLATINUM SOUND INNOVATIONS, INC.

Box:UNKNOW

CAGE:0ZJN1

=====  
Composition/Information on Ingredients  
=====

Ingred Name:ETHYLENE GLYCOL (SARA 313) (CERCLA)

CAS:107-21-1

RTECS #:KW2975000

Fraction by Wt: 2.0%

Other REC

Limits:NONE RECOMMENDED

ACGIH TLV:50 PPM

EPA Rpt Qty:1 LB

DOT Rpt Qty:1 LB

Ingred Name:ESTER ALCOHOL

CAS:25265-67-7

Fraction by Wt: 1.0%

Other REC Limits:NONE RECOMMENDED

=====  
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:INHAL: IRRITATION OF MUCOUS MEMBRANES  
OF NOSE/THROAT/RESPIRATORY TRACT. HEADACHE, NAUSEA. EYE:  
IRRITATION.

SKIN: IRRITATION, ABSORPTION, (RED, DRY, CONTACT  
DERMATITIS). INGEST: GI IRRITATION, NAUSEA, VOMITING DIARRHEA.  
CHRONIC: PERMANENT BRAIN/NERVOUS SYSTEM DAMAGE.

=====  
===== First Aid Measures =====

First Aid:EYE: FLUSH W/LARGE AMOUNTS OF WATER FOR AT LEAST 15 MINUTES,  
CALL DR. SKIN: WASH W/SOAP & WATER. REMOVE CONTAM CLOTHES, WASH  
BEFORE REUSE, CALL DR. INHAL: GET FRESH AIR. TREAT SYMPTOMATICALLY,  
CALL DR. INGEST: DRINK 1-2 GLASSES WATER TO  
DILUTE. DONT INDUCE  
VOMIT. CALL DR/POISON CONTROL CENTER. TREAT SYMPTOMATICALLY.

=====  
===== Fire Fighting Measures =====

Flash Point:NONE

Autoignition Temp:Autoignition Temp Text:NA

Lower Limits:0.6

Upper Limits:4.2

Extinguishing Media:FOAM, CO2, DRY CHEMICAL, WATER FOG.

Fire Fighting Procedures:COOL CONTAINER W/WATER SPRAY.

Unusual Fire/Explosion Hazard:CLOSED CONTAINER MAY EXPLODE FROM STEAM  
PRESSURE.

=====  
===== Accidental Release Measures ===

=====

Spill Release Procedures:DIKE, ABSORB. CONTAINERIZE.

Neutralizing Agent:NA

===== Handling and Storage =====

Handling and Storage Precautions:DONT EXPOSE TO EXTREME TEMPERATURES OR  
ALLOW TO FREEZE.

Other Precautions:KEEP OUT OF REACH OF CHILDREN.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE NIOSH/MSHA APPROVED ORGANIC VAPOR/MIST,  
SUPPLIED AIR, OR SCBA.

Ventilation:MECHANICAL, (GENERAL  
) OR LOCAL EXHAUST.

Protective Gloves:POLYETHYLENE.

Eye Protection:CHEMICAL SPLASH GOGGLES/SAFETY GLASSES.

Other Protective Equipment:IMPERVIOUS CLOTHING, EYEWASH STATION.

Supplemental Safety and Health

NK

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:212F,100C

Melt/Freeze Pt:M.P/F.P Text:32.0F,0.0C

Decomp Temp:Decomp Text:NA

Vapor Pres:1.0

Vapor Density: