View NSN Online: https://aerobasegroup.de/nsn/2640-00-052-6724

Product ID:5704077;WESTERN WELD BU-16 LIQUID BUFFER MSDS Date:02/03/1997 FSC:2640 NIIN:00-052-6724 MSDS Number: CFCRP === Responsible Party === Company Name: UNOCAL CHEMICALS DIV UNION OIL CO OF CALIFORNIA Address:1701 GOLF RD., SUITE 1-1101 **Box:NONE** City :ROLLING MEADOWS State:IL ZIP:60008-4295 Country:US Info Phone Num:800-967-7601 Emergency Phone Num:800-967-7601 CAGE:5W323 === Contractor Identification === Company Name: SABINE ASSN FOR RETARDED CITIZENS INC Address:545 W SAN ANTONIO AVE Box:1150 City:MANY State:LA ZIP:71449 Country:US Phone:318-256-2025 CAGE:0F8U7 Company Name: UNOCAL CHEMICALS DIV UNION OIL CO OF CALIFORNIA Address:1345 N MEACHAM RD Box:City:SCHAUMBURG State:IL ZIP:60195 Country:US Phone:800-967-7601 CAGE:5W323

=================

Composition/Information on Ingredients =========

Ingred Name:HEXANE (N-HEXANE) (CERCLA) CAS:110-54-3 RTECS #:MN9275000 Other REC Limits:NONE RECOMMENDED OSHA PEL:500 PPM ACGIH TLV:50 PPM; 9596 EPA Rpt Qty:1 LB DOT Rpt Qty:1 LB

LD50 LC50 Mixture:LD50 OR/RAT=5G/KG;DERM/RAB=3.16G/KG Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic :INHAL:IRRITATES RESPIRATORY TRACT.CNS EFFECTS.ANESTHETIC.EYES:IRRITANT.SKIN:BRIEF CONTACT MAY DRY SKIN.PROLONGED CONTACT MAY CAUSE DERMATITIS.INGEST:VOMITING THIS MATERIEL AFTER SWALLOWING MAY CAUSE S EVERE LUNG DAMAGE.CHRONIC EXPOSURE MAY CAUSE IRREVERSIBLE NERVE DAMAGE. Explanation of Carcinogenicity:HEXANE HAS BEEN INVESTIGATED BY RETCS 92-4 AS A MUTAGEN,TUMORIGEN AND REPRODUCTIVE EFFECTOR. Effects of Overexposure:INHAL:DIZZINESS,UNCONSCIOUSNESS,NUMBNESS OF EXTREMITIE S,HEADACHE. Medical Cond Aggravated by Exposure:MANUFACTURER STATES NONE KNOWN.

First Aid:INHAL:REMOVE TO FRESH AIR.GIVE ARTIFICIAL RESPIRATION IF NEEDED.GET PROMPT MEDICAL ATTENTION.EYES:FLUSH WITH WATER FOR 15 MINUTES,WHILE LIFTING LIDS.GET MEDICAL ATTENTION.SKIN:REMOVE CONTAMINATED CLOT HING.WASH WITH SOAP AND WATER.GET MEDICAL ATTENTION IF IRRITATION PERSISTS.INGEST:DO NOT INDUCE VOMITING!GET PROMPT QU

ALIFIED MADICAL ATTENTION.

Flash Point Method:TCC Flash Point:-11F,-24C Autoignition Temp:Autoignition Temp Text:464F Lower Limits:1.0 Upper Limits:7.8 Extinguishing Media:USE DRY CHEMICAL OR CARBON DIOXIDE.WATER MAY BE INEFFECTIVE. Fire Fighting Procedures:WEAR A SELF-CONTAINED BREATHING APPARATUS AND FULL PROTECTIVE CLOTHING.USE WATER SPRAY TO COOL FIRE EXPOSED CONTAINERS.

Unusual Fire/Explosion Hazard: EXPLOSIVE

## VAPORS MAY FORM; EXTINGUISH ALL NEARBY SOURCES OF IGNITION.

Spill Release Procedures:USE PROPER RESPIRATORY AND PROTECTIVE EQUIPMENT.EXTINGUISH SOURCES OF EQUIPMENT.GROUND ALL HANDLING EQUIPMENT. DIKE LARGE SPILLS.ADSORB WITH A NON-COMBUSTIBLE SORBENT;PUT INTO APPROPRIATE CONTAINER FO R DISPOSAL.KEEP OUT OF SEWER OR WATERWAYS. Neutralizing Agent:NONE.

\_\_\_\_\_

Handling and Storage Precautions:STORE IN A COOL,DRY,WELL VENTILATED PLACE, AWAY FROM INCOMPATIBLE MATERIELS AND SOURCES OF IGNITION.GROUND EQUIPMENT WHEN HANDLING. Other Precautions:EMPTY CONTAINERS CAN HAVE EXPLOSIVE RESIDUES.USE NON-

SPARKING TOOLS.KEEP CONTAINERS CLOSED WHEN NOT IN USE.DO NOT CUT,GRIND,WELD OR DRILL NEAR THIS CONTAINER.

Respiratory Protection: USE EITHER A SELF-CONTINED BREATHING APPARATUS

OR A NIOSH/MSHA APPROVED RESPIRATOR FOR ORGANIC VAPOR. Ventilation:USE LOCAL OR MECHANICAL EXHAUST TO MAINTAIN TLV.MECHANICAL EQUIPMENT SHOULD BE NON-SPARKING(EXPLOSION-PROOF).

Protective Gloves: RUBBER GLOVES.

Frotective Gloves: RUBBER GLOVES.

Eye Protection: USE A FACE SHIELD.H

Other Protective Equipment: APPROVED WORK CLOTHES. HAVE EYE WASH AVAILABLE.

Work Hygienic Practices:WASH HANDS.SEPERATE WORK CLOTHES FROM STREET CLOTHES.LAUNDER WORK CLOTHES BEFORE REUSE.KEEP FOOD OUT OF THE WORK AREA. Suppl

emental Safety and Health NONE

HCC:F2 Boiling Pt:B.P. Text:149F,65C Melt/Freeze Pt:M.P/F.P Text: