View NSN Online: https://aerobasegroup.de/nsn/6750-01-304-2888

EASTMAN KODAK COMPANY -- 844 6163 T-MAX RS DEVELOPER AND REPLENISHER, WORKING SOLUTION -- 6750-01-304-2888

Product ID:844 6163 T-MAX RS DEVELOPER AND REPLENISHER, WORKING SOLUTION MSDS Date:02/11/1998 FSC:6750 NIIN:01-304-2888 MSDS Number: CFCWM === Responsible Party === Company Name: EASTMAN KODAK COMPANY Address:343 STATE STREET City:ROCHESTER State:NY ZIP:14650 С ountry:US Info Phone Num:716-477-3194 MSDS :800- 242-2424 Emergency Phone Num:716-722-5151 CAGE:19139 === Contractor Identification === Company Name: EASTMAN KODAK CO GOVERNMENT MARKETS CONTRACTS Address:343 STATE ST Box:City:ROCHESTER State:NY ZIP:14650-1115 Country:US Phone:716-722-5151/(800) 242-2424 CAGE:19139 Company Name: EASTMAN KODAK CO US CUSTOMER SERVICE/GOVERNMENT SALES Address:800 LEE RD Box:City:ROCHESTER State:NY ZIP:14650-3129 Country:US Phone:800-828-6203 CAGE:5K871

Composition/Information on Ingredients ==========

Ingred Name:WATER CAS:7732-18-5 RTECS #:ZC0110000 Fraction by Wt: 80 - 89% Other REC Limits:NONE RECOMMENDED OSHA PEL:NOT RELEVANT ACGIH TLV:NOT RELEVANT

Ingred Name:DIETHANOLAMINE-SULFUR DIOXIDE COMPLEX CAS:63149-47-3 Fraction by Wt: 10 - 19% Other REC Limits:NONE RECOMMENDED

Ingred Name:HYDROQUINONE (SARA 302/313) (CERCLA) CAS:123-31-9 RTECS #:MX3500000 Fraction by Wt: 1 - 5% Other REC Limits:NONE RECOMMENDED OSHA PEL:2 MG/M3 ACGIH TLV: 2 MG/M3; 9596 EPA Rpt Qty:1 LB DOT Rpt Qty:1 LB

Ingred Name:SODIUM BISULFITE (SASA III) (CERCLA) CAS:7631-90-5 RTECS #:VZ2000000 Fraction by Wt: < 1% Other REC Limits:NONE RECOMMENDED OSHA PEL:5 MG/M3 ACGIH TLV:5 MG/M3; 9596 EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS

Ingred Name:DIETHYLENE GLYCOL CAS:111-46-6 RTECS #:ID5950000 Fraction by Wt: < 1% Other REC Limits:NONE RECOMMENDED

LD50 LC50 Mixture:LD50 (ORAL, RAT) IS NOT K

NOWN. Routes of Entry: Inhalation:NO Skin:NO Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic: TARGET ORGANS: EYE, SKIN, GI TRACT. ACUTE- CAUSES EYE IRRITATION. PROLONGED/REPEATED SKIN CONTACT MAY CAUSE IRRITATION, ALLERGIC SKIN REACTION. EXPECTED TO BE A LOW HAZARD BY INHALATION. SULFUR DIOXIDE, FORMED IN CONTACT WITH STRONG ACID/HEAT, CAN IRRITATE RESPIRATORY TRACT. HARMFUL IF SWALLOWED. CHRONIC - UNKNOWN. Explanation of Car cinogenicity:NONE Effects of Overexposure: IRRITATION Medical Cond Aggravated by Exposure:SOME ASTHMATIC OR SULFITE-SENSITIVE INDIVIDUALS MAY EXPERIENCE WHEEZING, CHEST TIGHTNESS, STOMACH UPSET, HIVES, FAINTNESS, WEAKNESS AND DIARRHEA First Aid:CALL PHYSICIAN IF SYMPTOMS DEVELOP. EYE:IMMEDIATELY FLUSH WITH WATER FOR 15 MINUTES. HOLD EYELIDS OPEN. SKIN: FLUSH WITH PLENTY OF WATER. INHALED: MOVE TO FRESH AIR. PROVI DE CPR/OXYGEN IF NEEDED. ORAL: O NLY INDUCE VOMITING AT INSTRUCTION OF PHYSICIAN. CALL A PHYSICIAN/POISON CONTROL CENTER IMMEDIATELY. NEVER GIVE FLUID OR INDUCE VOMITING IF PATIENT IS UNCONSCIOUS OR HAS CONVULSIONS. Flash Point:NONE Lower Limits:NOT RELEVANT Upper Limits:NOT RELEVANT Extinguishing Media: USE WATER FOG, CARBON DIOXIDE (CO2), ALCOHOL FOAM OR DRY CHEMICAL. USE WATER SPRAY TO COOL FIRE EXPOSED C ONTAINERS. Fire Fighting Procedures: WEAR PROTECTIVE CLOTHING AND NIOSH-APPROVED

SELF-CONTAINED BREATHING APPARATUS. HAZARDOUS DECOMPOSITION PRODUCTS MAY BE FORMED. Unusual Fire/Explosion Hazard:NONE

Spill Release Procedures: FLUSH TO SEWER WITH LARGE AMOUNT OF WATER. OTHERWISE, ABSORB SPILL WITH INERT MATERIAL SUCH AS VERMICULITE, THEN PLACE IN A CONTAINER FOR CHEMICAL WASTE. CLEAN SURFACE THOROUGHLY TO REMO

VE RESIDUAL CO NTAMINATION. Neutralizing Agent:NOT RELEVANT

 Handling and Storage Precautions:STORE IN A COOL PLACE, AWAY FROM STRONG OXIDIZING AGENTS. KEEP CONTAINER TIGHTLY CLOSED.
Other Precautions:DO NOT GET IN EYES, ON SKIN OR ON CLOTHING. AVOID INHALATION OF VAPORS OR MISTS. KEEP OUT OF REACH OF CHILDREN. FOR LABORATORY USE ONLY. NOT FOR DRUG, FOOD/HOUSEHOLD USE. USE WITH ADEQUATE VENTILATION .

=== Exposure Controls/Personal Protection =============

Respiratory Protection:NONE NORMALLY REQUIRED. A NIOSH-APPROVED FULL-FACE POSITIVE-PRESSURE AIR-SUPPLIED RESPIRATOR MUST BE WORN IF HAZARDOUS DECOMPOSITION PRODUCTS ARE LIKELY TO BE RELEASED OR HAVE BEEN RELEASED.

Ventilation: GOOD GENERAL VENTILATION IS SUFFICIENT FOR MOST CONDITIONS (10 ROOM VOLUMES PER HOUR).

Protective Gloves: RUBBER FOR REPEATED/PROLONGED CONTACT Eye Protection: SAFETY GLASSES WITH SIDE SHIELD/GOGGLES O

ther Protective Equipment:EYE BATH, WASHING FACILITIES, SAFETY SHOWER Work Hygienic Practices:OBSERVE GOOD INDUSTRIAL HYGIENE PRACTICES AND RECOMMENDED PROCEDURES. WASH AFTER HANDLING AND BEFORE EATING OR DRINKING.

Supplemental Safety and Health

HCC:N1

NRC/State Lic Num:NOT RELEVANT Boiling Pt:B.P. Text:>212F,>100C Vapor Pres:18 @ 68F Vapor Density:0.6 Spec Gravity:1.04 pH:8.6 Solubility in Water:COMPLETE Appearance a nd Odor:COLORLESS LIQUID - AMINE ODOR Percent Volatiles by Volume:> 80

Stability Indicator/Materials to Avoid:YES STRONG OXIDIZING AGENTS Stability Condition to Avoid:NONE Hazardous Decomposition Products:CARBON MONOXIDE, CARBON DIOXIDE, OXIDES OF NITROGEN, OXIDES OF SULFUR

Waste Disposal Methods:DISCHARGE, TREATMENT OR DISPOSAL MAY BE SUBJECT TO FED

ERAL, STATE OR LOCAL REGULATIONS. FLUSH TO SEWER WITH LARGE AMOUNT OF WATER, IF ALLOWED. SINCE EMPTIED CONTAINERS RETAIN PRODUCT RESIDUE, FOLLOW L ABEL WARNINGS EVEN AFTER CONTAINER IS EMPTIED.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all

liability for its use. Any person utilizing this

document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.