

POINTER INC -- 7938174-60/3000-9, BATTERY PACK, LITHIUM -- 5826-01-307-7380

===== Product Identification =====

Product ID:7938174-60/3000-9, BATTERY PACK, LITHIUM

MSDS Date:09/27/1995

FSC:5826

NIIN:01-307-7380

MSDS Number: CFCWN

=== Responsible Party ===

Company Name:POINTER INC

Address:1027 N STADEM DR

City:TEMPE

State:AZ

ZIP:85281

Country:US

Info Phone Num:602-966-1674

Emergency Phone Num:602-96

6-1674, 800-424-9300 CHEMTREC

CAGE:58507

=== Contractor Identification ===

Company Name:POINTER INC

Address:1027 N STADEM DR

Box:City:TEMPE

State:AZ

ZIP:85281

Country:US

Phone:602-966-1674

CAGE:58507

===== Composition/Information on Ingredients =====

Ingred Name:LITHIUM METAL

CAS:7439-93-2

RTECS #:OJ5540000

Fraction by Wt: 2.5%

Other REC Limits:NONE RECOMMENDED

Ingred Name:SULFUR DIOXIDE

CAS:7446-09-5

RTECS #:WS4550000

Fraction by Wt: 25%

Other REC Limits:NONE RECOMMENDED

OS

HA PEL:5 PPM
ACGIH TLV:2 PPM

Ingred Name:ACETONITRILE
CAS:2206-26-0
Fraction by Wt: 60%
Other REC Limits:NONE RECOMMENDED

Ingred Name:ACETYLENE BLACK
CAS:133-86-4
Fraction by Wt: 5%
Other REC Limits:NONE RECOMMENDED

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:DEPENDING ON THE CONCENTRATION OF
SULFUR DIOXIDE, ACTS AS AN ASP
HYXIAANT AND MAY POSSIBLY CAUSE
UNCONSCIOUSNESS WITH NO KNOWN CHRONIC HEALTH EFFECTS.
Explanation of Carcinogenicity:NONE
Effects of Overexposure:SULPUR DIOXIDE-IRRITATION OF NOSE, THROAT, EYES
AND/OR SKIN. SUFFOCATING ODOR.
Medical Cond Aggravated by Exposure:SULPHUR DIOXIDE-ASTHMA AND OTHER
RESPIRATORY DISEASE.

===== First Aid Measures =====

First Aid:IF CELLS OF BATTERY VENTS PERSONNEL SHOULD BE EVACUATED FROM
THE CONTAMINATED AREA, ARTIF
ICIAL RESPIRATION SHOULD BE GIVEN IF
BREATHING STOPS. FLUSH MATERIAL FROM SKIN.

===== Fire Fighting Measures =====

Flash Point Method:COC
Flash Point:NON-FLAMMABLE
Extinguishing Media:USE WATER OR CARBON DIOXIDE ON BURNING LITHIUM
SULPHUR DIOXIDE CELLS OR BATTERIES. USE CLASS D FIRE EXT. AGENT ON
RAW LI
Fire Fighting Procedures:USE SELF-CONTAINED BREATHING APPARATUS.
Unusual Fire/Explosion Hazard:BATTERY MAY VENT WHEN SUBJECT TO
EXCESSIVE HEAT

EXPOSING CELL CONTENTS.

===== Accidental Release Measures =====

Spill Release Procedures:KEEP OUT OF AREA UNLESS USING IMPERVIOUS GLOVES AND CLOTHING AND FULL FACE BREATHING APPARATUS. PROVIDE MAXIMUM VENTILATION TO CLEAR OUT HAZARDOUS GASES.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

===== Handling and Storage =====

Handling and Storage Precautions:DO NOT STORE AT TEMPERATURES ABOVE 160F. STORE AT 70F FOR MAX

IMUM SHELF LIFE IN WELL VENTILATED AREA.

DO NOT CRUSH OR PUNCTURE PACK OR CELLS.

Other Precautions:DO NOT BYPASS FUES/DIODE ASSEMBLY IN PACK. TRANSPORT RESTRICTIONS APPLY.

===== Exposure Controls/Personal Protection =====

Eye Protection:SAFETY GLASSES WITH SIDE SHIELDS.

Supplemental Safety and Health

NONE

===== Physical/Chemical Properties =====

HCC:R2

Melt/Freeze Pt:M.P/F.P Text:374F,190C

Spec Gravity:1

Solubility in Water:NOT SOLUBLE IN WATER

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

Stability Condition to Avoid:BATTERY CONTAINS HERMATICALLY SEALED CELLS AND IS NON-REACTIVE PROVIDED THE CELL SEAL REMAINS INTACT.

Conditions to Avoid Polymerization:HEATING, MECHANICAL ABUSE AND ELECTRICAL ABUSE. DO NOT ATTEMPT TO RECHARGE OR SHORT CIRCUIT.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF IN ACCORD

ANCE WITH LOCAL, STATE AND
FEDERAL ENVIRONMENTAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility f
or the suitability of this information to their
particular situation.