

GENERAL ELECTRIC CO., SILICONE PRODUCT DIV. -- SILICONE SEALANT -- 8040-00-880-7332
===== Product Identification =====

Product ID:SILICONE SEALANT

MSDS Date:01/07/1997

FSC:8040

NIIN:00-880-7332

Kit Part:Y

MSDS Number: CFJTJ

=== Responsible Party ===

Company Name:GENERAL ELECTRIC CO., SILICONE PRODUCT DIV.

Address:HUDSON RIVER ROAD

City:WATERFORD

State:NY

ZIP:12188

Country:US

Info Phone Num:518-23

7-3330

Emergency Phone Num:518-237-3330

Preparer's Name:J.L. MCGUFFEY

CAGE:01139

=== Contractor Identification ===

Company Name:GENERAL ELECTRIC CO, SILICONE PRODUCTS BUSINESS DEPT

Address:260 HUDSON RIVER RD

Box:City:WATERFORD

State:NY

ZIP:12188

Country:US

Phone:518-237-3330/800-332-3390

CAGE:01139

Company Name:XTO INC

Address:16 CORPORATE DR

Box:UNKNOW

City:EAST SYRACUSE

State:NY

ZIP:13057-1015

Country:US

CAGE:1AE59

===== Composition/Information on Ingredients =====

Ingred

Name:DI-T-ETHOXY BUTOXYDIACETOXYSILANE

CAS:13170-23-5

Fraction by Wt: 1-5%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:NOT EST.

ACGIH TLV:NOT EST.

Ingred Name:METHYLTRiacETOXYSILANE (ORAL LD50=2060 MG/KG RAT)

CAS:4253-34-3

RTECS #:VV4500000

Fraction by Wt: 1-5%

Other REC Limits:10 PPM

OSHA PEL:NOT EST.

ACGIH TLV:NOT EST.

Ingred Name:POLYDIMETHYLSILOXANE AILANOL/SP (ORAL LD50>40000MG/KG RAT)(INHAL LC50=>535MG/L/4HR RAT)

CAS:70131-67-8

Fraction by Wt: 60-80%

Other REC Limits:NONE RECOMMENDED

Ingred Name:SILANOL/STPD SILOXANE W/ME SILOXNS (NON-HAZ)(ORAL LD50>40000MG/KG RAT/INHAL LC50>535MG/L ESTIMATED)

CAS:68554-67-6

Fraction by Wt: 5-10%

Other REC Limits:NONE RECOMMENDED

Ingred Name:AMORPHOUS SILICA (NON-HAZ)

CAS:112945-52-5

RTECS #:VV7310000

Fraction by Wt: 10-30%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:6 MG/M3

ACGIH TLV:10 MG/M3

=====
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carci

nogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:INGEST: HARMFUL. SKIN: IRRITATION.

INHAL: IRRITATION. EYE: IRRITATION. CHRONIC: SKIN/RESPIRATORY

SENSITIZATION. ACUTE TOXICANT/POTENTIAL CANCER HAZARD.

=====
===== First Aid Measures =====

First Aid:INGEST: RINSE MOUTH W/WATER SEVERAL TIMES. OBSERVE VICTEM 24 HRS. GET MED AID. SKIN: REMOVE W/DRY CLOTH. WASH W/DETERGENT/WATER. GET MED AID. INHAL: GET FRESH AIR. EYE: IMMED FLUSH

W/LOTS WATER
>15 MI N. GET MED AID.

=====
Fire Fighting Measures
=====

Flash Point Method:PMCC
Flash Point:72.0F,22.2C
Lower Limits:NA
Upper Limits:NA
Extinguishing Media:ALL STANDARD FIREFIGHTING MEDIA.
Fire Fighting Procedures:COMBUSTIBLE

=====
Accidental Release Measures
=====

Spill Release Procedures:WIPE/SCRAPE/SOAK UP IN INERT ABSORBANT.
CONTAINERIZE. WASH WALKING SURFACES W/DETERGENT/WATER TO REDUCE
SLIPPING HAZ
ARD.

=====
Handling and Storage
=====

Handling and Storage Precautions:COMBUSTIBLE. REMOVE CONTACTS BEFORE
USING SEALANT. RESIDUAL SEALANT MAY REMAIN ON FINGERS SEVERAL DAYS
& TRANSFER TO LENSES.

=====
Exposure Controls/Personal Protection
=====

Respiratory Protection:APPROVED NIOSH RESPIRATORY PROTECTION.
Ventilation:LOCAL EXHAUST.
Protective Gloves:RUBBER OR CLOTH
Eye Protection:SAFETY GLASSES
Other Protective Equipment:EYEWASH S
TATION
Supplemental Safety and Health
MORE INFORMATION FOR THIS MSDS ON FILE.

=====
Physical/Chemical Properties
=====

Boiling Pt:B.P. Text:NA
Melt/Freeze Pt:M.P/F.P Text:NA
Vapor Pres:NA
Vapor Density:NA
Spec Gravity:1.05
Evaporation Rate & Reference: