

GENERAL ELECTRIC CO., SILICONE PRODUCT DIV. -- SILICON POLYMER & SOLVENT --
8040-01-009-1562

===== Product Identification =====

Product ID:SILICON POLYMER & SOLVENT

MSDS Date:02/06/1996

FSC:8040

NIIN:01-009-1562

Kit Part:Y

MSDS Number: CFJTQ

=== Responsible Party ===

Company Name:GENERAL ELECTRIC CO., SILICONE PRODUCT DIV.

Address:HUDSON RIVER ROAD

City:WATERFORD

State:NY

ZIP:12188

Country:US

Inf

o Phone Num:518-237-3330

Emergency Phone Num:518-237-3330

Preparer's Name:C.E. HANNIGAN

CAGE:01139

=== Contractor Identification ===

Company Name:GENERAL ELECTRIC CO, SILICONE PRODUCTS BUSINESS DEPT

Address:260 HUDSON RIVER RD

Box:City:WATERFORD

State:NY

ZIP:12188

Country:US

Phone:518-237-3330/800-332-3390

CAGE:01139

Company Name:XTO INC

Address:16 CORPORATE DR

Box:UNKNOW

City:EAST SYRACUSE

State:NY

ZIP:13057-1015

Country:US

CAGE:1AE59

===== Composition/Information on Ingredients =====

=====

Ingred Name: BENZENE (SARA 313)(VP=75@20C)(LD50=3800MG/KG RAT,
LC50=10000PPM/7 HR RAT)
CAS: 71-43-2
RTECS #: CY1400000
Fraction by Wt: 40000MG/KG RAT)(LC50 INHAL >535MG/L)
CAS: 68554-67-6
Fraction by Wt: 30.0%
Other REC Limits: NONE RECOMMENDED

Ingred Name: VOC = 690 G/L
RTECS #: 9999999VO
Other REC Limits: NONE RECOMMENDED
OSHA PEL: NOT RELEVANT
ACGIH TLV: NOT RELEVANT

===== Hazards Identification =====

Routes of Entry: Inhalation: YES Skin: YES Ingestion: YES
Reports of Carcinogenicity: NTP: NO IARC: NO OSHA: NO
Health Hazards Acute and Chronic: INGEST: HARMFUL
(VOMITING/NAUSEA/DIARRHEA/IRRIT) SKIN: DRYING/ABSORPTION. INHAL:
HEADACHE/DIZZINESS/NAUSEA/INCOORDINATION/IRRIT. EYE: IRRIT/TISSUE
DAMAGE. CHRONIC: SKIN/RESP SENSITIZATION. ACUTE TOXIC ANT/POTENTIAL
CANCER HAZARD. TARGETS DERMATITIS/RESP AILMENTS/CNS
DAMAGE/LIVER/KIDNEY/CORNEAS/PULMINARY EDEMA.
Medical Cond Aggravated by Exposure: RESPIRATORY, LIVER, KIDNEY.

===== First Aid Measures =====

First Aid: INGEST: DON'T INDUCE VOMITING. DILUTE W/102 GLASSES
WATER/MILK. GET MED AID. NEVER GIVE ANYTHING BY MOUTH TO
UNCONSCIOUS PERSON. SKIN: REMOVE CONTAM CLOTHES/WASH BEFORE REUSE.
WASH W/SOAP & WATER. GET MED AID. INHAL: GET FRESH AIR. IF NOT
BREATHING GIVE ARTIF RESP(MOUTH-TO-MOUTH) . IF TROUBLE BREATHING
GIVE OXYGEN. GET MED AID. EYE: IMMEDIATELY FLUSH W/LOTS WATER >15 MIN.
GET IMMEDIATE MED AID.

=====

==== Fire Fighting Measures =====

Flash Point Method:PMCC

Flash Point:-12F,-24C

Autoignition Temp:Autoignition Temp Text:465F

Lower Limits:1.0

Upper Limits:12.0

Extinguishing Media:ALCOHOL FOAM, CARBON DIOXIDE, DRY CHEMICAL, REGULAR FOAM, WATER MIST.

Fire Fighting Procedures:EXTREMELY FLAMMABLE! USE FULL PROTECTIVE CLOTHING!

===== Accidental Release Measures =====

Spill Release Procedures:WIPE/SCRAPE/SOAK UP ON INERT ABSORBENT. CONTAIN

RELEASE. WEAR PROPER PROTECTIVE EQUIPMENT. REMOVE IGNITION SOURCES. EVACUATE. INCREASE VENTILATION.

===== Handling and Storage =====

Handling and Storage Precautions:USE GROUND STRAP. STORE IN ORIGINAL CONTAINER