

EASTMAN KODAK COMPANY, EASTERN REGIONAL DIST. CTR. -- 832 0608 FLEXICOLOR  
DEVELOPER REPLENISH LORR PART A -- 6750-01-416-1777

=====  
Product Identification  
=====

Product ID:832 0608 FLEXICOLOR DEVELOPER REPLENISH LORR PART A

MSDS Date:06/13/1997

FSC:6750

NIIN:01-416-1777

Kit Part:Y

MSDS Number: CFKLS

=== Responsible Party ===

Company Name:EASTMAN KODAK COMPANY, EASTERN REGIONAL DIST. CTR.

Adresse

ss:1187 W RIDGE RD

City:ROCHESTER

State:NY

ZIP:14650

Country:US

Info Phone Num:716-722-5151 OR 800-242-2424

Emergency Phone Num:716-722-5151

CAGE:5K871

=== Contractor Identification ===

Company Name:EASTMAN KODAK CO GOVERNMENT MARKETS CONTRACTS

Address:343 STATE ST

Box:City:ROCHESTER

State:NY

ZIP:14650-1115

Country:US

Phone:716-722-5151/(800) 242-2424

CAGE:19139

Company Name:EASTMAN KODAK CO US CUSTOMER SERVICE/GOVERNMENT SALES

Address:800 LEE RD

Box:City:ROCHESTER

State:NY

ZIP:14650-3129

Countr

y:US

Phone:800-828-6203

CAGE:5K871

=====  
Composition/Information on Ingredients  
=====

Ingred Name:WATER

CAS:7732-18-5

RTECS #:ZC0110000

Fraction by Wt: 65-70%

Other REC Limits:NONE RECOMMENDED

Ingred Name:POTASSIUM CARBONATE

CAS:584-08-7

RTECS #:TS7750000

Fraction by Wt: 25-30%

Other REC Limits:NONE RECOMMENDED

Ingred Name:POTASSIUM SULFITE

CAS:10117-38-1

RTECS #:WT3530000

AS:140-01-2  
Fraction by Wt: 1-5%  
Other REC Limits:NONE RECOMMENDED

Ingred Name:SODIUM SULFITE  
CAS:7757-83-7  
RTECS #:WE2150000  
Fraction by Wt: 1-5%  
Other REC Limits:NONE RECOMMENDED

=====  
===== Hazards Identification =====

Routes of Entry: Inhalation:NO Skin:NO Ingestion:NO  
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Health Hazards Acute and Chronic:EXPECTED TO BE A LOW HAZARD FOR USUAL  
INDUSTRIAL OR COMMERCIAL HANDLING BY TRAINED PERSONNEL. CONTACT

W/STRONG ACIDS OR IF HEATED, MAY YEILD SULFUR DIOXIDE; WHICH IS  
IRRITATING TO RESPIRATORY TRACT. C ONTACT MAY CAUSE EYE IRRITATION,  
SKIN SENSITIZATION. HARMFUL IF SWALLOWED.

Explanation of Carcinogenicity:NONE SPECIFIED BY MANUFACTURER.  
Effects of Overexposure:INHALED-RESPIRATORY TRACT IRRITATION, DIFFICULT  
BREATHING (ASTHMATICS, HYPERSENSITIVE PERSONS). INGESTED-HARMFUL.  
EYES-IRRITATION. SKIN-ALLERGIC REACTION, SENSITIZATION.  
Medical Cond Aggravated by Exposure:NONE SPECIFIED  
BY MANUFACTURER.

=====  
===== First Aid Measures =====

First Aid:INHALATION-IF SYMPTOMATIC, MOVE TO FRESH AIR. GET MEDICAL  
ATTENTION IF SYMPTOMS OCCUR. EYES-FLUSH WITH WATER FOR 15 MINUTES.  
GET MEDICAL ATTENTION IF SYMPTOMS OCCUR. SKIN-WASH WITH SOAP &  
WATER. GET M EDICAL ATTENTION IF SYMPTOMS OCCUR. INGESTED-IF  
CONSCIOUS, DRINK 1-2 GLASSES OF WATER. SEEK MEDICAL ATTENTION.

=====  
===== Fire Fighting Measures =====

Fla  
sh Point:NONE  
Extinguishing Media:USE MEDIA APPROPRIATE FOR SURROUNDING FIRE.  
Fire Fighting Procedures:WEAR SELF CONTAINED BREATHING APPARATUS AND  
PROTECTIVE CLOTHING.  
Unusual Fire/Explosion Hazard:NONE.

=====  
===== Accidental Release Measures =====

Spill Release Procedures:ABSORB SPILL WITH INERT MATERIAL, THEN PLACE  
INA CHEMICAL WASTE CONTAINER. PREVENT RUN-OFF FROM ENTERING DRAINS,  
SEWERS AND STREAMS.  
Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

=====  
=====

=====  
Handling and Storage  
=====

Handling and Storage Precautions:KEEP CONTAINER TIGHTLY CLOSED. KEEP AWAY FROM INCOMPATIBLE MATERIALS. AVOID BREATHING MIST. USE WITH ADEQUATE VENTILATION.

Other Precautions:AVOID CONTACT WITH EYES AND PROLONGED OR REPEATED CONTACT WITH SKIN. WASH THOROUGHLY AFTER HANDLING.

=====  
Exposure Controls/Personal Protection  
=====

Respiratory Protection:NONE NORMALLY REQUIRED.

Ventilation:USE ADEQUATE MECHANICAL VENTILATION. MANUFACTURER SAYS 10 ROOM VOLUMES/HOUR.

Protective Gloves:IMPERVIOUS-PVC.

Eye Protection:SAFETY GLASSES/CHEMICAL SPLASH GOGGLES

Other Protective Equipment:EYE WASH STATION & SAFETY SHOWER. PROTECTIVE CLOTHING APPROPRIATE FOR THE RISK OF EXPOSURE.

Work Hygienic Practices:WASH HANDS AFTER HANDLING AND BEFORE EATING, DRINKING, OR SMOKING. LAUNDRER CONTAMINATED CLOTHES BEFORE REUSE.

Supplemental Safety and Health

KEY1=C2. THIS ITEM IS PART OF A KIT. THE ITEM HAS A COMPONENT WHICH

CONTAINS HAZARDOUS MATERIALS. RATED C2 FOR HCC BECAUSE IS SHIPPED AS A CORROSIVE MATERIAL.

=====  
Physical/Chemical Properties  
=====

HCC:B1

Boiling Pt:>100.C, 212.F

Vapor Pres:18

Vapor Density:0.6

Spec Gravity:1.39

pH:12.3

Evaporation Rate & Reference:N/K (N-BUTYL ACETATE=1)

Solubility in Water:COMPLETE

Appearance and Odor:CLEAR, COLORLESS SOLUTION; ODORLESS.

Percent Volatiles by Volume:65-75

=====  
Stability and Reactivity Data  
=====

=====

Stability Indicator/Materials to Avoid: YES

ACIDS.

Stability Condition to Avoid: NONE SPECIFIED BY MANUFACTURER.

Hazardous Decomposition Products: NONE.

===== Disposal Considerations =====

Waste Disposal Methods: DISCHARGE, TREATMENT OR DISPOSAL MAY BE SUBJECT TO LOCAL, STATE AND FEDERAL REGULATIONS. NEUTRALIZE PRIOR TO DISPOSAL. NEUTRALIZATION AND SEWERING MAY NOT BE ALLOWED IN SOME STATES OR MUNICIPALITIES.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.