

DOW CORNING CORP -- 3-7132 RTV ADH/SLNT-TAN, (SB-82162) -- 8030-01-345-5925

=====  
Product Identification  
=====

Product ID:3-7132 RTV ADH/SLNT-TAN, (SB-82162)

MSDS Date:04/10/1991

FSC:8030

NIIN:01-345-5925

MSDS Number: CFMTF

=== Responsible Party ===

Company Name:DOW CORNING CORP

Address:SOUTH SAGINAW RD

City:MIDLAND

State:MI

ZIP:48686

Country:US

Info Phone Num:517-496-6000

Emergency Phone Num:517

-496-5900

CAGE:5D028

=== Contractor Identification ===

Company Name:DOW CORNING CORP

Address:3901 S SAGINAW RD

Box:997

City:MIDLAND

State:MI

ZIP:48686-0997

Country:US

Phone:517-496-6000/517-496-6315

CAGE:5D028

Company Name:DOW CORNING CORP

Address:2200 W SALZBURG RD

Box:City:AUBURN

State:MI

ZIP:48611

Country:US

Phone:517-496-4388

CAGE:71984

=====  
Composition/Information on Ingredients  
=====

Ingred Name:SILANE, METHYLTRIACETOXY-; (METHYLTRIACETOXYSILANE)

CAS:4253-34-3

RTECS #:

VV4500000

Fraction by Wt: 2%

Ingred Name:ETHYLTRIACETOXYSILANE

CAS:17689-77-9

Fraction by Wt: 2%

Ingred Name:SILICA, AMORPHOUS FUMED

CAS:112945-52-5

RTECS #:VV7310000

Fraction by Wt: 10%

OSHA PEL:6 MG/M3

ACGIH TLV:10 MG/M3

=====  
===== Hazards Identification =====

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:EYE: DIRECT

CONTACT IRRITATES SLIGHTLY

TO MODERATELY WITH REDNESS AND SWELLING. SKIN: SINGLE SHORT EXPOSURE (LESS THAN 24 HOURS) MAY IRRITATE. REPEATED PROLONGED CONTACT (24 TO 48 HOURS) MAY IRRITATE MODERATELY. INHALATION: VAPOR OVEREXPOSURE MAY IRRITATE EYES, NOSE, AND THROAT. INGESTION: SMALL AMTS (EFTS OF OVEREXP)

Explanation of Carcinogenicity:NONE SPECIFIED BY MANUFACTURER.

Effects of Overexposure:HEALTH HAZARDS: TRANSFERRED TO MOUTH BY FINGERS DURING USE, ETC., SHOULD NOT IN

JURE. SWALLOWING LARGE AMOUNTS MAY

CAUSE DIGESTIVE DISCOMFORT. NO KNOWN ADVERSE CHRONIC HEALTH EFFECTS, BUT UNNECESSARY EXPOSURE TO ANY CHEMICAL SHOULD BE AVOIDED.

Medical Cond Aggravated by Exposure:MAY ENHANCE ALLERGIC CONDITIONS ON CERTAIN PEOPLE.

=====  
===== First Aid Measures =====

First Aid:EYE: FLUSH WITH WATER FOR AT LEAST 15 MINUTES. GET MEDICAL ATTENTION. SKIN: WIPE OFF AND FLUSH WITH WATER. GET MEDICAL ATTENTION IF IRRITATION

DEVELOPS. INHALATION: REMOVE TO FRESH AIR.

INGESTION: CALL MD IMMEDIATELY .

===== Fire Fighting Measures =====

Flash Point Method:CC

Flash Point:212F,100C

Extinguishing Media:WATER FOG, CARBON DIOXIDE, DRY CHEMICAL, FOAM.

Fire Fighting Procedures:USE NIOSH APPROVED SCBA AND FULL PROTECTIVE EQUIPMENT .

Unusual Fire/Explosion Hazard:NONE SPECIFIED BY MANUFACTURER.

===== Accidental Release Measures =====

Spill Release Procedures:

REMOVE PRODUCT AND CONTAIN FOR SALVAGE OR DISPOSAL.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

===== Handling and Storage =====

Handling and Storage Precautions:STORE BELOW 90F/32C. KEEP CONTAINER CLOSED UNTIL READY TO USE.

Other Precautions:PRODUCT FORMS ACETIC ACID (HOAC) WHEN EXPOSED TO WATER OR HUMID AIR. PROVIDE VENTILATION DURING USE TO CONTROL HOAC EXPOSURE WITHIN 10 PPM (CURRENT TLV) OR USE RESPIRATORY PROTECTION.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE RESPIRATORY PROTECTION UNLESS LOCAL EXHAUST VENTILATION IS ADEQUATE OR AIR SAMPLING DATA SHOW EXPOSURES ARE WITHIN TLV AND PEL GUIDELINES. USE NIOSH APPROVED ACID GAS/ORGANIC VAPOR TYPE RESPIRATOR .

Ventilation:LOCAL EXHAUST MAY BE NEEDED. MECHANICAL (GENERAL) RECOMMENDED.

Protective Gloves:IMPERVIOUS GLOVES .

Eye Protection:ANSI APPROVED CHEM WORKERS GOGGLES .

Other Protective Equipment:ANSI APPROVED EYE WASH & DELUGE SHOWER .

Work Hygienic Practices:WASHING AT MEALTIME & END OF SHIFT IS ADEQ. REMOVE CONTAMINATED CLOTHING & SHOES AS SOON AS PRACTICAL & CLEAN THOROUGHLY (SUPPORT)

Supplemental Safety and Health WORK HYGIENIC PRACTICES: BEFORE REUSE.

===== Physical/Chemical Properties =====

HCC:T6

Vapor Pressure: