

PRATT AND LAMBERT, INC; INDUSTRIAL COATINGS DIV -- ENAMEL ALKYD SEMIGLOSS #775402 --
8010-01-131-9194

===== Product Identification =====

Product ID:ENAMEL ALKYD SEMIGLOSS #775402

MSDS Date:03/23/1993

FSC:8010

NIIN:01-131-9194

MSDS Number: CFNCC

=== Responsible Party ===

Company Name:PRATT AND LAMBERT, INC; INDUSTRIAL COATINGS DIV

Box:2153

City:WICHITA

State:KS

ZIP:67201

Country:US

Info Phone Num:3

16-733-1361

Emergency Phone Num:716-873-6000/DOT: 800-255-3924

Preparer's Name:L. A. ELLISON

CAGE:61196

=== Contractor Identification ===

Company Name:PRATT AND LAMBERT INC

Box:6027

City:CLEVELAND

State:OH

ZIP:44101-1027

Country:US

Phone:216-566-2902

CAGE:61196

===== Composition/Information on Ingredients =====

Ingred Name:PETROLEUM DISTILLATE HYDROTREATED LIGHT SOLVENT

CAS:64742-47-8

Fraction by Wt: 10.0%

Other REC Limits:NONE RECOMMENDED

Ingred Name:XYLENE (SARA 313) (CERC

LA) (VP = 5 @ 20C)
CAS:1330-20-7
RTECS #:ZE2100000
Fraction by Wt: 10.0%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:100 PPM/STEL 150
ACGIH TLV:100 PPM/STEL 150
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:METHYL ISOAMYL KETONE
CAS:110-12-3
RTECS #:MP3850000
Fraction by Wt: 5.0%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:50 PPM
ACGIH TLV:50 PPM

Ingred Name:TALC
CAS:14807-96-6
RTECS #:MW2700000
Fraction by Wt: 15.0%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:2.0 MG/M3
ACGIH TLV:2 MG/M3

Ingred Name:CRYSTALLINE SILICA
CAS:14808-60-7
RTECS #:VV7330000
Fraction by Wt: 115F. STORE LARGE
QUANTITIES IN COMPLIANCE WITH OSHA 29 CFR 1910.106.
Other Precautions:DONT WASH OR REUSE EMPTY CONTAINER FOR ANY PURPOSE.
GROUND & BOND CONTAINERS TO RECEIVING CONTAINER. DONT WELD, BRAZE
OR CUT ON EMPTY CONTAINER. NEVER USE PRESSURE TO EMPTY. DRUM IS NOT
A PRESSURE VESSEL.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE NIOSH CHEMICAL CARTRIDGE RESPIRATOR. FOR
SPRAYING USE MECHANICAL PREFILTER. IN CONFINED AREAS USE AIR
SUPPLIED RESPIRATOR.
Ventilation:LOCAL EXHAUST.
Protective Gloves:IMPERMEABLE.
Eye Protection:SAFETY SPECTACLES.
Other Protective Equipment:EYEWASH FACILITY, SAFETY SHOWER.
Supplemental Safety and Health
MORE INFORMATION ON FILE

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:165 TO 383F
Melt/Freeze Pt:M.P/F.P Text:-50F,-46C
Decomp Temp:Decomp Text:1832F,1

000C
Vapor Pres:10.0
Vapor Density:>AIR.
Spec Gravity:1.2
pH:4-7
Viscosity:67-77 KU
Evaporation Rate & Reference:SLOWER THAN DIETHYL ETHER
Solubility in Water:SLIGHT.
Appearance and Odor:LIQUID, W/SOLVENT ODOR.
Percent Volatiles by Volume:42.0
Corrosion Rate:NA

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
STRONG ACIDS OR ALKALINE MATERIALS. OXIDIZING MATERIALS.
Stability Condition to Avoid:AVOID EXCESSIVE HEAT (>115F) AND SO
URCES
OF IGNITION.
Hazardous Decomposition Products:SMOKE, CARBON MONOXIDE & CARBON
DIOXIDE.

===== Disposal Considerations =====

Waste Disposal Methods:IN ACCORDANCE W/FEDERAL, STATE & LOCAL
LAWS/REGULATIONS. RCRA CLASSIFICATION: D001.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.