

DEL PAINT CORP. -- TT-E-2784 GREEN, #34052 -- 8010-01-418-5431

===== Product Identification =====

Product ID:TT-E-2784 GREEN, #34052
MSDS Date:06/14/1995
FSC:8010
NIIN:01-418-5431
MSDS Number: CFNHH
=== Responsible Party ===
Company Name:DEL PAINT CORP.
Address:3105 E. RENO
City:OKLAHOMA CITY
State:OK
ZIP:73117
Country:US
Info Phone Num:405-672-1431/FAX 405-672-0804
Emergency Phone Num:800-424-930
0 24 HRS
CAGE:JO954
=== Contractor Identification ===
Company Name:DEL PAINT CORP.
Address:3105 E. RENO
City:OKLAHOMA CITY
State:OK
ZIP:73117
Country:US
Phone:405-672-1431/FAX 405-672-0804
CAGE:JO954
Company Name:DEL PAINT MFG
Address:3105 EAST RENO
Box:City:OKLAHOMA CITY
State:OK
ZIP:73117
Country:US
Phone:405-672-1431
CAGE:39934

===== Composition/Information on Ingredients =====

Ingred Name:PROPYLENE GLYCOL
CAS:57-55-6
RTECS #:TY2000000
Fraction by Wt: 6.25%
Other REC Limit

s:NONE RECOMMENDED

Ingred Name:2,2,4-TRIMETHYL-1-3-PENTANEDIOL MONOISOBUTYRATE
CAS:25265-77-4
Fraction by Wt: 4.86%
Other REC Limits:NONE RECOMMENDED

Ingred Name:DIMETHYLAMINOETHANOL LOW VOC
CAS:108-01-0
RTECS #:KK6125000
Fraction by Wt: 0.38%
Other REC Limits:NONE RECOMMENDED

Ingred Name:2-N-OCTYL-4-ISOTHIAZOLIN-3-ONE
CAS:123-96-6
RTECS #:RH0795000
Fraction by Wt: 0.18%
Other REC Limits:NONE RECOMMENDED

Ingred Name:NON HAZARDOUS INGREDIENTS
Fraction by Wt: 88.33%
Other REC Limits:NONE RECOMMENDED

Ingred Name:VOC = 1.7 LBS/GL
RTECS #:9999999VO
Other REC Limits:NONE RECOMMENDED
OSHA PEL:NOT EST.

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:INHAL: HEADACHE, NAUSEA, IRRITATION.
EYE: IRRITATION. CHRONIC: SKIN: IRRITATION.
Medical Cond Aggravated by Exposure:LUNG DISEASE

===== First Aid Measures =====

First Aid:EYE: FLUSH W/LARGE AMOUNTS OF WATER FOR 15 MINUTES. CALL DR.
SKIN: WASH W/SOAP & WATER. INGEST: GIVE 2 GLASSES OF WATER TO
DRINK. CALL DR.

===== Fire Fighting Measures =====

Flash Point Method:SCC
Flash Point:>212F,>100C
Autoignition Temp:Autoignition Temp Text:216F
Lower Limits:NONE
Upper Limits:NA
Extinguishing Media:FOAM, ALCOHOL FOAM, CO2, DRY CHEMICAL, WATER FOG.
Fire Fighting Procedures:USE SCBA (PRESSURE DEMAN

D NIOSH/MSHA APPROVED)
& FULL PROTECTIVE GEAR.

Unusual Fire/Explosion Hazard:MATERIAL MAY SPLATTER ABOVE 212F. POLYMER
FILM MAY BURN.

===== Accidental Release Measures =====

Spill Release Procedures:EVAC AREA. FLOOR MAY BE SLIPPERY, USE CARE TO
AVOID FALLING. DIKE/ABSORB. TRANSFER TO SEPARATE, SUITABLE
CONTAINER FOR RECOVERY/DISPOSAL. DONT CONTAMINATE SEWERS, OPEN
BODIES OF WATER.

===== Handling and Storage =====
==

Handling and Storage Precautions:KEEP FROM FREEZING.
Other Precautions:KEEP AWAY FROM CHILDREN.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:APPROVED MECHANICAL FILTER RESPIRATOR
Ventilation:NORMAL (FAN)
Protective Gloves:RUBBER
Eye Protection:SAFETY GLASSES/GOGGLES
Other Protective Equipment:EYEWASH STATION
Supplemental Safety and Health
NK

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:212 TO 644F
Melt/Freeze Pt:M.P/F.P Text:32.0F,0.0C
Decomp Temp:Decomp Text:350F,177C
Vapor Pres:NONE
Vapor Density:>AIR
Spec Gravity:1.01
pH: