View NSN Online: https://aerobasegroup.de/nsn/8010-01-426-5513

Product ID:WATERBORNE POLYURETHANE BROWN, #30051 MSDS Date:05/21/1997 FSC:8010 NIIN:01-426-5513 Kit Part:Y MSDS Number: CFNKM === Responsible Party === Company Name: SHERWIN-WILLIAMS CO Address:101 PROSPECT AVE N W City:CLEVELAND State:OH ZIP:44115-1042 Country:US Info Phone Num:216-5 66-2902 Emergency Phone Num:216-566-2917 CAGE:54636 === Contractor Identification === Company Name: SHERWIN-WILLIAMS CO THE Address:101 PROSPECT AVE NW Box:City:CLEVELAND State:OH ZIP:44115-1042 Country:US Phone:800-251-2486/216-566-2242 CAGE:54636 Ingred Name:1-METHYL-2-PYRROLIDINONE (SARA 313) (VP = 1)

CAS:872-50-4 RTECS #:UY5790000 Fraction by Wt: 5.0% Other REC Limits:NONE RECOMMENDED

Ingred Name:QUARTZ CAS:14808-60-7 RT ECS #:VV7330000 Fraction by Wt: 0.4% Other REC Limits:NONE RECOMMENDED OSHA PEL:0.1 MG/M3 ACGIH TLV:0.1 MG/M3

Ingred Name:CRISTOBALITE CAS:14464-46-1 RTECS #:VV7325000 Fraction by Wt: 6.0% Other REC Limits:NONE RECOMMENDED OSHA PEL:0.05 MG/M3 ACGIH TLV:0.05 MG/M3

Ingred Name:VOC = 1.36 LBS/GL RTECS #:9999999VO Other REC Limits:NONE RECOMMENDED OSHA PEL:NOT RELEVANT ACGIH TLV:NOT RELEVANT

Ingred Name:TALC CAS:14807-96-6 RTECS #:MW2700000 Fraction by Wt: 9.0% Other REC Limits:NONE RECOMMENDED O SHA PEL:2 MG/M3 ACGIH TLV:2 MG/M3

Ingred Name:CARBON BLACK CAS:1333-86-4 RTECS #:FF5800000 Fraction by Wt: 0.1% Other REC Limits:NONE RECOMMENDED OSHA PEL:3.5 MG/M3 ACGIH TLV:3.5 MG/M3

Ingred Name:CHROMIUM (III) OXIDE (SARA 313) CAS:1308-38-9 RTECS #:GB6475000 Fraction by Wt: 7.0% Other REC Limits:NONE RECOMMENDED OSHA PEL:0.5 MG/M3 ACGIH TLV:0.5 MG/M3

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Reports of Carc

inogenicity:NTP:YES IARC:YES OSHA:NO
Health Hazards Acute and Chronic: EYE: IRRITATION, REDNESS, ITCHING,
BURNING. SKIN: IRRITATION, REDNESS, ITCHING, BURNING. INHAL:
IRRITATION, HEADACHE, NAUSEA, DIZZINESS. CHRONIC: LUNG DAMAGE,
CANCER.
Explanation of Carcinogenicity: CARBON BLACK IS LISTED BY IARC.
CRYSTALLINE SILICA IS LISTED BY IARC. CRYSTALLINE SILICA IS LISTED
BY IARC & NTP.
Medical Cond Aggravated by Exposure:ALLERGIC RESPIRATORY &/OR SKIN
REACTION.
REAGTION.
===============================
First Aid:INHAL: REMOVE TO FRESH AIR. GET MED AID. SKIN: WASH
THOROUGHLY W/SOAP & WATER. REMOVE CONTAM CLOTHES, WASH BEFORE
REUSE. EYE: FLUSH W/LARGE AMOUNTS OF WATER FOR 15 MINUTES. INGEST:
GET MED AID.
Fire Fighting Managemen
======================================
Fleeh Deint Method: DMCC
Flash Point Method: PMCC
Flash Point:>200F,>93C
Lower Limits:NA
Upper Limits:NA
Extinguishing Media: CARBON DIOXIDE, DRY CHEMICAL ALCOHOL FOAM.
Fire Fighti
ng Procedures: USE FULL PROTECTIVE EQUIPMENT INCLUDING SCBA.
WATER MAY BE INEFFECTIVE. IF USED, FOG NOZZLES PREFERRED. USE WATER
TO COOL FIRE EXPOSED CNTNRS TO PREVENT *
Unusual Fire/Explosion Hazard:*PRESSURE BUILDUP/AUTOIGNITION/EXPLOSION.
CLOSED CONTAINER MAY EXPLODE W/EXTREME HEAT.
======================================
Spill Release Procedures: REMOVE IGNITION SOURCES. VENT AREA. REMOVE
W/INERT ABSORBENT.
======================================

- Handling and Storage Precautions: PEOPLE W/CHRONIC BREATHING PROBLEMS OR ISOCYANATE SENSITIZATION SHOULD NOT BE NEAR PRODUCT. KEEP CONTAINER CLOSED WHEN NOT IN USE. TRANSFER ONLY TO \*\*
- Other Precautions:\*\*APPROVED CONTAINER W/APPROPRIATE LABELING. KEEP OUT OF REACH OF CHILDREN. PRODUCT MUST BE MIXED W/OTHER COMPONENTS BEFORE USE. READ LABELS BEFORE USING PRODUCT. DONT INCINERATE CLOSED CONTAINER.

====== Exposure Controls/Personal Protectio

Respiratory Protection:USE POSITIVE PRESSURE AIR SUPPLIED RESPIRATOR OR PROPERLY FITTED ORGANIC VAPOR/PARTICULATE RESPIRATOR. WHEN ABRADING/BURNING, USE PARTICULATE RESPIRATOR, (NIOSH/MSHA APPROVED). Ventilation:LOCAL EXHAUST PREFERRED. GENERAL ACCEPTABLE. Protective Gloves:YES Eye Protection:SAFETY SPECTACLES W/SIDE SHIELD. Other Protective Equipment:BARRIER CREAMS. Supplemental Safety and Health MORE INFORMATION ON FILE.

================== Physical/Chemical Pro

perties ==============

Boiling Pt:B.P. Text:212 TO 396F Melt/Freeze Pt:M.P/F.P Text:NA Vapor Density:>AIR. Spec Gravity:1.3 Evaporation Rate & amp; Reference: