

KRYLON, THE SHERWIN-WILLIAMS CO., SPECIALITY DIV. -- 1501 GLOSSY WHITE SPRAY PAINT,800719 -- 8010-00-132-2865

=====  
===== Product Identification =====

Product ID:1501 GLOSSY WHITE SPRAY PAINT,800719

MSDS Date:04/10/1989

FSC:8010

NIIN:00-132-2865

MSDS Number: CFRCQ

=== Responsible Party ===

Company Name:KRYLON, THE SHERWIN-WILLIAMS CO., SPECIALITY DIV.

Address:6830 COCHRAN ROAD

City:SOLO

State:OH

ZIP:4

4139-3908

Country:US

Info Phone Num:216-292-7400

Emergency Phone Num:216-292-7400

CAGE:EO276

=== Contractor Identification ===

Company Name:BLICK DICK CO

Address:P O BOX 1267

Box:City:GALESBURG

State:IL

ZIP:61401

Country:US

Phone:309-343-6181

CAGE:06608

Company Name:KRYLON, THE SHERWIN-WILLIAMS CO., SPECIALITY DIV.

Address:6830 COCHRAN ROAD

Box:City:SOLO

State:OH

ZIP:44139-3908

Country:US

Phone:216-292-7400

CAGE:EO276

=====  
===== Composition/Information on Ingredients =====

Ingred

Name:ACETONE (SARA 313) (CERCLA)  
CAS:67-64-1  
RTECS #:AL3150000  
Fraction by Wt: 30 - 50%  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:1000 PPM  
ACGIH TLV:750PPM/1000STEL;9596  
EPA Rpt Qty:5000 LBS  
DOT Rpt Qty:5000 LBS

Ingred Name:PROPANE  
CAS:74-98-6  
RTECS #:TX2275000  
Fraction by Wt: 10 - 30%  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:1000 PPM  
ACGIH TLV:ASPHYXIAN; 9596

Ingred Name:METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA 313) (CERCLA)  
CAS:78-93-3  
RTECS #:EL6475000  
Fraction by Wt: 5 - 10%  
Other  
REC Limits:NONE RECOMMENDED  
OSHA PEL:200 PPM  
ACGIH TLV:200 PPM/300STEL;9596  
EPA Rpt Qty:5000 LBS  
DOT Rpt Qty:5000 LBS

Ingred Name:METHYL ISOBUTYL KETONE (HEXONE) (SARA 313) (CERCLA)  
CAS:108-10-1  
RTECS #:SA9275000  
Fraction by Wt: 1 - 5%  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:100 PPM  
ACGIH TLV:50 PPM/75 STEL; 9596  
EPA Rpt Qty:5000 LBS  
DOT Rpt Qty:5000 LBS

Ingred Name:2-PROPANOL,1-METHOXY- ACETATE/PROPYLENE GLYCOL MONOMETHYL  
ETHER ACETATE  
CAS:108-65-6  
RTECS #:AI8295000  
Fraction by Wt: 5

- 10%  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:NOT ESTABLISHED.  
ACGIH TLV:NOT ESTABLISHED.

Ingred Name:TOLUENE (SARA 313) (CERCLA)  
CAS:108-88-3  
RTECS #:XS5250000  
Fraction by Wt: 1 - 5%  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:200 PPM; Z-2  
ACGIH TLV:S, 50 PPM; 9596  
EPA Rpt Qty:1000 LBS  
DOT Rpt Qty:1000 LBS

Ingred Name:XYLENES (O-,M-,P- ISOMERS) (SARA 313) (CERCLA)  
CAS:1330-20-7  
RTECS #:ZE2100000  
Fraction by Wt: 10 - 30%  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:100 PPM  
ACGIH TLV:100 PPM/1  
50STEL;9596  
EPA Rpt Qty:1000 LBS  
DOT Rpt Qty:1000 LBS

Ingred Name:TITANIUM DIOXIDE  
CAS:13463-67-7  
RTECS #:XR2275000  
Fraction by Wt: 5 - 10%  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:15 MG/M3 TDUST  
ACGIH TLV:10 MG/M3 TDUST; 9596

===== Hazards Identification =====

LD50 LC50 Mixture:LD50 (ORAL, RAT) IS NOT KNOWN.  
Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO  
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Health Hazards Acute and Chronic:TARGET O

RGANS:EYES, SKIN, CNS, LUNGS.

ACUTE- INHALATION OF VAPORS MAY CAUSE CNS DEPRESSION. MAY CAUSE IRRITATION OF EYES, SKIN & RESPIRATORY TRACT. MAY CAUSE SKIN DEFATTING. HARMFUL IF SWALLOWED. MAY CAUSE VOMITING. ASPIRATION HAZARD. CHRONIC- OVEREXPOSURE MAY CAUSE DERMATITIS, LIVER, KIDNEYS, BRAIN & CNS DAMAGE

Explanation of Carcinogenicity:NONE

Effects of Overexposure:IRRITATION, HEADACHE, DIFFICULTY IN BREATHING, NAUSEA, VOMITING, DEFATTING, DIZZINESS, LOSS OF COORDINATION, FATIGUE, CONFUSION, DERMATITIS, BLURRED VISION, TEARING, UNCONSCIOUSNESS

Medical Cond Aggravated by Exposure:INDIVIDUALS WITH PRE-EXISTING DISEASES OF THE EYE, SKIN, RESPIRATORY TRACT, LIVER, KIDNEYS, CNS MAY HAVE INCREASED SUSCEPTIBILITY TO THE TOXICITY OF EXCESSIVE EXPOSURES.

===== First Aid Measures =====

First Aid:GET MEDICAL ATTENTION IF SYMPTOMS PERSIST.

EYES/SKIN:IMMEDIATELY FLUSH WITH WATER FOR 15 MINUTES. HOLD EYELIDS  
O

PEN. INHALED:MOVE TO FRESH AIR. PROVIDE CPR/OXYGEN IF NECESSARY.

ORAL:SEEK MEDICAL ATTENTION IMMEDIATELY. IF CONSCIOUS, DRINK LARGE AMOUNT OF WATER. NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON.

===== Fire Fighting Measures =====

Flash Point:FLAMMABL AEROSOL

Extinguishing Media:USE FOAM, DRY CHEMICAL OR CARBON DIOXIDE. WATER MAY BE INEFFECTIVE BUT SHOULD BE USED TO COOL FIRE-EXPOSED CONTAINERS.

Fire Fighting Procedures:WEAR FULL PROTECTIVE CLOTHING AND

NIOSH-APPROVED SELF-CONTAINED BREATHING APPARATUS. VAPORS ARE HEAVIER THAN AIR, CAN TRAVEL TO IGNITION SOURCES AND FLASH BACK.

Unusual Fire/Explosion Hazard:SPRAY CANS UNDER PRESSURE. EXTREMELY FLAMMABLE. EXPLOSION HAZARD EXISTS WHEN SPRAY CANS HEATED. DO NOT ENTER SPRAY CAN STORAGE AREA IF FIRE PRESENT.

===== Accidental Release Measures =====

Spill Release Procedures:VENTILATE AREA. REMOVE IGNITION SOURCES. LEAKING CONTAINERS

SHOULD BE PLACED OUTDOORS, IN AN OPEN CONTAINER,  
AWAY FROM SOURCES OF IGNITION. ALLOW PRESSURE TO DISSIPATE. ABSORB  
LIQUID WITH NON-FLAMMABLE ABSORBENT AND PLACE IN CONTAINER FOR  
DISPOSAL.

Neutralizing Agent:NOT RELEVANT

=====  
===== Handling and Storage =====

Handling and Storage Precautions:STORE SPRAY CANS IN COOL, WELL  
VENTILATED AREAS AWAY FROM SOURCES OF IGNITION & SUNLIGHT.

Other Precautions:"EMPTY" CONTAINERS RETAIN RESIDUE AND CAN BE  
DANGEROUS.

FOLLOW ALL LABEL INSTRUCTIONS. AVOID REPEATED/PROLONGED  
SKIN CONTACT. KEEP OUT OF REACH OF CHILDREN. DO NOT BREATHE VAPORS.  
DO NOT SPRAY TOWARD FACE/HOT SURFACES. WASH AFTER HANDLING.

=====  
===== Exposure Controls/Personal Protection =====

Respiratory Protection:IF TLV IS EXCEEDED, WEAR NIOSH-APPROVED ORGANIC  
VAPOR RESPIRATOR OR AIR-PURIFYING RESPIRATOR. IN EMERGENCY, WEAR A  
NIOSH-APPROVED POSITIVE-PRESSURE SELF-CONTAINED BREATHING  
APPARATUS.

Ventilation:

MECHANICAL (GENERAL AND/OR LOCAL EXHAUST, EXPLOSION-PROOF)  
VENTILATION TO MAINTAIN EXPOSURE BELOW TLV(S).

Protective Gloves:BUTYL IF SKIN CONTACT IS POSSIBLE

Eye Protection:CHEMICAL SAFETY GOGGLES/GLASSES

Other Protective Equipment:EYE WASH STATION & SAFETY SHOWERS SHOULD BE  
AVAILABLE IN THE IMMEDIATE VICINITY OF ANY POTENTIAL EXPOSURE.

Work Hygienic Practices:OBSERVE GOOD INDUSTRIAL HYGIENE PRACTICES AND  
RECOMMENDED PROCEDURES. WASH THOROUGHLY BEFORE EATING,  
DRINKING/SMOKING.

Supplemental Safety and Health

EXTREMELY FLAMMABLE. CONTENTS UNDER PRESSURE. CONTAINS FLAMMABLE GAS  
SUCH AS PROPANE AND FLAMMABLE LIQUID. DO NOT USE IN CONFINED AREA  
OR AREA WITH LITTLE AIR MOVEMENT. EMPLOY MEANS TO PREVENT VAPOR  
BUILDUP.

=====  
===== Physical/Chemical Properties =====

HCC:V3

NRC/State Lic Num:NOT RELEVANT

Vapor Pres:3862 @ 70F

Vapor Density:>1

Spec Gravity:1 (N-BUTYL ACETATE=1)

Solubility in Water:SLIGHT

Appearance and Odor:AEROSOL - SOLVENT

ODOR

Percent Volatiles by Volume:81- 89

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

Stability Condition to Avoid:HIGH HEAT, OPEN FLAMES, DIRECT SUNLIGHT,  
TEMPERATURES ABOVE 120F, SPARKS, SMOKING

Hazardous Decomposition Products:CARBON MONOXIDE, CARBON DIOXIDE

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE AND  
FEDERAL REGULATIONS. D

O NOT PUNCTURE, INCINERATE SPRAY CANS EVEN  
AFTER USE. DO NOT FLUSH INTO DRAINS. REUSING OR RECYCLING IS  
RECOMMENDED.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent  
professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.