View NSN Online: https://aerobasegroup.de/nsn/9150-00-993-8588

PIMA VALVE INC -- MOBIL DTE OIL HEAVY MEDIUM -- 9150-00-993-8588

Product ID:MOBIL DTE OIL HEAVY MEDIUM MSDS Date:12/07/1994 FSC:9150 NIIN:00-993-8588 MSDS Number: CFRFH === Responsible Party === Company Name: PIMA VALVE INC Address:6525 W. ALLISON RD Box:5010 **City:CHANDLER** State:AZ ZIP:85226-9405 Country:US Info Phone Num:520-796-1095 Emergency Phone Num:520-796-1 095 CAGE:MO457 === Contractor Identification === Company Name: MOBIL OIL CORP, NORTH AMERICAS MARKETING AND REFINING Address:3225 GALLOWS ROAD Box:City:FAIRFAX State:VA ZIP:22037 Country:US Phone:800-662-4525/ 856-224-4644 CAGE:3U728 Company Name: PIMA VALVE INC Address:6525 W. ALLISON RD Box:5010 City:CHANDLER State:AZ ZIP:85226-9405 Country:US Phone:520-796-1095 CAGE:MO457 Company Name: SALATHE OIL CO INC Address:2226 PETERS RD Box:City:HARVEY State:LA ZIP:70058 Country:US Phone:504-366-4542 CAGE

:0T5C6

Ingred Name:PRODUCT IS NOT FORMULATED TO CONTAIN INGREDIENTS WHICH HAVE EXPOSURE LIMITS ESTABLISHED BY REGULATORY AGENCIES. RTECS #:99999992Z Other REC Limits:NONE RECOMMENDED

LD50 LC50 Mixture:ORAL LD50 (RAT) IS >2000 MG/KG Routes of Entry: Inhalation:NO Skin:NO Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards A cute and Chronic: INGEST: PRACTICALLY NON-TOXIC. EYE'SKIN: PRACTICALLY NON-IRRITATING AND NON-SENSITIZING.INHAL:NO HAZARD EXPECTED. Explanation of Carcinogenicity: THERE ARE NO INGREDIENTS ABOVE 0.1% WHICH ARE IDENTIFIED AS CARCINOGENS BY NTP, IARC OR OSHA. Effects of Overexposure:NO SYMPTOMS ANTICIPATED. Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER. First Aid:SKIN:REMOVE CONTAMINATED CLOTHING;WAS H WITH SOAP AND WATER.EYES:FLUSH WITH WATER FOR 15 MINUTES.CALL PHYSICIAN IF IRRITATION OCCURS.INHAL:REMOVE TO FRESH AIR.GIVE OXYGEN OR ARTIFICIAL RESPIRATION IF N EEDED. INGEST: NOT EXPECTED TO BE A PROBLEM.IF MORE THAN 1 PINT IS INGESTED, DO NOT INDUCE VOMITING.GET PROMPT QUALIFIED MEDICAL ATTENTION. IF CONSCIOUS, GIVE 1-2 GLASSES OF WATER.

Flash Point Method:COC Flash Point:>400F,>204C Lower Limits:0.6 U

pper Limits:7.0 Extinguishing Media:WATER FOG, DRY CHEMICAL, CARBON DIOXIDE, FOAM. Fire Fighting Procedures: USE A SELF-CONTAINED BREATHING APPARATUS AND FULL PROTECTIVE EQUIPMENT.COOL FIRE EXPOSED CONTAINERS WITH WATER FOG. Unusual Fire/Explosion Hazard:NONE SPECIFIED BY MANUFACTURER. Spill Release Procedures: SOAK UP WITH NON-COMBUSTIBLE INERT ADSORBANT(EG.CLAY); PLACE COLLECTED MATERIAL IN AN APPROPRIATE CONTAINER FOR DISPOSAL; CLEAN SPILL AREA TO REMOVE SLIPPERINESS.AVOID RUNOFF INTO WATER WAYS.REPORT SPIL LS RESULTING IN SHEEN UPON WATER TO 800-424-8802. Neutralizing Agent:NOT APPLICABLE. Handling and Storage Precautions: STORE IN A COOL, DRY, WELL-VENTILATED PLACE. KEEP CONTAINER CLOSED WHEN NOT IN USE.KEEP AWAY FROM HEAT, SPARKS, FLAMES AND INCOMPATIBLE MATERIALS. Other Precautions:NONE SPECIFIED BY MANUFACTURER. ====== Respiratory Protection:NOT NEEDED IN NORMAL SERVICE. Ventilation: USE GENERAL DILUTION VENTILATION. Protective Gloves:NOT NEEDED IN NORMAL SERVICE. Eye Protection:SAFETY GLASSES Other Protective Equipment: PROVIDE A LOCAL EYE WASH STATION AND SAFETY SHOWER. Work Hygienic Practices: USE REASONABLE CARE IN HANDLING THIS PRODUCT.WASH HANDS AFTER USE AND BEFORE EATING. Supplemental Safety and Health NONE

----- Physical /Chemical Properties ------

HCC:V6 Boiling Pt:B.P. Text:>600F,>316C Vapor Pres:41CS@104F Solubility in Water:NEGLIGIBLE Appearance and Odor:LIQUID;LIGHT AMBER;MILD ODOR. Percent Volatiles by Volume: