

CHEVRON USA PRODUCTS CO -- JP-8, CPS243791 -- 9130-01-031-5816

=====
Product Identification
=====

Product ID:JP-8, CPS243791

MSDS Date:03/06/1994

FSC:9130

NIIN:01-031-5816

MSDS Number: CFTYR

=== Responsible Party ===

Company Name:CHEVRON USA PRODUCTS CO

Address:575 MARKET ST

City:SAN FRANCISCO

State:CA

ZIP:94105-2856

Country:US

Info Phone Num:415-894-1899;510-242-5357

Emergency Phone Num:800-231-0

623;800-424-9300(CHEMTREC)

CAGE:81230

=== Contractor Identification ===

Company Name:CHEVRON ENVIRONMENTAL HEALTH CENTER INC

Address:15299 SAN PABLO AVE

Box:4054

City:RICHMOND

State:CA

ZIP:94804

Country:US

Phone:800-582-3835

CAGE:0AHD1

Company Name:CHEVRON PRODUCTS COMPANY LUBRICANTS AND SPECIALTY PRODUCTS

Address:6001 BOLLINGER CANYON RD

Box:City:SAN RAMON

State:CA

ZIP:94583

Country:US

Phone:800-414-6737 / 800-582-3835

CAGE:81230

=====
Composition/Information on Ingredients
=====

====

Ingred Name:JET FUELS CONTAINING INGS 2,3,4 & 5
RTECS #:9999999ZZ
Fraction by Wt: 100%
OSHA PEL:N/K
ACGIH TLV:N/K

Ingred Name:KEROSENE; (ALIPHATIC PETROLEUM SOLVENT)
CAS:8008-20-6
RTECS #:OA5500000
OSHA PEL:N/K
ACGIH TLV:N/K

Ingred Name:KEROSENE, HYDRODESULFURIZED
CAS:64742-81-0
RTECS #:OA5510000
OSHA PEL:N/K
ACGIH TLV:N/K

Ingred Name:DISTILLATES (PETROLEUM), HYDRODESULFURIZED MIDDLE;
(DISTILLATES, HYDRODESULFURIZED MIDDLE)
CAS:64742-80-9
RTECS #:JN9202000
OSHA PEL:N/K
ACGIH
TLV:N/K

Ingred Name:GAS OIL, BLEND; (DISTILLATES, STRAIGHT RUN MIDDLE)
CAS:64741-44-2
RTECS #:LX3296000
OSHA PEL:N/K
ACGIH TLV:N/K

Ingred Name:SUPDAT:INHAL:PRLNGD BRTHG OF VAPS CAN CAUSE CNS EFTS. SIGNS
& SYMPS OF EXPOS: SKIN: MAY INCL PAIN/FEELING OF (ING 7)
RTECS #:9999999ZZ

Ingred Name:ING 6:HEAT, DISCOLORATION, SWELLING, AND BLISTERING. INHAL:
CNS EFTS MAY INCL 1 OR MORE OF FOLLOWING:HDCH, DIZZ, (ING 8)
RTECS #:9999999ZZ

Ingred Name:ING 7:LOSS OF APPETITE, WEAK AND LOSS OF COO

RDINATION.

CHRONIC: RPTS IN LITERATURE CONCLUDE THAT LONG-TERM EXPOS (ING 9)
RTECS #:9999999ZZ

Ingred Name:ING 8:TO JET FUELS MAY RSLT IN CHANGES IN 1)INCIDENCE &
PREVALENCE OF PSYCHIATRIC SYMPS 2)PSYCHOLOGICAL TESTS (ING 10)
RTECS #:9999999ZZ

Ingred Name:ING 9:AND 3)EEGS. THESE STUDIES WERE CONDUCTED IN SPECIFIC
WORK SITUATIONS WHERE THERE WERE EXPOS TO JET FUELS.(ING 11)
RTECS #:9999999ZZ

Ingred Name:ING 10:STUDIES HAVE BEEN REVIEWED & IT IS MFR OPINION THAT
WORK SITUATIONS
ARE TOO COMPLEX & ANALYTICAL METHS (ING 12)
RTECS #:9999999ZZ

Ingred Name:ING 11:THAT DEFINE BRAIN DMG ARE TOO IMPRECISE TO STATE
W/SCIENTIFIC CERTAINTY THAT EITHER CNDTNS OCCURS/IT WAS (ING 13)
RTECS #:9999999ZZ

Ingred Name:ING 12:DUE TO TYPE OF MATL DISCUSSED IN DOCUMENT.
CARCIN:PROD CONTAINS MIX OF PETRO HYDROCARBS CALLED MIDDLE (ING 14)
RTECS #:9999999ZZ

Ingred Name:ING 13:DISTIL (WHICH MEANS THEY BOIL BETWEEN APPROXIMATELY
350F & 750F). BECAUSE OF BROAD DESCRIPTION, MANY PROD
(ING 15)
RTECS #:9999999ZZ

Ingred Name:ING 14:ARE CONSIDERED MIDDLE DISTIL YET THEY ARE PRDCED BY
VARIETY OF DIFFERENT PETROL REFINING PROCESSES. TOX (ING 16)
RTECS #:9999999ZZ

Ingred Name:ING 15:DATA DEVELOPED ON SOME MIDDLE DISTIL FOUND THAT THEY
CAUSE POS RESPONSES IN SOME MUTAGENICITY TESTS & (ING 17)
RTECS #:9999999ZZ

Ingred Name:ING 16:CAUSED SKIN CANCER WHEN RPTDLY APPLIED TO MICE OVER
THEIR LIFETIME. PROD MAY CONTAIN SOME MIDDLE DISTIL(ING 18)
RTECS #:9999999ZZ

Ingred Nam

e:ING 17:FOUND TO CAUSE THOSE ADVERSE EFFECTS.
RTECS #:9999999ZZ

Ingred Name:FIRST AID PROC:PERS. IF MED ADVICE CANNOT BE OBTAINED, TAKE
PERSON & PROD CNTNR TO NEAREST MED EMER TREATMENT (ING 20)
RTECS #:9999999ZZ

Ingred Name:ING 19:CTR/HOSPITAL. IF ANY SIGNS/SYMPHS AS DESCRIBED OCCUR,
MOVE PERSON TO FRESH AIR. IF ANY OF THESE EFTS (ING 21)
RTECS #:9999999ZZ

Ingred Name:ING 20:CONTINUE, SEE MD. NOTE TO PHYS:INGEST OF
PROD/SUSSEQUENT VOMIT CAN RSLT IN ASPIR OF LIGHT HYDROCARB LIQ (I
NG
22)
RTECS #:9999999ZZ

Ingred Name:ING 21:WHICH CAN CAUSE PNEUMONITIS.
RTECS #:9999999ZZ

Ingred Name:SPILL PROC:SOIL & WATER & FROM ENTERING DRAINAGE & SEWAGE
SYS. CLEAN UP SM SPILLS USING APPROP TECHNIQUES SUCH (ING 24)
RTECS #:9999999ZZ

Ingred Name:ING 23:AS SORBENT MATLS/PUMPING. WHERE FEASIBLE & APPROP,
REMOVE CONTAMINATE SOIL. FOR MORE INFO CONT NEHC .
RTECS #:9999999ZZ

Ingred Name:OTHER PREC:AVIATION FUELS SHOULD BE FILTERED DURING
TRANSFER INTO FUEL TANKS.
RTECS #:99
99999ZZ

===== Hazards Identification =====

LD50 LC50 Mixture:LD50:(ORAL,RAT) >5 ML/KG
Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:ACUTE:EYE:NOT EXPECTED TO CAUSE
PRLNGD/SIGNIFICANT IRRITATION. SKIN:MOD IRRITANT SO CONT W/SKIN
COULD CAUSE PRLNGD(DAYS) INJURY TO AFFECTED AREA. DEGREE OF INJURY
WILL DEPEND ON AMT OF MATL THAT GETS ON SKIN & SPEED &

THOROUGHNESS OF FIRSTAID TREATMENT. IF ABSORBED THRU SKIN,
SUBSTANCE IS CONSIDERED (EFTS OF OVEREXP)

Explanation of Carcinogenicity:NOT RELEVANT.

Effects of Overexposure:HLTH HAZ:PRACTICALLY NON-TOX TO INTERNAL
ORGANS. INGEST:CONSIDERED PRACTICALLY NON-TOX TO INTERNAL ORGANS.
BECAUSE OF LOW VISCOSITY OF SUBSTANCE, IT CAN DIRECTLY ENTER LUNGS
IF IT IS SWALLOWED(THIS IS CALLED ASPIR). THIS CAN OCCUR DURING
ACT OF SWALLOWING/WHEN VOMIT SUBSTANCE. ONCE IN LUNGS, SUBSTANCE IS

VERY (SUPDAT)

Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

===== First Aid Measures =====

First Aid:EYE:NOT REQD. HOWEVER, AS PREC FLUSH W/FRESH WATER FOR @ LST
15 MINS. REMOVE CONT LENSES IF WORN. SKIN:REMOVE CONTAMD CLTHG.
WASH THORO W/SOAP & WATER. SEE MD IF ANY SIGNS/SYMP S DESCRIBED IN
DOCUMENT OCCUR. DISCARD CONTAMD NON-WATERPROOF SHOES & BOOTS. WASH
CONTAMD CLTHG. INGEST:GIVE WATER/MILK TO DRINK & TELEPHONE FOR
MED
ADVICE. DO NOT MAKE PERSON VOMIT UNLESS DIRECTED TO DO SO BY MED
(ING 19)

===== Fire Fighting Measures =====

Flash Point Method:TCC

Flash Point:100F,38C

Lower Limits:0.6%

Upper Limits:4.7%

Extinguishing Media:CO*2, DRY CHEMICAL, FOAM & WATER FOG.

Fire Fighting Procedures:NIOSH APPRVD SCBA & FULL PROT EQUIP . LIQ EVAP
& FORMS VAP(FUMES) WHICH CAN CATCH FIRE & BURN W/EXPLO VIOLENCE.
INVISIBLE VAP SPREADS EASILY & CAN(SUPDAT)

Unusual Fire/Exp

losion Hazard:NORMAL COMBUSTION FORMS CARBON DIOXIDE
AND WATER VAPOR; INCOMPLETE COMBUSTION CAN PRODUCE CARBON MONOXIDE.

===== Accidental Release Measures =====

Spill Release Procedures:ELIM ALL SOURCES OF IGNIT IN VICIN OF
SPILL/RELEASED VAP. CLEAN UP SPILLS IMMED, OBSERVING PREC IN EXPOS
CTLS/PERSONAL PROT SECTION. THIS MATL IS CONSIDERED TO BE WATER
POLLUTANT & RELEASES OF THIS PR OD SHOULD BE PVNTD FROM
CONTAMINATING (ING 23)

Neutralizing Age

nt:NONE SPECIFIED BY MANUFACTURER.

=====
Handling and Storage
=====

Handling and Storage Precautions:DO NOT USE/STORE NEAR FLAME,
SPARKS/HOT SURFS. USE ONLY IN WELL VENTILATED AREA. KEEP CNTNR
CLSD. DO NOT WELD, HEAT/DRILL CONTAINER.

Other Precautions:REPLACE CAP/BUNG. EMPTIED CNTNR STILL CONTAINS
HAZ/EXPLO VAP/LIQ. CAUTION! DO NOT USE PRESS TO EMPTY DRUM/DRUM MAY
RUPTURE W/EXPLO FORCE. WARNING! NOT FOR USE AS PORTABLE
HEATER/APPLIANCE FUE

L. TOX FU MES MAY ACCUM & CAUSE DEATH. (ING 25)

=====
Exposure Controls/Personal Protection
=====

Respiratory Protection:NO SPECIAL RESPIRATORY PROTECTION IS NORMALLY
REQUIRED. HOWEVER, IF OPERATING CONDITIONS CREATE HIGH AIRBORNE
CONCENTRATIONS, THE USE OF AN NIOSH APPROVED RESPIRATOR IS
RECOMMENDED.

Ventilation:USE THIS MATERIAL ONLY IN WELL VENTILATED AREAS.

Protective Gloves:IMPERVIOUS GLOVES .

Eye Protection:ANSI APPRVD CHEM WORKERS GOGGLES .

Other Protective

Equipment:ANSI APPRVD EYE WASH & DELUGE SHOWER .

Work Hygienic Practices:NONE SPECIFIED BY MANUFACTURER.

Supplemental Safety and Health

FIRE FIGHT PROC:BE SET ON FIRE BY MANY SOURCES SUCH AS PILOT LIGHTS,
WELDING EQUIPMENT, & ELECTRICAL MOTORS AND SWTICHES. FIRE HAZ IS
GREATER AS LIQUID TEMPERATURE RISES ABOVE 85F. READ ENTIRE DOCUMEN
T. EFTS OF OVEREXP:DIFFICULT TO REMOVE & CAN CAUSE SEVERE INJURY TO
LUNGS & DEATH. (ING 6)

=====
Physical/Chemical Properties
=====

Boiling Pt:B.P. Text:>320F,>160C

Melt/Freeze Pt:M.P/F.P Text:-40F,-40C

Vapor Pres:0.1 PSIA

Vapor Density:5.7

Spec Gravity:0.81

Evaporation Rate & Reference:NO DATA AVAILABLE

Solubility in Water:INSOLUBLE

Appearance and Odor:PALE YELLOW LIQUID WITH PETROLEUM ODOR.

Percent Volatiles by Volume:100

=====
Stability and Reactivity Data
=====

Stability Indicator/Materials to Avoid:YES

MAY REACT WITH STRONG OXIDIZING AGENTS, SUCH AS CHLORATES, NITRATES,

PEROXIDES, ETC.

Stability Condition to Avoid:NO DATA AVAILABLE.

Hazardous Decomposition Products:NORMAL COMBUSTION FORMS CARBON DIOXIDE AND WATER VAPOR; INCOMPLETE COMBUSTION CAN PRODUCE CARBON MONOXIDE.

===== Disposal Considerations =====

Waste Disposal Methods:PLACE CONTAMD MATLS IN DISPOSABLE CNTNRS & DISPOSE IF IN MANNER CONSISTENT W/APPLIC REGS. CONTACT FEDERAL, STATE, AND LOCAL ENVIRONMENTAL/HEALTH AUTHORITIES FOR APPRVD DISPOSAL OF THIS MATERIAL.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.