

ACCUMETRIC INC. -- SILICON ELASTOMER -- 8040-00-902-3871

===== Product Identification =====

Product ID:SILICON ELASTOMER
MSDS Date:05/05/1997
FSC:8040
NIIN:00-902-3871
Kit Part:Y
MSDS Number: CFWZD
=== Responsible Party ===
Company Name:ACCUMETRIC INC.
Address:350 RING ROAD
Box:843
City:ELIZABETHTOWN
State:KY
ZIP:42701
Country:US
Info Phone Num:502-769-3385
Emergency Phone Num:502-769-3385
Prepar
er's Name:GARY HARTLEDGE
CAGE:58149
=== Contractor Identification ===
Company Name:ACCUMETRIC INC
Address:350 RING RD
Box:843
City:ELIZABETHTOWN
State:KY
ZIP:42701
Country:US
Phone:502-769-3385
CAGE:58149

===== Composition/Information on Ingredients =====

Ingred Name:METHYLTRACETOXYSILANE
CAS:4253-34-3
RTECS #:VV4500000
Fraction by Wt: 2%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:10 PPM
ACGIH TLV:10 PPM, STEL 15

Ingred Name:ETHYLTRACETOXYSILANE
CAS:17689-77-9
Fraction by

Wt: 2%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:10 PPM
ACGIH TLV:10 PPM, STEL 15

Ingred Name:SILICA, AMORPHOUS
CAS:112945-52-5
RTECS #:VV7310000
Fraction by Wt: 10%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:10PPM
ACGIH TLV:10PPM, STEL 15

Ingred Name:VOC = 54G/L
RTECS #:9999999VO
Other REC Limits:NONE RECOMMENDED
OSHA PEL:NOT EST.

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO
IARC:NO OSHA:NO
Health Hazards Acute and Chronic:EYE: IRRITATION, REDNESS, SWELLING.
SKIN: IRRITATION. INHALE: IRRITATES EYES, NOSE, THROAT. INGESTION:
DIGESTIVE DISCOMFORT.
Medical Cond Aggravated by Exposure:PRE-EXISTING MEDICAL CONDITIONS MAY
BE ADVERSLY AFFECTED OR AGGRAVATED BY EXPOSURE. ALLERGIC REACTIONS
MAY RESULT.

===== First Aid Measures =====

First Aid:EYE: FLUSH W/WATER FOR 15 MINUTES, GET MED AID. SKIN: FLUSH
W/WATER, GET
MED AID. INHAL: REMOVE TO FRESH AIR.

===== Fire Fighting Measures =====

Flash Point Method:CC
Flash Point:212F,100C
Autoignition Temp:Autoignition Temp Text:NE
Extinguishing Media:WATER FOG, CO2, DRY CHEMICAL, FOAM
Fire Fighting Procedures:USE SCUBA AND PROTECTIVE CLOTHING

===== Accidental Release Measures =====

Spill Release Procedures:REMOVE PRODUCT, CONTAIN FOR DISPOSAL.

===== Handling and Storage =====

=====

Handling and Storage Precautions:STORE AT 90°F. KEEP CONTAINER CLOSED
WHEN NOT IN USE. KEEP AWAY FROM WATER/HUMID AIR. PROVIDE
VENTILATION WITHIN 10PPM OR USE RESP PROTECTION.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:YES, RECOMMENDED
Ventilation:LOCAL EXHAUST
Protective Gloves:NONE NEEDED
Eye Protection:SAFETY GLASSES
Work Hygienic Practices:WASH AFTER USE AND AT END OF SHIFT
Supplemental Safety and Health
NK

=====

===== Physical/Chemical Properties =====

HCC:F2
Boiling Pt:B.P. Text:NA
Melt/Freeze Pt:M.P/F.P Text:NA
Vapor Pres: