

KOP-COAT INC -- MIL-C-8514C YELLOW PRIMER -- 8030-01-015-6104

=====
Product Identification
=====

Product ID:MIL-C-8514C YELLOW PRIMER

MSDS Date:04/26/1995

FSC:8030

NIIN:01-015-6104

Kit Part:Y

MSDS Number: CFWZT

=== Responsible Party ===

Company Name:KOP-COAT INC

Address:436 7TH AVENUE

City:PITTSBURGH

State:PA

ZIP:15219-1818

Country:US

Info Phone Num:800-547-2468

Emergency Phone Num:800-548-0489 O

R 412-227-2700

Preparer's Name:L. BRIGGS

CAGE:00297

=== Contractor Identification ===

Company Name:KOP-COAT INC

Address:436 7TH AVENUE

City:PITTSBURGH

State:PA

ZIP:15219-1818

Country:US

Phone:800-553-5631, CHEMTREC 800-424-9300

CAGE:00297

=====
Composition/Information on Ingredients
=====

Ingred Name:ZINC CHROMATE

CAS:13530-65-9

RTECS #:GB3290000

Fraction by Wt: 5-10%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:.001 MG/M3

ACGIH TLV:0.1 MG/M3

Ingred Name:TALC

CAS:14807-96-6

RT

ECS #:MW2700000
Fraction by Wt: 1-5%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:2.0 MG/M3
ACGIH TLV:2.0 MG/M3

Ingred Name:TERPOLYMER OF POLYVINYL BUTYRAL ALCOHOL & ACETATE
CAS:27360-07-2
Fraction by Wt: 5-10%
Other REC Limits:NONE RECOMMENDED

Ingred Name:ETHYL ALCOHOL (ETHANOL) (SARA 313)
CAS:64-17-5
RTECS #:KQ6300000
Other REC Limits:NONE RECOMMENDED
OSHA PEL:1900 MG/M3
ACGIH TLV:1880 MG/M3

Ingred Name:METHYL ALCOHOL (METHANOL) (SARA 313) (CERCLA)
CAS:67-56-1
RTECS #:PC1400000
Fraction by Wt
: 1-5%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:260 MG/M3/325
ACGIH TLV:262 MG/M3/STEL 328
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:ISOPROPYL ALCOHOL (SARA 313)
CAS:67-63-0
RTECS #:NT8050000
Fraction by Wt: 5-10%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:980 MG/M3/STEL 1225
ACGIH TLV:983 MG/M3/STEL 1230

Ingred Name:CHROMIUM (SARA 313) (CERCLA)
CAS:7440-47-3
RTECS #:GB4200000
Fraction by Wt: 1-5%
Other REC Limits:NONE RECOMMENDED
EPA Rpt Qty:1 LB
DOT Rpt Qty:1 LB

Ingred Name:SE

C-BUTYL ALCOHOL (SARA 313)

CAS:78-92-2

RTECS #:EO1750000

Fraction by Wt: 15-20%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:305 MG/M3/STEL 455

ACGIH TLV:303 PPM

Ingred Name:VOC = 42 G/L

RTECS #:9999999VO

Other REC Limits:NONE RECOMMENDED

OSHA PEL:NOT RELEVANT

ACGIH TLV:NOT RELEVANT

=====
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:EYE

S: IRRITATION, TEARING, CORNEAL

DAMAGE. SKIN: DERMATITIS, SENSITIZATION, DEFATTING, DRYING,
REDNESS, CRACKING, BLISTERING, IRRITATION. INHAL: MUCOUS MEMBRANE,
IRRITATION, KIDNEY/LIVER DAMAGE, RESPI RATORY TRACT IRRIT, CNS
DEPRESSION, (HEADACHE, WEAKNESS, DIZZY, INCOORDINATION & POSSIBLE
COLAPSE). LUNG CHANGES. *

Effects of Overexposure:* GI IRRITATION, ABDOMINAL PAIN, NAUSEA, VOMIT,
DIARRHEA, CHEMICAL PNEUMONITIS/FATAL.

=====
===== First Aid Measures =====

First Aid:EYE: FLUSH W/WATER FOR 15 MINUTES, GET MED AID. SKIN: WASH
W/SOAP & WATER. REMOVE, CONTAM CLOTHES, WASH BEFORE REUSE. GET MED
AID. INHAL: GET FRESH AIR. GIVE OXYGEN/ARTIF RESP IF NEEDED, GET
MED AID. INGEST: DONT INDUCE VOMIT, DRINK WATER/MILK, GET MED AID
IMMED.

=====
===== Fire Fighting Measures =====

Flash Point:52.0F,11.1C

Extinguishing Media:DRY CHEMICAL, CARBON DIOXIDE, WATER SPRAY, FOAM.

Fire Fighting Procedures:U

SE PROTECTIVE EQUIPMENT, SCBA OR FULLFACE MASK. USE WATER TO COOL CONTAINERS.

===== Accidental Release Measures =====

Spill Release Procedures:ELIMINATE IGNITS. VENTILATE AREA. USE INERT ABSORBENT TO CLEAN UP.

===== Handling and Storage =====

Handling and Storage Precautions:KEEP IN A CLOSED LABELED CONTAINER, COOL, DRY VENTILATED AREA. KEEP CONTAINERS CLOSED. KEEP AWAY FROM IGNITS & HEAT.

Other Precautions:DO NOT USE UNTIL MANUFACTURER'S PRECAUTIONS HAVE BEEN READ/UNDERSTOOD.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:REQUIRED.

Ventilation:REQUIRED.

Protective Gloves:CHEMICAL RESISTANT, FLEXIBLE.

Eye Protection:SAFETY GLASSES W/FACE/SIDE SHIELDS.

Other Protective Equipment:EYEWASH STATION, SAFETY SHOES, HEAD/NECK COVER, APRON, JACKET, ETC.

Work Hygienic Practices:WASH HANDS AFTER USE.

Supplemental Safety and Health

NK

===== Physical/Chemical Properties =====

Vapor Density:>1.0

Spec Gravity:4.038

Evaporation Rate & Reference: