

COURTAULDS AEROSPACE INC -- PR-1425 B-2, 1425 B 16, ACCELERATOR -- 8030-01-129-1141  
===== Product Identification =====

Product ID:PR-1425 B-2, 1425 B 16, ACCELERATOR

MSDS Date:09/12/1996

FSC:8030

NIIN:01-129-1141

Kit Part:Y

MSDS Number: CFXBM

=== Responsible Party ===

Company Name:COURTAULDS AEROSPACE INC

Address:5430 SAN FERNANDO ROAD

Box:1800

City:GLENDALE

State:CA

ZIP:91209

Country:US

Info Phon

e Num:818-240-2060

Emergency Phone Num:800-228-5635/800-424-9300(CHEMTREC)

CAGE:83574

=== Contractor Identification ===

Company Name:PRC-DESOTO INTERNATIONAL, INC. A PPG INDUSTRIES COMPANY

Address:5430 SAN FERNANDO RD

Box:1800

City:GLENDALE

State:CA

ZIP:91209

Country:US

Phone:818-240-2060

CAGE:83574

===== Composition/Information on Ingredients =====

Ingred Name:DIMETHYL ACETAMIDE (VP = 2)

CAS:127-19-5

RTECS #:AB7700000

Fraction by Wt: 30.0%

Other REC Limits:NONE RECOMMENDED

O

SHA PEL:10 PPM  
ACGIH TLV:10 PPM

Ingred Name:CALCIUM DICHROMATE  
CAS:14307-33-6  
RTECS #:HX7630000  
Fraction by Wt: 20.0%  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:0.1 MG/M3 STEL  
ACGIH TLV:0.05 MG/M3

Ingred Name:TALC  
CAS:14807-96-6  
RTECS #:WW2710000  
Fraction by Wt: 10.0%  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:2 MG/M3  
ACGIH TLV:2 MG/M3

Ingred Name:SILICA DERIVATIVES (NON HAZARDOUS)  
CAS:67762-90-7  
Other REC Limits:NONE RECOMMENDED

Ingred Name:WATER (NON HAZARDOUS)  
CAS:7732-18-5  
RTECS #:ZC0110  
000  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:NOT RELEVANT  
ACGIH TLV:NOT RELEVANT

Ingred Name:HYDRATED ALUMINUM SILICATE (NON HAZARDOUS)  
CAS:1335-30-4  
Other REC Limits:NONE RECOMMENDED

Ingred Name:MAGNESIUM ALUMINUM SILICATE (NON HAZARDOUS)  
CAS:8031-18-3  
Other REC Limits:NONE RECOMMENDED

Ingred Name:CARBON BLACK  
CAS:1333-86-4  
RTECS #:FF5800000  
Fraction by Wt: 200F,>93C  
Extinguishing Media:CARBON DIOXIDE, FOAM, DRY CHEMICAL, WATER.  
Fire Fighting Procedures:USE AIR SUPPLIED RESPIRATOR

=====

===== Accidental Release Measures =====

Spill Release Procedures:SCOOP INTO CONTAINER. CLEAN UP RESIDUE W/SUITABLE SOLVENT.

===== Handling and Storage =====

Handling and Storage Precautions:DONT STORE >120F. KEEP CONTAINER TIGHTLY CLOSED WHEN NOT IN USE.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE ORGANIC VAPOR CARTRIDGE OR AIR-SUPPLIED RESPIRATOR.

Ventilation:GENERAL VENTILATION.

Protective Gloves:SOLVENT RESISTANT.

Eye Protection:SAFETY GLASSES.

Supplemental Safety and Health  
NK

===== Physical/Chemical Properties =====

Vapor Density:>AIR

Spec Gravity:1.345

Evaporation Rate & Reference:UNAVAILABLE

Appearance and Odor:BLACK PASTE

Percent Volatiles by Volume:1.5

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS

Hazardous Decomposition Products:CA

RBON MONOXIDE, CARBON DIOXIDE,

SULFUR DIOXIDE, TRACES OF HYDROGEN SULFIDE.

===== Disposal Considerations =====

Waste Disposal Methods:IN COMPLIANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be a

ccurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.