

DURANT PAINT -- TT-E-2784A -- 8010-01-333-9439

===== Product Identification =====

Product ID:TT-E-2784A
MSDS Date:09/15/1997
FSC:8010
NIIN:01-333-9439
MSDS Number: CFXCY
=== Responsible Party ===
Company Name:DURANT PAINT
Address:960 BROADWAY
City:REVERE
State:MA
ZIP:02051
Country:US
Info Phone Num:617-289-1400
Emergency Phone Num:617-289-1400
CAGE:NO367
=== Contractor Identification ===
Company Name:DURANT PAINT
Address:950 BROADWAY
Box:City:REVERE
State:MA
ZIP:02051
Country:US
Phone:617-289-1400
CAGE:NO367
Company Name:DURANT PAINTS INC
Address:112 RAILROAD ST
Box:City:REVERE
State:MA
ZIP:02151-4007
Country:US
Phone:781-289-8415
CAGE:3F338

===== Composition/Information on Ingredients =====

Ingred Name:GLYCOL ETHER (VAPOR PRESSURE 25%)
CAS:111-77-3
RTECS #:KL6125000
Fraction by Wt: 7.20%
Other REC Limits:NONE RECOMMENDED

Ingred Name:GLYCOL ETHER (VAPOR PRESSURE 0.1%)

)
CAS:770-35-4
Fraction by Wt: 1.30%
Other REC Limits:NONE RECOMMENDED

Ingred Name:VOC = 1.46 G/L, NON-EXEMPT SOLVENT PER ADJUSTED GALLON.
RTECS #:9999999VO
Other REC Limits:NONE RECOMMENDED

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:EYE: IRRITATION. SKIN: IRRITATION.
INHAL: IRRITATING TO NOSE/THROAT. INGEST:TOXIC.
Effects
of Overexposure:INHAL: HEADACHE, NAUSEA, VOMITING, DROWSINESS.
Medical Cond Aggravated by Exposure:HEART CONDITIONS, ASTHMA.

===== First Aid Measures =====

First Aid:EYE: FLUSH W/WATER FOR 15 MINUTES, GET MED AID. SKIN: WASH
W/SOAP & WATER. REMOVE CONTAIN CLOTHES. INHAL: GET FRESH AIR. OXGEN
IF NEEDED. INGEST: GIVE TWO GLASSES OF WATER. INDUCE VOMIT.

===== Fire Fighting Measures =====

Flash Point:NONFLAMMBLE
Ext
inguishing Media:CO2, FOAM.
Fire Fighting Procedures:USE FULL PROTECTIVE GEAR.
Unusual Fire/Explosion Hazard:COOL CONTAINERS W/WATER STEAM IN EVENT OF
A FIRE.

===== Accidental Release Measures =====

Spill Release Procedures:DIKE & CONTAIN. SOAK UP RESIDUE W/ABSORBENT
MATERIAL.

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN A COOL, DRY PLACE. PROTECT
FROM FREEZING.

===== Exposure C

ontrols/Personal Protection =====

Respiratory Protection:REQUIRED.

Ventilation:REQUIRED.

Protective Gloves:REQUIRED.

Eye Protection:REQUIRED.

Other Protective Equipment:APRON.

Work Hygienic Practices:WASH AFTER HANDLING.

Supplemental Safety and Health

NK

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:212F,156C

Vapor Density:>AIR

Evaporation Rate & Reference:VALUE NOT STATED

Solubility in Water:100%

Percent Volatiles by Volume:58.9

=====

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

OXIDIZING MATERIALS.

Stability Condition to Avoid:HEAT, SPARKS & OPEN FLAME.

Hazardous Decomposition Products:CARBON MONOXIDE & UNIDENTIFIED ORGANIC COMPOUNDS.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF IN RECKA APPROVED FACILITY.

Disclaimer (provided with this information by the compiling agencies):

This information is for

mulated for use by elements of the Department

of Defense. The United States of America in no manner whatsoever,

expressly or implied, warrants this information to be accurate and

disclaims all liability for its use. Any person utilizing this

document should seek competent professional advice to verify and

assume responsibility for the suitability of this information to their

particular situation.