View NSN Online: https://aerobasegroup.de/nsn/8030-01-364-3886

PRODUCTS RESEARCH & CHEMICAL CORP. -- EPOXY RESIN COMPOUND PR1828 B1/4

8030-01-364-3886

============= Product Identification =================

Product ID:EPOXY RESIN COMPOUND PR1828 B1/4

MSDS Date:02/03/1994

FSC:8030

NIIN:01-364-3886

Kit Part:Y

MSDS Number: CFXHV === Responsible Party ===

Company Name: PRODUCTS RESEARCH & CHEMICAL CORP.

Address:5430 SAN FERNANDO RD.

Box:1800

City:GLENDALE

State:CA ZIP:91209 Country

:US

Info Phone Num:818-240-2060

Emergency Phone Num:800-228-5635 Preparer's Name:SEROJE HARTOONIANI

CAGE:DO563

=== Contractor Identification ===

Company Name: PRC-DESOTO INTERNATIONAL, INC. A PPG INDUSTRIES COMPANY

Address:5430 SAN FERNANDO RD

Box:1800

City:GLENDALE

State:CA ZIP:91209 Country:US

Phone:818-240-2060

CAGE:83574

Company Name: PRODUCTS RESEARCH & CHEMICAL

Address: NOW DBA COURTAULDS AEROSPACE

Box:1800

City:GLENDALE

State:CA ZIP:91209

Phone:818-240-2060

CAGE:DO563

====== Composi

tion/Information on Ingredients ========
Ingred Name:EPOXY NOVOLAC RESIN CAS:28064-14-4 Fraction by Wt: 25.0% Other REC Limits:NONE RECOMMENDED
Ingred Name:HYDANTOIN EPOXY RESIN CAS:15336-82-0 Fraction by Wt: 35.0% Other REC Limits:NONE RECOMMENDED
Ingred Name:CALCIUM CARBONATE (MARBLE) (LIMESTONE) CAS:1317-65-3 RTECS #:EV9580000 Fraction by Wt: 35.0% Other REC Limits:NONE RECOMMENDED OSHA PEL:15 MG/M3 ACGIH TLV:10 MG/M3
Ingred Name:ORGANOSILANE ESTER (VP = 1.0) CAS:2530-83-8 RTECS #:V V4025000 Fraction by Wt: 5.0% Other REC Limits:NONE RECOMMENDED =================================
LD50 LC50 Mixture:IN HEALTH HAZARDS. Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:EYE: IRRIT, BURN, TEARING, RED, CORROSIVE. SKIN: IRRIT, ALLERGIC REACTION, CORROSIVE, SYSTEMATIC POISONING. INGEST: ABDOMINAL PAIN, NAUSEA, VOMIT, TOXIC. ORAL LD50 FOR RATS IS >4000 MG/KG. LD50 IS 250 MG/KG (RAT). INHAL: IRRITATION. LC50 >4.1 MG/M3 AIR FOR 4-HOUR EXPOSURE.
======================================
First Aid:EYE: FLUSH W/LUKEWARM WATER FOR 15 MINUTES, GET MED AID. SKIN: WASH W/SOAP & WATER, GET MED AID. INHAL: GET FRESH AIR, GET MED AID. INGEST: DRINK LARGE AMOUNTS OF WATER, DONT INDUCE VOMIT, GET MED AID.
======================================
Flash Point:>200F,>93C Exti

nguishing Media:CARBON DIOXIDE, DRY CHEMICAL, FOAM, WATER FOG. Fire Fighting Procedures:USE AIR SUPPLIED RESPIRATOR.
======================================
Spill Release Procedures:SCOOP INTO CONTAINER. CLEAN UP RESIDUE W/SUITABLE SOLVENT.
====== Exposure Controls/Personal Protection =======
Respiratory Protection:NOT REQUIRED. Ventilation:GENERAL. Protective Gloves:RUBBER OR PLASTIC. Eye Protection:SAFETY GLASSES. Work Hygienic Practices:WASH THOROUGHLY AFTER HANDLING OR BEFORE SMOKING OR EATING. Supplemental Safety and Health NK
======== Physical/Chemical Properties =========
Vapor Density:NONVOLATIL Spec Gravity:1.45 pH:NA Evaporation Rate & mp; Reference:NONVOLATILE Solubility in Water:SLIGHT Appearance and Odor:PURPLE PASTE. Percent Volatiles by Volume:0.7 Corrosion Rate:NA
========= Stability and Reactivity Data =========
Stability Indicator/Materials to Avoid:YES STRONG AMINES. Haz ardous Decomposition Products:OXIDES OF CARBON & OXIDES OF SILICON MAY EVOLVE.
======= Disposal Considerations ===========
Waste Disposal Methods:DISPOSE OF IN ACCORDANCE W/FEDERAL, STATE & LOCAL REGULATIONS.
Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department

of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this informati

on to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.