View NSN Online: https://aerobasegroup.de/nsn/6850-01-446-8061 P-T TECHNOLOGIES INC -- REMOVE-HP -- 6850-01-446-8061 Product ID:REMOVE-HP MSDS Date:04/29/1997 FSC:6850 NIIN:01-446-8061 MSDS Number: CFYJV === Responsible Party === Company Name:P-T TECHNOLOGIES INC Address:108 4TH AVENUE, SOUTH City:SAFETY HARBOR State:FL ZIP:34695 Country:US Info Phone Num:800-441-7874 / 813-726-4644 Emergency Phone Num:800-441-7874 / 813-726 -4644 CAGE:0JVH6 === Contractor Identification === Company Name:P-T TECHNOLOGIES INC Address: 108 4TH AVENUE, SOUTH Box:City:SAFETY HARBOR State:FL ZIP:34695 Country:US Phone:813-726-4644 CAGE:0JVH6

====== Composition/Information on Ingredients =======

Ingred Name: HEAVY AROMATIC NAPHTHA (SOLVENT NAPHTHA) CAS: 64742-94-5

CAS:64742-94-5 RTECS #:WF3100000

Other REC Limits: NONE RECOMMENDED

Ingred Name: ETHYL LACTATE

CAS:97-64-3

RTECS #:OD5075000

Other REC Limits: NONE RECOMMENDED

| == Hazards Identification ============ |
|---|
| Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:EYE-MAY CAUSE IRRITATION. SKIN-MAY CAUSE DEFATTING OR DRYNESS OF SKIN. CONTINUED DRYNESS MAY CAUSE DERMATITIS. INHALATION-CAN CAUSE IRRITATION OF THE RESPIRATORY TRACT. INGESTION-MAY CAUSE GASTROINTES TINAL IRRITATION. Explanation of Carcinogenicity:NOT CARCINOGENIC. |
| Effects of Overexposure:EY E-TEARING AND REDNESS. INHALATION-NAUSEA, DIZZINESS OR HEADACHE. INGESTION-NAUSEA AND VOMITING. Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER. |
| ====================================== |
| First Aid:EYE-FLUSH WITH WATER FOR 15 MIN. IF IRRITATION PERSISTS, CONTACT PHYSICIAN. SKIN-WASH THOROUGHLY WITH SOAP AND WATER. REMOVE CONTAMINATED CLOTHING. INHALATION-IF AFFECTED BY VAPOR, GET TO FRESH AIR. I F BREATHING IS DIFFICULT, SEE PHYSICIA N.INGESTION-DO |
| NOT INDUCE VOMITING. PRODUCT CONTAINS HYDROCARBONS. CONSULT PHYSICIAN. |
| ========== Fire Fighting Measures =========== |
| Flash Point Method:TCC Flash Point:133F,56C Autoignition Temp:Autoignition Temp Text:410F Extinguishing Media:EXTINGUISH WITH CARBON DIOXIDE, FOAM OR DRY CHEMICAL. CLASS B FIRE PROCEDURES. Fire Fighting Procedures:COMBUSTIBLE LIQUID. CAN FORM COMBUSTIBLE MIXTURES AT OR ABOVE FLASH POINT. Unusual Fire/Explosion Hazard:NONE KNO WN. |
| ======== Accidental Release Measures ========= |
| Spill Release Procedures:REMOVE IGNITION SOURCES. CONTAIN THE SPILL. RECOVER FREE PRODUCT. ABSORB WITH SUITABLE CHEMICAL ABSORBENT FOR DISPOSAL VIA INCINERATION OR BURIAL IN APPROVED LANDFILL. Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER. |
| =========== Handling and Storage ============= |
| Handling and Storage Precautions:AMBIENT. Other Precautions:KEEP AWAY FROM HEAT SOURCES, OPEN FLAMES, AN |

D OTHER IGNITION SOURCES.

====== Exposure Controls/Personal Protection ========

Respiratory Protection: NONE SPECIFIED BY MANUFACTURER.

Ventilation:NORMAL ROOM VENTILATION IS USUALLY ADEQUATE. USE FANS OR OTHER MECHANICAL VENTILATION IN ENCLOSED AREAS.

Protective Gloves:SOLVENT RESISTANT GLOVES RECOMMENDED.

Eye Protection: SAFETY GLASSES RECOMMENDED.

Other Protective Equipment: NONE SPECIFIED BY MANUFACTURER.

Work Hygienic Practices: WASH THOROUGHLY AFTER HANDLING.

Supplement

al Safety and Health

======== Physical/Chemical Properties ===========

HCC:F4
Vapor Pres:1

Spec Gravity:.9631 Solubility in Water: