

P-T TECHNOLOGIES INC -- IG-QD SOLVENT -- 6850-01-446-8534

===== Product Identification =====

Product ID:IG-QD SOLVENT

MSDS Date:05/15/1997

FSC:6850

NIIN:01-446-8534

MSDS Number: CFZDY

=== Responsible Party ===

Company Name:P-T TECHNOLOGIES INC

Address:108 4TH AVENUE, SOUTH

City:SAFETY HARBOR

State:FL

ZIP:34695

Country:US

Info Phone Num:800-441-7874 / 813-726-4644

Emergency Phone Num:800-441-7874 /

813-726-4644

CAGE:0JVH6

=== Contractor Identification ===

Company Name:P-T TECHNOLOGIES INC

Address:108 4TH AVENUE, SOUTH

Box:City:SAFETY HARBOR

State:FL

ZIP:34695

Country:US

Phone:813-726-4644

CAGE:0JVH6

===== Composition/Information on Ingredients =====

Ingred Name:NON-HAZARDOUS INGREDIENTS

Fraction by Wt: NONE

Other REC Limits:NONE RECOMMENDED

Ingred Name:MINERAL SPIRITS

CAS:64475-85-0

RTECS #:PY8240000

Other REC Limits:NONE RECOMMENDED

===== Hazards Id

entification =====

LD50 LC50 Mixture:EXPOSURE LIMITS: 8 HRS TWA (PPM)

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:EYE-MAY CAUSE SLIGHT IRRITATION.

SKIN-MAY IRRITATE AND CAUSE DERMATITIS. INHALATION-CAN CAUSE IRRITATION OF THE RESPIRATORY TRACT. INGESTION-MAY CAUSE GASTROINTESTINAL IRRITATION. MAY CAUSE INJURY IF ASPIRATED INTO LUNGS.

Explanation of Carcinogenicity

:NOT CARCINOGENIC.

Effects of Overexposure:INHALATION-NAUSEA, DIZZINESS OR HEADACHE OR OTHER CENTRAL NERVOUS SYSTEM EFFECT. INGESTION-NAUSEA AND VOMITING.

Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

===== First Aid Measures =====

First Aid:EYE-FLUSH WITH WATER FOR 15 MIN. IF IRRITATION PERSISTS, CONTACT PHYSICIAN. SKIN-WASH THOROUGHLY WITH SOAP AND WATER. REMOVE CONTAMINATED CLOTHING. INHALATION-IF AFFECTED BY VAPORS, GET TO FRESH AIR. IF BREATHING IS DIFFICULT, SEE PHYSICIAN. INGESTION-DO NOT INDUCE VOMITING. PRODUCT CONTAINS HYDROCARBONS. CONSULT PHYSICIAN.

===== Fire Fighting Measures =====

Flash Point Method:TCC

Flash Point:104F,40C

Autoignition Temp:Autoignition Temp Text:559F

Lower Limits:1.2

Upper Limits:9.6

Extinguishing Media:EXTINGUISH WITH CARBON DIOXIDE, FOAM OR DRY CHEMICAL. CLASS B FIRE PROCEDURES.

Fire Fighting Procedures:COMBUSTIBLE LIQUID. CAN FORM COMBUSTIBLE

MIXTURES AT OR ABOVE FLASH POINT.

Unusual Fire/Explosion Hazard:NONE SPECIFIED BY MANUFACTURER.

===== Accidental Release Measures =====

Spill Release Procedures:REMOVE IGNITION SOURCES. CONTAIN THE SPILL. RECOVER FREE PRODUCT. ABSORB WITH SUITABLE CHEMICAL ABSORBENT FOR DISPOSAL VIA INCINERATION OR BURIAL IN APPROVED LANDFILL.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

===== Handling and Storage =====

=====

Handling and Storage Precautions:AMBIENT.

Other Precautions:KEEP AWAY FROM HEAT SOURCES, OPEN FLAMES AND OTHER
IGNITION SOURCES.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE SPECIFIED BY MANUFACTURER.

Ventilation:NORMAL ROOM VENTILATION IS ADEQUATE. USE FANS OR OTHER
MECHANICAL VENTILATION IN ENCLOSED AREAS.

Protective Gloves:SOLVENT RESISTANT GLOVES ARE RECOMMENDED

Eye Protection:SAFETY GLASSES ARE RECOMMENDED.

Other Protect

ive Equipment:NONE SPECIFIED BY MANUFACTURER.

Work Hygienic Practices:WASH THOROUGHLY AFTER HANDLING.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:F4

Boiling Pt:B.P. Text:319F,159C

Vapor Pres:2 MMHG

Vapor Density:>1

Spec Gravity:0.75

VOC Pounds/Gallon:745

Evaporation Rate & Reference: