

DEVOE COATINGS CO DIV OF GROW GROUP INC -- DEVGRIP 137 EPOXY PRIMER NONSKID DARK GRAY BASE #137B0248 -- 8010-01-397-3986

===== Product Identification =====

Product ID:DEVGRIP 137 EPOXY PRIMER NONSKID DARK GRAY BASE #137B0248

MSDS Date:06/02/1995

FSC:8010

NIIN:01-397-3986

Kit Part:Y

MSDS Number: CGFJT

=== Responsible Party ===

Company Name:DEVOE COATINGS CO DIV OF GROW GROUP INC

Address:4000 DUPON

T CIR

Box:7600

City:LOUISVILLE

State:KY

ZIP:40207-4802

Country:US

Info Phone Num:502-897-9861

Emergency Phone Num:800-424-9300

Preparer's Name:LOUIS F. HOLZKNECHT

CAGE:1HK86

=== Contractor Identification ===

Company Name:DEVOE COATINGS CO

Address:4000 DUPONT CIRCLE

Box:7600

City:LOUISVILLE

State:KY

ZIP:40207-4802

Country:US

Phone:502-897-9861

CAGE:1HK86

===== Composition/Information on Ingredients =====

Ingred Name:CARBON BLACK

CAS:1333-86-4

RTECS #:FF5800000

Fraction by Wt:

15 MIN. GET MED AID. SKIN:

WASH W/SOAP & WATER. REMOVE CONTAM CLOTHES. GET MED AID IF IRRIT PERSISTS. INGESTION: CALL DR. IMMEDIATE. DON'T INDUCE VOMITING. CHEM PNEUMONITIS W/ASPIRATION OF VOMITUS, POSSIBLY FATAL. INHAL: GET FRESH AIR IF TROUBLE BREATHING. IF CONTINUED TROUBLE BREATHING GET IMMEDIATE MED AID. BREATHING STOPPED, RESTORE BREATHING W/CPR. GET IMMEDIATE MED AID.

=====
===== Fire Fighting Measures =====

Flash Point:100F,38C

Lower Limits:1.0

Extinguishing Media:CO2, DRY CHEMICAL, FOAM (CLASS B FIRE).

Fire Fighting Procedures:FULL PROTECT EQUIP W/SCBA. WATER SPRAY MAY BE INEFFECTIVE, FOG NOZZLES PREFERRED. COOL FIRE-HEAT EXPOSED CLSD CNTNRS. PREVENT PRESSURE BUILD-UP/AUTOIGNITION.

Unusual Fire/Explosion Hazard:KEEP CNTNRS TIGHTLY CLSD. KEEP FROM HEAT/ELECTRICAL EQUIP/SPARKS/FLAME. CLSD CNTNRS MAY EXPLODE IN EXTREME HEAT. DON'T CUT/WELD ON/NEAR CNTNR AS MAY IGNITE.

=====
===== Accidental Release Measures =====

Spill Release Procedures:REMOVE IGNIT SOURCES. AVOID BREATHING VAPORS. VENTILATE AREA. BEFORE CLEAN-UP REFER TO HAZ CAUTION INFO. CONTAIN SPILL/REMOVE W/INERT ABSORBENT/NONSPARKING TOOLS. STORE IN CLOSED CONTAINER UNTIL PROPERLY DISPOSED OF.

=====
===== Handling and Storage =====

Handling and Storage Precautions:ISOLATE FROM HEAT/SPARKS/FLAMES. DON'T SMOKE. PREVENT VAPOR BUILD-UP W/CONTINUOUS FLOW FRESH AIR. DON'T STORE >120F, NE

AR FIRE/OPEN FLAME. STORE LG*

Other Precautions:AMTS IN BUILDINGS TO COMPLY W/OSHA 1910.106. KEEP CNTNR CLSD WHEN NOT USING. DON'T TRANSFER TO BOTTLES/UNLABELED CNTNRS. DON'T REUSE EMPTY CNTNRS. IF MAT'L PART OF 2 COMPONENT PROD, MIXTURE WILL HAVE HAZARDS OF BOTH COMPONENTS.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:DON'T BREATHE VAPORS/SPRAY MIST/SANDING DUST.NIOSH/MSHA APPROVED MECHANICAL FILTER RESPIRATOR IN RESTRICTED VENTILATION

TION, NIOSH/MSHA APPROVED CHEM/MECHANCL FILTER FOR
PARTICULATES/VAPOR.CONFINED AREAS, NIOS H/MSHA APPROVED AIR-SUPPLY
RESPRTR/HOODS

Ventilation:GEN DILUTION/LOCAL EXHAUST VENT. TO KEEP AIR CONTAM CONC