

MINNESOTA MINING MFG CO DENTAL PROD DIV -- 5905WS SCOTCHBOND MULTIPURPOSE
PRIMER -- 6520-01-394-5421

===== Product Identification =====

Product ID:5905WS SCOTCHBOND MULTIPURPOSE PRIMER

MSDS Date:02/26/1997

FSC:6520

NIIN:01-394-5421

Kit Part:Y

MSDS Number: CGKYQ

=== Responsible Party ===

Company Name:MINNESOTA MINING MFG CO DENTAL PROD DIV

Address:3M CENTER

City:ST PAUL

State:MN

ZIP:55144-1000

Coun

try:US

Info Phone Num:612-733-1110

Emergency Phone Num:612-733-1110

CAGE:76381

=== Contractor Identification ===

Company Name:MINNESOTA MINING AND MFG CO, DBA 3M

Address:3M CENTER BLDG 224-5S-04

Box:City:SAINT PAUL

State:MN

ZIP:55144-1000

Country:US

Phone:866-556 5712 / 612-733-1110

CAGE:76381

Company Name:MINNESOTA MINING AND MFG CO DENTAL PRODUCTS DIV

Address:3M CENTER

Box:City:SAINT PAUL

State:MN

ZIP:55144-1000

Country:US

Phone:800-364-3577/651-737-6501

CAGE:0K0U5

===== Composition

/Information on Ingredients =====

Ingred Name:WATER
CAS:7732-18-5
RTECS #:ZC0110000
Fraction by Wt: 43%

Ingred Name:HYDROXYETHYL METHACRYLATE, ETHYLENE GLYCOL METHACRYLATE
CAS:868-77-9
RTECS #:OZ4725000
Fraction by Wt: 35-40%

Ingred Name:POLYCARBOXYLIC ACID COPOLYMER
Fraction by Wt: 10-15%

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards A

cute and Chronic:EYES: SEVERE IRRITATION. SKIN:
ALLERGIC REACTION & MILD IRRITATION. INHALATION: UPPER RESPIRATORY
IRRITATION. INGESTION: GI IRRITATION TISSUES & IRRITATION OF THE
ORAL MUCOSA. VEHICLES CAN ALTER SKIN ABSORPTION.

Explanation of Carcinogenicity:NONE

Effects of Overexposure:IRRITATION, REDNESS, SWELLING, PAIN, TEARING,
CLOUDYNESS, IMPAIRED VISION, BLISTERING, ITCHING, SORENESS,
COUGHING, SNEEZING, VOMITING, ABDOMINAL TENDERNESS, NAUSEA, BLOOD
IN VOMITUS & B
LOOD IN FECES, BLEEDING.

===== First Aid Measures =====

First Aid:EYES: FLUSH W/LARGE AMOUNTS OF WATER FOR 15 MINS. SKIN: FLUSH
W/LARGE AMOUNTS OF WATER. INHALATION: REMOVE TO FRESH AIR.
INGESTION: DRINK 2 GLASSES OF WATER. OBTAIN MEDICAL ATTENTION IN
ALL CASES.

===== Fire Fighting Measures =====

Flash Point:207F

===== Accidental Release Measures =====

Spill Release Procedures:V

ENTILATE AREA. COVER W/ABSORBENT MATERIAL.
PLACE IN METAL CONTAINER.

===== Handling and Storage =====

Handling and Storage Precautions:KEEP CONTAINER TIGHTLY CLOSED. STORE
IN A COOL PLACE. USE W/ADEQUATE VENTILATION. WEAR APPROPRIATE
GLOVES WHEN HANDLING THIS MATERIAL.

Other Precautions:AVOID EYE/SKIN CONTACT. AVOID PROLONGED BREATHING OF
VAPORS. DON'T INGEST. ACRYLATE MAY PENETRATE GLOVES. IF PRIMER
CONTACTS GLOVE, REMOVE & DISCARD. WASH
HANDS W/SOAP & WATER & THEN
RE-GLOVE.

===== Exposure Controls/Personal Protection =====

Protective Gloves:RECOMMENDED
Supplemental Safety and Health

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:>95F
Vapor Pres: