

EASTMAN KODAK COMPANY -- 181 5430 EKTACOLOR RA BLEACH FIX & REPLENISHER, WORK SOLN -- 6750-01-319-4154

===== Product Identification =====

Product ID:181 5430 EKTACOLOR RA BLEACH FIX & REPLENISHER, WORK SOLN

MSDS Date:10/17/1997

FSC:6750

NIIN:01-319-4154

MSDS Number: CGLVY

=== Responsible Party ===

Company Name:EASTMAN KODAK COMPANY

Address:343 STATE STREET

City:ROCHESTER

State:NY

ZIP:14650

Country

:US

Info Phone Num:716-477-3194 MSDS :800- 242-2424

Emergency Phone Num:716-722-5151

CAGE:19139

=== Contractor Identification ===

Company Name:EASTMAN KODAK CO GOVERNMENT MARKETS CONTRACTS

Address:343 STATE ST

Box:City:ROCHESTER

State:NY

ZIP:14650-1115

Country:US

Phone:716-722-5151/(800) 242-2424

CAGE:19139

Company Name:EASTMAN KODAK CO US CUSTOMER SERVICE/GOVERNMENT SALES

Address:800 LEE RD

Box:City:ROCHESTER

State:NY

ZIP:14650-3129

Country:US

Phone:800-828-6203

CAGE:5K871

===== Compo

sition/Information on Ingredients =====

Ingred Name:WATER  
CAS:7732-18-5  
RTECS #:ZC0110000  
Fraction by Wt: 85-90%  
Other REC Limits:NONE RECOMMENDED

Ingred Name:AMMONIUM THIOSULFATE  
CAS:7783-18-8  
RTECS #:XN6465000  
Fraction by Wt: 5-10%  
Other REC Limits:NONE RECOMMENDED

Ingred Name:FERRIC AMMONIUM ETHYLENEDIAMINETETRAACETIC ACID  
CAS:21265-50-9  
Fraction by Wt: 5-10%  
Other REC Limits:NONE RECOMMENDED

Ingred Name:SODIUM BISULFITE (SASA III) (CERCLA)  
CAS:7631-90-5  
RTECS #:VZ2000000  
Fraction by Wt: 1-5%  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:5 MG/M3  
ACGIH TLV:5 MG/M3; 9596  
EPA Rpt Qty:5000 LBS  
DOT Rpt Qty:5000 LBS

Ingred Name:ACETIC ACID (CERCLA)  
CAS:64-19-7  
RTECS #:AF1225000  
Fraction by Wt: 100C  
Melt/Freeze Pt:M.P/F.P Text:NP  
Decomp Temp:Decomp Text:NP  
Vapor Pres:18  
Vapor Density:0.6  
Spec Gravity:1.102  
pH:SUPPLE  
Viscosity:NP  
Evaporation Rate & Reference:NP  
Solubility in Water:COMPLETE  
Appearance and Odor:LIQUID, DARK REDDISH-BROWN COLOR, SLIGHT AMMONIA  
ODOR  
Percent

Volatiles by Volume:70-75

Corrosion Rate:NP

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS, STRONG ACIDS, BASES, SODIUM HYPOCHLORITE  
(BLEACH).

Stability Condition to Avoid:NONE SPECIFIED BY MANUFACTURER.

Hazardous Decomposition Products:HAZ COMBUST PROD:CO,CO2,OXIDES OF  
NITROGEN,OXIDES OF SULFUR.HAZ DECOMPO PROD:AMMONIA,CHLORAMINE.

===== Disposal Considerations =====

Waste Disposal Methods:DISCHARGE/TREATMENT/DISPOSAL MAY BE SUBJECT TO  
NATIONAL/STATE/LOCAL LAWS.FLUSH TO SEWER W/LG AMTS OF WATER.CHEM  
SUBJ TO REPORTING REQMTS OF SEC 313 TITLE III SARA/40CFR372:NONE.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims

all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.