

ASHLAND CHEMICAL COMPANY -- CONOSOL C-200 SOLVENT -- 6850-01-377-1811

=====
Product Identification
=====

Product ID:CONOSOL C-200 SOLVENT

MSDS Date:02/10/1995

FSC:6850

NIIN:01-377-1811

MSDS Number: CGMZH

=== Responsible Party ===

Company Name:ASHLAND CHEMICAL COMPANY

Box:2219

City:COLUMBUS

State:OH

ZIP:43216-2219

Country:US

Info Phone Num:614-790-3333/800-325-3751

Emergency Phone Num:800-274-5236

OR 800-ASHLAND

CAGE:34897

=== Contractor Identification ===

Company Name:ASHLAND CHEMICAL CO

Box:2219

City:COLUMBUS

State:OH

ZIP:43216-2219

Country:US

Phone:614-790-3333/800-274-5263

CAGE:34897

Company Name:EMULTEC INDUSTRIAL PRODUCTS INC

Address:1150 HAYDEN DR SUITE 100

Box:City:CHARROLLTON

State:TX

ZIP:75006

Country:US

Phone:972-417-1288

CAGE:0WA27

=====
Composition/Information on Ingredients
=====

Ingred Name:ALIPHATIC HYDROCARBON

Other REC Limits:NONE RECOMMENDED

OSHA PE

L:5 MG/M3 AS OIL MIST
ACGIH TLV:5 MG/M3 AS OIL MIST

=====
===== Hazards Identification =====

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:INHALATION MAY CAUSE RESPIRATORY IRRITATION, CNS DEPRESSION. SKIN & EYE CONTACT MAY CAUSE MILD IRRITATION. INGESTING VERY LARGE AMOUNTS MAY CAUSE GI TRACT IRRITATION. ASPIR

ATION MAY CAUSE LUNG INFLAMM ATION AND/OR DAMAGE.

Explanation of Carcinogenicity:NO INGREDIENT OF A CONCENTRATION OF 0.1% OR GREATER IS LISTED AS A CARCINOGEN BY IARC, NTP OR OSHA.

Effects of Overexposure:INHALED-IRRITATION, DIZZINESS, DROWSINESS, WEAKNESS, FATIGUE, NAUSEA, HEADACHE. SKIN-IRRITATION, REDNESS, BURNING SENSATION, DRYING & CRACKING. EYES-IRRITATION-IRRITATION, STINGING, TEARING, REDNESS.

Medical Cond Aggravated by Exposure:PRE-EXISTING SKIN DISORDERS.

=====

=====
===== First Aid Measures =====

First Aid:EYES-FLUSH WITH WATER FOR 15 MINUTES, HOLD LIDS OPEN. GET MEDICAL ATTENTION. SKIN-REMOVE CONTAMINATED CLOTHES. WASH WITH SOAP & WATER. SEEK MEDICAL ATTENTION IF SYMPTOMS PERSIST. INHALED-REMOVE TO FRE SH AIR. RESTORE BREATHING AS NEEDED. INGESTED-DO NOT INDUCE VOMITING! SEEK MEDICAL ATTENTION.

=====
===== Fire Fighting Measures =====

Flash Point Method:PMCC

Flash Point:>200F,>93C

Lowe

r Limits:1.0

Extinguishing Media:DRY CHEMICAL, CARBON DIOXIDE OR WATER FOG.

Fire Fighting Procedures:WEAR FIRE FIGHTING PROTECTIVE EQUIPMENT AND FULL FACE-PIECE SELF-CONTAINED BREATHING APPARATUS. COOL FIRE EXPOSED CONTAINERS WITH WATER SPRAY.

Unusual Fire/Explosion Hazard:NO SPECIAL FIRE HAZARDS ARE KNOWN TO BE ASSOCIATED WITH THIS PRODUCT.

=====
===== Accidental Release Measures =====

Spill Release Procedures:ELIMINATE ALL SOURCES OF IGNITION. ABSORB ONTO

SAND OR OTHER ABSORBENT MATERIAL. KEEP OUT OF DRAINS, SEWERS,
STREAMS, OTHER BODIES OF WATER.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

=====
===== Handling and Storage =====

Handling and Storage Precautions:STORE IN A COOL, DRY PLACE AWAY FROM
STRONG OXIDIZING AGENTS AND SOURCES OF IGNITION.

Other Precautions:CONTAINERS OF THIS PRODUCT MAY BE AHZARDOUS WHEN
EMPTIEDD CONTAINERS RETAIN PRODUCT RESIDUES. ALL HAZARD PRECAUTIONS
GIVEN IN THIS

DATA SHEET MUST BE OBSERVED.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:IF ENGINEERING CONTROLS FAIL OR NON-ROUTINE USE
OR EMERGENCY OCCURS, USE NIOSH/MSHA-APPROVED RESPIRATOR WITH
ORGANIC VAPOR CARTRIDGE OR SCBA OR SUPPLIED-AIR RESPIRATOR. USE IAW
29 CFR 1910.134.

Ventilation:USE MECHANICAL (GENERAL) OR LOCAL EXHAUST TO MAINTAIN
EXPOSURE BELOW TLV(S).

Protective Gloves:RESISTANT-NITRILE.

Eye Protection:SAFETY GLASSES/CHEMICAL SP
LASH GOGGLES.

Other Protective Equipment:IMPERVIOUS CLOTHING & BOOTS. DLA-HMIS: EYE
WASH STATION & SAFETY SHOWER.

Work Hygienic Practices:WASH THOROUGHLY AFTER HANDLING AND BEFORE
EATING, DRINKING OR SMOKING. LAUNDER CONTAMINATED CLOTHING BEFORE
REUSE.

Supplemental Safety and Health

=====
===== Physical/Chemical Properties =====

HCC:N1

Boiling Pt:B.P. Text:430F,221C

Vapor Pres:0.40

Vapor Density:6.20

Spec Gravity:0.818-0.830

Appearance and Odor:CLEAR, COLORLES
S LIQUID.

=====
===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
STRONG OXIDIZING AGENTS.

Stability Condition to Avoid:AVOID HEAT, OPEN FLAME & PROLONGED STORAGE
AT ELEVATED TEMPERATURES.

Hazardous Decomposition Products:CARBON MONOXIDE AND CARBON DIOXIDE,
ETC.

Conditions to Avoid Polymerization:CANNOT OCCUR.

=====
===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH

LOCAL, STATE AND
FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of th
is information to their
particular situation.