View NSN Online: https://aerobasegroup.de/nsn/6850-01-441-3223

OLD WORLD INDUSTRIES INC -- FLEET CHARGE HEAVY DUTY COLLANT/ANTIFREEZE 6850-01-441-3223

Product ID:FLEET CHARGE HEAVY DUTY COLLANT/ANTIFREEZE MSDS Date:02/01/1996 FSC:6850 NIIN:01-441-3223 MSDS Number: CGNBH === Responsible Party === Company Name: OLD WORLD INDUSTRIES INC Address:4065 COMMERCIAL AVE City:NORTHBROOK State:IL ZIP:60062-1851 Country:US Info Phone Num:847-559-2000 Emergency Phone Num:847-559-2000 CAGE:0U3B1 === Contractor Identification === Company Name: DAVIS PETROLEUM SERVICES, INC Address:3517 ASHER AVE Box:24864 City:LITTLE ROCK State:AR ZIP:72204 Country:US Phone:501-663-0003 CAGE:0VTU2 Company Name: OLD WORLD INDUSTRIES INC Address:4065 COMMERCIAL AVE Box:City:NORTHBROOK State:IL ZIP:60062-1851 Country:US Phone:847-559-2000/2116/FAX: 847-559-2173 CAGE:0U3B1

Ingred

Name:ETHYLENE GLYCOL (SARA 313) (CERCLA) CAS:107-21-1 RTECS #:KW2975000 Fraction by Wt: 90-95% Other REC Limits:NONE RECOMMENDED ACGIH TLV:C STEL39PPM,A4,VAP96 EPA Rpt Qty:1 LB DOT Rpt Qty:1 LB

Ingred Name:DIETHYLENE GLYCOL CAS:111-46-6 RTECS #:ID5950000 Fraction by Wt: 0-5% Other REC Limits:NONE RECOMMENDED

LD50 LC50 Mixture:LD50 (HUMANS): 100 ML 3 OZ (ESTIMATED) Routes of Entry: Inhalation:NO Skin:YES Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:AT HIGH TEMPERATURES INHALATION OF VAPORS MAY CAUSE ADVERSE EFFECTS. PROLONGED/REPEATED SKIN CONTACT MAY RESULT IN ABSORPTION OF HARMFUL AMOUNTS. EYE CONTACT MAY CAUSE SLIGHT TRANSIENT IRRITATION. VAP ORS OF MISTS MAY CAUSE EYE IRRITATION. INGESTION OF EXCESSIVE AMOUNTS MAY CAUSE CNS EFFECTS, CARIOPULMONARY EFFECTS.

Explanation of Carcinogenicity: THIS COMPOUND CONTAINS NO INGREDIENTS AT CONCENT

RATIONS OF 0.1% OR GREATER THAT ARE CARCINOGENS OR SUSPECT CARCINOGENS.

Effects of Overexposure:TEMPORARY EYE IRRITATION, CENTRAL NERVOUS SYSTEM EFFECTS, CARDIOPULMONARY EFFECTS, METABOLIC ACIDOSIS, KIDNEY FAILURE, DEATH, NAUSEA, VOMITING, ANESTHETIC EFFECTS, NARCOTIC EFFECTS.

Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

First Aid:EYES: FLUSH WITH WATER FOR 15 MINUTES WHILE HOLDING EYELI

DS

OPEN. GET MEDICAL ATTENTION. SKIN: REMOVE CONTAMINATED CLOTHING. WASH WITH SOAP & WATER. IF IRRITATION PERSIST, GET MEDICAL ATTENTION. INHAL ATION: REMOVE TO FRESH AIR. RESTORE BREATHING. GET MEDICAL ATTENTION. INGESTION: GIVE 2 GLASSES OF WATER & IMMEDIATELY CALL PHYSICIAN. INDUCE VOMITING OF CONSIOUS PATIENT. SMALL AMOUNTS CAN BE RINSED.

Flash Point Method:SCC
Flash Point:246F,119C
Lower Limits:3.
20 %
Upper Limits:NOT GIVEN
Extinguishing Media:WATER FOR OR FINE SPRAY, ALCOHOL RESISTANT FOAM, CARBON DIOXIDE, DRY CHEMICAL. DO NOT USE DIRECT WATER SPRAY.
Fire Fighting Procedures:FIRE FIGHTERS SHOULD WEAR SELF CONTAINED BREATHING APPARATUS AND FULL PROTECTIVE GEAR. COOL TANKS AND CONTAINERS EXPOSED TO FIRE WITH WATER.
Unusual Fire/Explosion Hazard:SOLUTION OF ETHYLENE GLYCOL AND WATER CAN FORM FLAMMABLE VAPORS WITH AIR IF HEATED SUFFICIENTLY. KEEP PEOPLE AWAY. ISOLATE FIR

E AREA AND DENY UNNECESSARY ENTRY.

Spill Release Procedures: TAKE ADEQUATE PRECAUTIONS TO KEEP PEOPLE, ESPECIALLY CHILDREN AWAY FROM SPILL SITE. PVC COATED RUBBER GLOVES AND MONOGOGGLES OR FACESHIELD CAN BE USED DURING CLEANUP OF SPILL SITE. SOAK UP WITH ABSORB ENT MATERIAL AND COLLECT FOR DISPOSAL. Neutralizing Agent: NONE SPECIFIED BY MANUFACTURER.

=

Handling and Storage Precautions: PRODUCT ON SURFACES CAN CAUSE SLIPPERY CONDITIONS. PRACTICE REASONABLE CARE AND CLEANLINESS. AVOID BREATHING SPRAY MISTS IF GENERATED.

Other Precautions: KEEP OUT OF REACH OF CHILDREN. PRODUCT MAY BECOME A SOLID AT TEMPERATURES BELOW 8F. DO NOT STORE NEAT FOOD, FOODSTUFFS, DRUGS OR POTABLE WATER SUPPLIES.

======= Exposure Controls/Personal Protection ===============

Respiratory Protection: IF EXPOSURE MAY OR DOES EXCEED OCCUPATION EXP

OSURE LIMITS USE A NIOSH-APPROVED RESPIRATOR TO PREVENT OVEREXPOSURE. IN ACCORD WITH 29 CFR 1910.134 USE EITHER AN ATMOSPHERE-SUPPLYING RESPIRATOR OR AN AI R-PURIFYING RESPIRATOR. Ventilation: EXHAUST VENTILATION SUFFICIENT TO KEEP AIRBORNE CONCENTRATIONS BELOW RESPECTIVE TLV'S. Protective Gloves: POLYETHYLENE, NEOPRENE, NITRILE, PVA Eye Protection: CHEMICAL GOGGLES, SAFETY GLASSES W/SIDES Other Protective Equipment: CHEMICAL RESISTANT CLOTHING AS NECESSARY TO PREVENT SKIN CONTACT. A N EMERGENCY EYEWASH AND SHOWER SHOULD BE AVAILABLE. Work Hygienic Practices: WASH HANDS THOROUGHLY WITH SOAP AND WATER BEFORE EATING, DRINKING, SMOKING OR USING TOILET FACILITIES. Supplemental Safety and Health CONTACT LENSES SHOULD NOT BE WORN WHEN WORKING WITH THIS CHEMICAL. 

HCC:V5 Boiling Pt:B.P. Text:339F,171C Melt/Freeze Pt:M.P/F.P Text:-8F,-22C Vapor Pres:< 0.1 Vapor Density:2.1 Spec Gravity:1.12 Evaporation Rate & amp; Reference:NIL (N-BUTYL ACETATE=1) Solubility in Water:COMPLETE Appearance and Odor:MILD ODOR Percent Volatiles by Volume:O %

Stability Indicator/Materials to Avoid:YES STRONG OXIDIZERS SUCH AS PERMANGANATES, CHROMATES AND PEROXIDES. Stability Condition to Avoid:ISOLATE FROM OXIDIZERS, HEAT AND OPEN FLAMES. Hazardous Decomposition Products:CARBON MONOXIDE, CARBON DIOXIDE, TRACE

AMOUNTS OF ALDEHYDES AND ORGANIC ACIDS.

Waste Disposal Methods:PREVENT WASTE FROM CONTAMINATING SURROUNDING ENVIRONMENT. DISCARD ANY PRODUCT, RESIDUE, DISPOSAL CONTAINER OR LINER IN ACCORDANCE WITH ALL FEDERAL, STATE AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, exp ressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.