

LASTING PAINTS, INC. -- ENAMEL FLOOR & DECK

=====
MSDS Safety Information
=====

FSC: 8010
NIIN: 00-527-0217
MSDS Date: 05/25/1997
MSDS Num: CGNFS
Product ID: ENAMEL FLOOR & DECK
MFN: 01
Responsible Party
Cage: GO423
Name: LASTING PAINTS, INC.
Address: 200 S. FRANKLINTOWN ROAD
City: BALTIMORE MD
21223
Info Phone Number: 410-947-6300
Emergency Phone Number: 410-947-6306
Review Ind: Y
Published: Y

=====
Contractor Summary
=====

Cage: 35178
Name: LASTING PAINTS INC.
Address: 200 S FRANKLINTOWN RD
City: BALTIMORE MD 21223-2038
Phone: UNKNOWN
Cage: GO423
Name: LASTING PAINTS, INC.
Address: 200 S FRANKLINTOWN ROAD
City: BALTIMORE MD 21223
Phone: 410-947-6300/800-368-2205

=====
Item Description Information
=====

Item Manager: GSA
Item Name: ENAMEL
Specification Number: TTE-487E
Unit of Issue: CN
Quantitative Expression: 00000000005GL
UI Container Qty: 1

=====
Ingredients
=====

Cas: 8052-41-3
RTECS #: WJ8925000
Name: ALIPHATIC DISTILLATE (STODDARD) (VAPOR PRESSURE 10.0)
% Wt: 24.5
Other

REC Limits: NONE RECOMMENDED

OSHA PEL: NOT ESTABLISHED

ACGIH TLV: 100 PPM

Cas: 64742-95-6

Name: AROMATIC PETROLEUM DISTILLATE (VAPOR PRESSURE 3.0)

% Wt: 1.3

Other REC Limits: NONE RECOMMENDED

OSHA PEL: NOT ESTABLISHED

ACGIH TLV: 50 PPM

Cas: 107-98-2

RTECS #: UB7700000

Name: PROPYLENE GLYCOL MONOMETHYL ETHER (VAPOR PRESSURE 10.9)

% Wt: 1.3

Other REC Limits: NONE RECOMMENDED

OSHA PEL: NOT ESTABLISHED

ACGIH TLV: 100 PPM

Name: EPOXY RESIN/ALKYL GLYCIDYL ETHER MIXTURE

% Wt: 8.9

Other REC Limits: NONE RECOMMENDED

OSHA PEL: NOT ESTABLISHED

ACGIH TLV: NOT ESTABLISHED

=====
Health Hazards Data

=====
Route Of Entry Inds - Inhalation: YES

Skin: YES

Ingestion: YES

Carcinogenicity Inds - NTP: NO

IARC: NO

OSHA: NO

Effects of Exposure: EYE: IRRIT. SKIN: IRRIT. INHAL: HARMFUL. BRAIN/NERVOUS
SYSTEM (DIZZY, HE

ADACHE, NAUSEA). NOSE/THROAT IRRIT. INGEST: GI IRRIT.

CHRONIC: PERMANENT BRAIN & NERVOUS SYSTEM DAMAGE. HARMFUL, FATAL.

Medical Cond Aggravated By Exposure: PRE-EXISTING RESPIRATORY CONDITIONS.

First Aid: EYE: FLUSH W/WATER FOR 15 MINUTES. SKIN: WASH W/SOAP & WATER.

REMOVE CONTAM CLOTHES. INHAL: REMOVE TO FRESH AIR. RESTORE BREATHING. INGEST:
DRINK 2 GLASSES OF WATER. DONT INDUCE VOMIT. CALL POISON CON TROL. IN ALL
CASES, GET IMMEDIATE MEDICAL ATTENTION.

=====
Handling and Disposal
=====

Spill Release Procedures: REMOVE IGNIT SOURCES. PROVIDE VENTILATION. USE SCOOP ON LARGE SPILLS & ABSORBENT MATERIAL ON SMALL SPILLS. USE RESPIRATORY PROTECTION. FLUSH AREA W/WATER. HOLD CLEAN-UP MATERIALS FOR PROPER DISPOSAL.
Waste Disposal Methods: IN ACCORDANCE W/FEDERAL, STATE & LOCAL REGULATIONS. BEFORE CLEAN-UP REFER TO HAZARD CAUTION INFORMATION IN OTHER SECTIONS.

Hand

ling And Storage Precautions: STORE IN A WELL-VENT AREA & AWAY FROM HEAT, IGNIT SOURCES. DONT STORE >100F. KEEP CONTAINER CLOSED & UPRIGHT. DONT PUNCTURE, DRAG, SLIDE CONTAINERS.

Other Precautions: DRUMS SHOULD BE GROUNDED WHEN POURING. RESTRICT FREE FALL OF LIQUID TO A FEW INCHES TO AVOID GENERATION OF STATIC CHARGE.

=====
Fire and Explosion Hazard Information
=====

Flash Point

Text: 108F,42C

Lower Limits: 1.1

Extinguishing Media: FOAM, CO2, DRY CHEMICAL, WATER FOG. USE ANY CLASS B APPROVED FIRE EXTINGUISHER.

Fire Fighting Procedures: KEEP CONTAINER TIGHTLY CLOSED. REMOVE FROM IGNIT SOURCES. IN EXTREME HEAT CLOSED CONTAINERS EXPLODE. APPLICATION TO HOT SURFACES REQUIRES SPECIAL PRECAUTIONS.

Unusual Fire/Explosion Hazard: WATER SPRAY MAY BE INEFFECTIVE. WATER FOG NOZZLES PREFERRED. USE WATER TO COOL CONTAINERS. USE FULL PROTECTIVE EQUIPMENT W/SCBA.

=====
Control Measures
=====

Respiratory Protection: UNRESTRICTED VENT: MECHANICAL FILTER TO REMOVE SOLID PARTICLES. RESTRICTED VENT: USE CHEMICAL/MECHANICAL FILTER TO REMOVE BOTH VAPOR & SOLIDS. NO VENT: USE AIR LINE TYPE RESPIRATOR.

Ventilation: VENT SYSTEM DESIGNED & MAINTAINED TO PROVIDE VOLUME & PATTERN TO PREVENT CONCENTRATION IN EXCESS OF THE TLV.

Protective Gloves: NEOPRENE, IMPERVIOUS

Eye Protection: GOGGLES, SIDE SHIELD SPECTACLES

Other Protective Equipment: EYE WASH STATION & SAFETY SHOWERS AVAILABLE.

Work Hygienic Practices: WASH HANDS BEFORE EATING OR USING WASHROOM. SMOKE IN DESIGNATED AREAS ONLY.

=====
Physical/Chemical Properties
=====

B.P. Text: 311 TO 390F

Vapor Density: >AIR

Evaporation Rate & Reference: SLOWER THAN ETHER

Percent Volatiles by Volume: 44

.56%

=====
Reactivity Data
=====

Stability Indicator: YES

Stability Condition To Avoid: HEAT & OPEN FLAME.

Materials To Avoid: OXIDIZING AGENTS.

Hazardous Decomposition Products: CARBON MONOXIDE & OTHER ORGANIC MATERIALS MAY
BE FORMED DURING COMBUSTION.

Hazardous Polymerization Indicator: NO
=====

Toxicological Information
=====

=====
Ecological Information
=====

=====
MSDS Transport Information
=====

=====
Regulatory Information
=====

=====
Other Information
=====

=====
Transportation Information
=====

Responsible Party Cage: GO423

Trans ID NO: 74917

Product ID: ENAMEL FLOOR & DECK

MSDS Prepared Date: 05/25/1997

Review Date: 03/05/1998

MFN: 1

Multiple KIT Number: 0

Review IND: Y

Unit Of Issue: CN

Container QTY: 1
=====

Detail DOT

Information

=====
DOT PSN Code: GJJ
Symbols: G
DOT Proper Shipping Name: FLAMMABLE LIQUIDS, N.O.S.
Hazard Class: 3
UN ID Num: UN1993
DOT Packaging Group: II
Label: FLAMMABLE LIQUID
Special Provision: T8,T31
Non Bulk Pack: 202
Bulk Pack: 242
Max Qty Pass: 5L
Max Qty Cargo: 60 L
Vessel Stow Req: B
=====

Detail IMO Information

=====
IMO PSN Code: HI
N
IMO Proper Shipping Name: FLAMMABLE LIQUID, N.O.S. o
IMDG Page Number: 3230
UN Number: 1993
UN Hazard Class: 3.2
IMO Packaging Group: I/II
Subsidiary Risk Label: -
EMS Number: 3-07
MED First Aid Guide NUM: T
=====

Detail IATA Information

=====
IATA PSN BV
IATA UN ID Num: 1993
IATA Proper Shipping Name: FLAMMABLE LIQUID, N.O.S. *
IATA UN Class: 3
IATA Label: FLAMMABLE LIQUID
UN Packing Group: II

Packing Note Passenger: 305
Max Quant Pass: 5L
Max Quant Cargo: 60L
Packaging Note Cargo: 307
=====

Detail AFI Information

=====
AFI PSN BV
AFI Symbols: *
AFI Proper Shipping Name: FLAMMABLE LIQUIDS, N.O.S.
AFI Hazard Class: 3
AFI UN ID NUM: UN1993
AFI Packing Group: II
Special Provisions: P5
Back Pack Reference: A7.3
=====

HAZCOM Label

=====

=====
Product ID: ENAMEL FLOOR & DECK

Cage: GO423

Assigned IND: Y

Company Name: LASTING PAINTS, INC.

Street: 200 S FRANKLINTOWN ROAD

City: BALTIMORE MD

Zipcode: 21223

Health Emergency Phone: 410-947-6306

Label Required IND: Y

Date Of Label Review: 10/12/1999

Status Code: A

Origination Code: G

Hazard And Precautions: EYE: IRRIT. SKIN: IRRIT. INHAL: HARMFUL. BRAIN/NERVOUS
SYSTEM (DIZZY, HEADACHE, NAUSEA). NOSE/THROAT IRRIT. INGEST: GI IRRIT.
CHRONI

C: PERMANENT BRAIN & NERVOUS SYSTEM DAMAGE. HARMFUL, FATAL.

=====
Disclaimer (provided with this information by the compiling agencies): This
information is formulated for use by elements of the Department of Defense.
The United States of America in no manner whatsoever expressly or implied
warrants, states, or intends said information to have any application, use or
viability by or to any person or persons outside the Department of D
efense

nor any person or persons contracting with any instrumentality of the United
States of America and disclaims all liability for such use. Any person
utilizing this instruction who is not a military or civilian employee of the
United States of America should seek competent professional advice to verify
and assume responsibility for the suitability of this information to their
particular situation regardless of similarity to a corresponding Department
of Defense or other govern
ment situation.