

THREE BOND OF AMERICA INC -- ADHESIVE CYANOACRYLATE TYPE 2, CL 2 TB1743 --
8040-01-024-6988

===== Product Identification =====

Product ID:ADHESIVE CYANOACRYLATE TYPE 2, CL 2 TB1743

MSDS Date:12/10/1996

FSC:8040

NIIN:01-024-6988

MSDS Number: CGNJF

=== Responsible Party ===

Company Name:THREE BOND OF AMERICA INC

Address:20815 HIGGINS CT

City:TORRANCE

State:CA

ZIP:90501

Country:US

Info Phone Num:310

-320-3342

Emergency Phone Num:310-320-3342

Preparer's Name:K. KISHITA

CAGE:60859

=== Contractor Identification ===

Company Name:THREE BOND OF AMERICA,INC.

Address:20815 HIGGINS COURT

Box:City:TORRANCE

State:CA

ZIP:90501

Country:US

Phone:310-320-3342

CAGE:60859

===== Composition/Information on Ingredients =====

Ingred Name:ETHYL CYANOACRYLATE

CAS:7085-85-0

Fraction by Wt: 95-98%

Other REC Limits:4 PPM

Ingred Name:POLYMETHYLMETHACRYLATE

CAS:9011-14-7

RTECS #:TR0400000

Fraction

by Wt: 2-5%

Other REC Limits:NONE RECOMMENDED

=====
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:EYE: IRRIT. SKIN: BONDS INSTANTLY.
INHAL: RUNNY NOSE.

=====
===== First Aid Measures =====

First Aid:EYE: FLUSH W/WATER FOR 15 MINUTES, LIFTING LIDS. GET MED AID.
SKIN: DONT PULL, USE GLUE REMOVER.
IN ALL CASES, GET MED AID.

=====
===== Fire Fighting Measures =====

Flash Point:181.4F,83C
Extinguishing Media:FOAM, CARBON DIOXIDE, DRY CHEMICAL.
Fire Fighting Procedures:WATER W/INTENSE POLYMERIZATION TO LIQUID. USE
FULL SCBA.
Unusual Fire/Explosion Hazard:NONE

=====
===== Accidental Release Measures =====

Spill Release Procedures:EVACUATE ALL IGNITS. EVACUATE AREA. RECOVER
MATERIAL AS PRACTICAL. SOAK UP WITH ABSORBENT MATERIAL. VE
NTILATE
AREA. USE SCBA, RUBBER BOOTS, POLYURETHANE GLOVES WHEN CLEANING.

=====
===== Handling and Storage =====

Handling and Storage Precautions:KEEP CONTAINER CLOSED WHILE NOT IN
USE. KEEP AWAY FROM HEAT & FLAME. STORE IN COOL PLACE.
Other Precautions:NONE

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE APPROPRIATE OSHA/MSHA APPROVED RESPIRATOR.
Ventilation:LOCAL EXHAUST/MECHANICAL (GENERAL)
Protective Glove

s:POLYURETHANE

Eye Protection:SAFETY GOGGLES

Other Protective Equipment:IMPERVIOUS CLOTHING

Work Hygienic Practices:MEDICAL SURVEILANCE & EMPLOYEE TRAINING
PROPOSED TO BE REQUIRED.

Supplemental Safety and Health

NK

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:150F,66C

Melt/Freeze Pt:M.P/F.P Text: