

DOW CORNING CORP -- 732 MULTI PURPOSE SEALANT BLACK -- 8030-00-851-0211

=====
Product Identification
=====

Product ID:732 MULTI PURPOSE SEALANT BLACK

MSDS Date:08/10/1990

FSC:8030

NIIN:00-851-0211

MSDS Number: CGSXJ

=== Responsible Party ===

Company Name:DOW CORNING CORP

Address:SOUTH SAGINAW RD

City:MIDLAND

State:MI

ZIP:48686

Country:US

Info Phone Num:517-496-6000

Emergency Phone Num:517-496-590

0

Preparer's Name:JACK L SHENEGER

CAGE:5D028

=== Contractor Identification ===

Company Name:DOW CORNING CORP

Address:3901 S SAGINAW RD

Box:997

City:MIDLAND

State:MI

ZIP:48686-0997

Country:US

Phone:517-496-6000/517-496-6315

CAGE:5D028

Company Name:DOW CORNING CORP

Address:2200 W SALZBURG RD

Box:City:AUBURN

State:MI

ZIP:48611

Country:US

Phone:517-496-4388

CAGE:71984

=====
Composition/Information on Ingredients
=====

Ingred Name:SILANE, METHYLTRACETOXY-; (METHYLTRACETOXYSIL

ANE)
CAS:4253-34-3
RTECS #:VV4500000
Fraction by Wt: 2%
OSHA PEL:N/K
ACGIH TLV:N/K

Ingred Name:ETHYLTRIACETOXYSILANE
CAS:17689-77-9
Fraction by Wt: 2%
OSHA PEL:N/K
ACGIH TLV:N/K

Ingred Name:SILICA GEL; (SILICA, AMORPHOUS)
CAS:112945-52-5
RTECS #:VV7310000
Fraction by Wt: 11%
OSHA PEL:6 MG/M3)
ACGIH TLV:10 MG/M3

=====
===== Hazards Identification =====

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.
Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Re
ports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:ACUTE: EYE: DIRECT CONTACT IRRITATES
SLIGHTLY TO MODERATELY WITH REDNESS AND SWELLING. SKIN: SINGLE
SHORT EXPOS (250F,>121C
Extinguishing Media:USE WATER FOG, CARBON DIOXIDE, DRY CHEMICAL, FOAM.
Fire Fighting Procedures:WEAR NIOSH APPROVED SCBA AND FULL PROTECTIVE
EQUIPMENT .
Unusual Fire/Explosion Hazard:NOT KNOWN TO DOW CORNING.

=====
===== Accidental Release Measures =====

S
pill Release Procedures:REMOVE PRODUCT AND CONTAIN FOR SALVAGE OR
DISPOSAL.
Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

=====
===== Handling and Storage =====

Handling and Storage Precautions:AVOID BREATHING VAPORS AND EYE AND
SKIN CONTACT. USE ONLY WITH ADEQUATE VENTILATION. STORE BELOW
90F/32C. USE REASONABLE CARE AND CAUTION.
Other Precautions:DO NOT TAKE INTERNALLY. PRODUCT FORMS ACETIC ACID
(HOAC) WHEN EXPOSED TO WATER OR HUMID AIR. PROV

IDE VENTILATION

DURING USE TO CONTROL HOAC EXPOSURE WITHIN 10 PPM (CURRENT TLV) OR USE RESPIRATORY PROT ECTION.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE NIOSH APPROVED RESPIRATORY PROTECTION UNLESS LOCAL EXHAUST VENTILATION IS ADEQUATE OR AIR SAMPLING DATA SHOW EXPOSURES AE WITHIN TLV AND PEL GUIDELINES. SUITABLE RESPIRATOR: NIOSH APPROVED ACID GA S/ORGANIC VAPOR TYPE.

Ventilation:LOCAL EXHAUST MAY BE NEEDED. MECHANICAL (GENERAL)

VENTILATION RECOMMENDED.

Protective Gloves:RUBBER OR PLASTIC GLOVES RECOMMENDED.

Eye Protection:ANSI APPRVD CHEM WORKERS GOGGLES .

Other Protective Equipment:EMERGENCY EYEWASH AND DELUGE SHOWER MEETING ANSI DESIGN CRITERIA .

Work Hygienic Practices:WASHING AT MEALTIME & END OF SHIFT IS ADEQ.

REMOVE CONTAM CLTHG & SHOES AS SOON AS PRACTICAL & CLEAN THORO (SUP DAT)

Supplemental Safety and Health

HYGIENE PRACTICE: BEFORE REUSE. GOOD PRACTICE REQUIRES THAT GROSS AMOUNTS

OF ANY CHEMICAL BE REMOVED FROM SKIN AS SOON AS PRACTICAL, ESPECIALLY BEFORE EATING OR SMOKING.

===== Physical/Chemical Properties =====

Vapor Pres:1

Spec Gravity:1.04

Solubility in Water: