

SHERWIN-WILLIAMS -- V93V230, MIL-P-23377F TYPE 1 CLASS C (SUPDAT) -- 8010-01-312-1169

=====
Product Identification
=====

Product ID:V93V230, MIL-P-23377F TYPE 1 CLASS C (SUPDAT)

MSDS Date:12/17/1997

FSC:8010

NIIN:01-312-1169

Kit Part:Y

MSDS Number: CGVNL

=== Responsible Party ===

Company Name:SHERWIN-WILLIAMS

Address:630 E 13TH ST

City:ANDOVER

State:KS

ZIP:67002

Country:US

Info Phone Num:216-566-

2902

Emergency Phone Num:216-566-2917

CAGE:DO642

=== Contractor Identification ===

Company Name:SHERWIN-WILLIAMS

Box:UNKNOW

CAGE:SWAND

Company Name:SHERWIN-WILLIAMS CO THE SPECIALTY DIV.

Address:6830 COCHRAN RD.

Box:6709

City:SOLOM

State:OH

ZIP:44139-3908

Phone:216-292-7400

CAGE:DO642

=====
Composition/Information on Ingredients
=====

Ingred Name:ETHYL BENZENE

CAS:100-41-4

RTECS #:DA0700000

= Wt:1.

OSHA PEL:100 PPM

ACGIH TLV:100 PPM

ACGIH STEL:125 PPM

EPA Rpt Qty:1000 LBS

DOT

Rpt Qty:1000 LBS

Ingred Name:XYLENE
CAS:1330-20-7
RTECS #:ZE2100000
= Wt:7.
OSHA PEL:100 PPM
ACGIH TLV:100 PPM
ACGIH STEL:150 PPM
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:METHYL PROPYL KETONE
CAS:107-87-9
RTECS #:SA7875000
Other REC Limits:NONE RECOMMENDED
OSHA PEL:200 PPM
ACGIH TLV:200 PPM
ACGIH STEL:250 PPM

Ingred Name:METHYL ISOBUTYL KETONE
CAS:108-10-1
RTECS #:SA9275000
= Wt:9.
OSHA PEL:100 PPM
ACGIH TLV:50 PPM
ACGIH STEL:75 PPM
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:EPOXY POLYMER
= Wt:70.
OSHA PEL:N/K
ACGIH TLV:N/K

=====
===== Hazards Identification =====

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.
Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:ACUTE: IRRITATION OF EYES, SKIN AND
RESPIRATORY SYSTEM. MAY CAUSE NERVOUS SYSTEM DEPRESSION. EXTREME
OVEREXPOSURE MAY RESULT IN UNCONSCIOUSNESS AND POSSIBLY DEATH.

SIGNS AND SYMPTOMS OF OVEREXPOSURE: HEADACHE, DIZZINESS, NAUSEA, AND LOSS OF COORDINATION ARE INDICATIONS OF EXCESSIVE EXPOSURE TO VAPORS OR SPRAY MISTS. REDNESS AND ITCHING OR BURNING SENSATION MAY INDICATE EYE OR EXCESSIVE SKIN EXPOSURE. CHRONIC: PROLONGED OVEREXPOSURE TO SOLVENT INGREDIENTS MAY CAUSE ADVERSE EFFECTS TO LIVER, URINARY AND REPRODUCTIVE SYSTEMS. REPORTS HAVE ASSOCIATED REPEATED AND PROLONGED OVEREXPOSURE TO SOLVENTS (SIGNS AND SYMPTOMS OF OVEREXPO

SRE)

Explanation of Carcinogenicity:NOT RELEVANT.

Effects of Overexposure:HEALTH HAZARDS ACUTE AND CHRONIC: WITH PERMANENT BRAIN AND NERVOUS SYSTEM DAMAGE.

Medical Cond Aggravated by Exposure:MAY CAUSE ALLERGIC SKIN REACTION IN SUSCEPTIBLE PERSONS.

===== First Aid Measures =====

First Aid:INHAL: REMOVE FROM EXPOSURE. RESTORE BREATHING. KEEP WARM & QUIET. SKIN: WASH AREA THOROUGHLY W/SOAP & WATER. REMOVE CONTAMINATED CLOTHING & LAUNDRY BEFORE RE-USE. EYES: FLUSH WITH LARGE AMOUNTS OF WATER FOR AT LEAST 15 MINUTES. GET MEDICAL ATTENTION. INGEST: GET MEDICAL ATTENTION.

===== Fire Fighting Measures =====

Flash Point Method:PMCC

Flash Point:=-7.8C, 46.F

Lower Limits:1.0%

Upper Limits:8.7%

Extinguishing Media:CARBON DIOXIDE, DRY CHEMICAL, FOAM.

Fire Fighting Procedures:FIREFIGHTERS SHOULD WEAR NIOSH APPROVED SELF CONTAINED BREATHING APPARATUS AND FULL PROTECTIVE EQUIPMENT . IF WATER IS

USED, FOG NOZZLES ARE PREFERRED. WATER MAY BE USED TO COOL CLOSED CONTAINERS TO PREVENT PRESSURE BUILD-UP AND POSSIBLE AUTOIGNITION / EXPLOSION WHEN EXPOSED TO EXTREME HEAT.

Unusual Fire/Explosion Hazard:KEEP CNTNRS TIGHTLY CLSD. ISOLATE FROM HEAT, ELEC EQUIP, SPKS, & OPEN FLAME. CLSD CNTNRS MAY EXPLODE WHEN EXPOS TO EXTREME HEAT. APPLIC TO HOT SURFS REQUIRE SPECIAL PRECAUTIONS. DURING EMERG CONDITIONS OVEREXP TO DECOMP PRODUCTS MAY CAUSE HEALTH HAZARDS. SYMPTOMS MAY NOT

BE IMMEDIATELY APPARENT.
OBTAIN MEDICAL ATTENTION.

===== Accidental Release Measures =====

Spill Release Procedures: REMOVE ALL SOURCES OF IGNITION. VENTILATE AND REMOVE WITH INERT ABSORBENT.
Neutralizing Agent: NONE SPECIFIED BY MANUFACTURER.

===== Handling and Storage =====

Handling and Storage Precautions: USE ONLY WITH ADEQUATE VENTILATION. AVOID BREATHING VAPORS AND SPRAY MIST. AVOID CONTACT WITH SKIN AND EYES.

Other Precautions: THIS COATING MAY CONTAIN MATERIALS CLASSIFIED AS NUISANCE PARTICULATES (LISTED "AS DUST") WHICH MAY BE PRESENT AT HAZARDOUS LEVELS ONLY DURING SANDING/ABRADING OF DRIED FILM. IF NO SPECIFIC DUSTS ARE LISTED, APPLICABLE LIMITS FOR NUISANCE DUSTS ARE: ACGIH TLV: 10 MG/M3 (TOTAL DUST), (TOXICOLOGICAL INFORMATION)

===== Exposure Controls/Personal Protection =====

Respiratory Protection: IF PERSONAL EXPOSURE CANNOT BE CONTROLLED BELOW APPLICABLE LIMITS BY VENTILATION, WEAR PROPERLY FITTED ORGANIC VAPOR/PARTICULATE RESPIRATOR APPROVED BY NIOSH FOR PROTECTION AGAINST MATERIALS. WHEN SANDING, OR ABRADING DRIED FILM, WEAR DUST/MIST RESPIRATOR APPROVED BY NIOSH FOR DUST WHICH MAY BE GENERATED FROM PRODUCT, UNDERLYING PAINT, OR ABRASIVE.

Ventilation: LOCAL EXHAUST PREFERABLE. GENERAL EXHAUST ACCEPTABLE IF EXPOSURE IS MAINTAINED BELOW APPLICABLE EXPOSURE LIMITS. REFER TO OSHA STDS 1910.94, 1910.107, 1910.108.

Protective G

loves: IMPERVIOUS GLOVES .

Eye Protection: ANSI APPROVED CHEM WORKERS GOGGLES .

Other Protective Equipment: ANSI APPROVED EYE WASH & DELUGE SHOWER . USE OF BARRIER CREAM ON EXPOSED SKIN IS RECOMMENDED.

Work Hygienic Practices: NONE SPECIFIED BY MANUFACTURER.

Supplemental Safety and Health

MFR TRADE NAME/PART NO: 2.8 VOC CHROMATED EPOXY POLYAMIDE PRIMER PART B (P&L 72450).

===== Physical/Chemical Properties =====

Boiling Pt: >102.8C, 217.F

Vapor Pres: OTHER INFO

Vapor

Density:HVR/AIR
Spec Gravity:1.06
VOC Pounds/Gallon:311
VOC Grams/Liter:2.6
Evaporation Rate & Reference:SLOWER THAN ETHER
Appearance and Odor:NONE SPECIFIED BY MANUFACTURER.
Percent Volatiles by Volume:38

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
NONE KNOWN.
Stability Condition to Avoid:NONE KNOWN.
Hazardous Decomposition Products:BY FIRE: CARBON DIOXIDE, CARBON
MONOXIDE, OXIDES OF METALS IN INGREDIENTS.

===== Toxicological Information =====

Toxicological Information:N/P. OTHER PRECAUTIONS (CONT): 3
MG/M3 (RESPIRABLE FRACTION); OSHA PEL: 15 MG/M3 (TOTAL DUST), 5
MG/M3 (RESPIRABLE FRACTION). CONTENTS ARE FLAMMABLE. KEEP AWAY
FROM HEAT, SPARKS AND OPEN FLAME. DURING USE UNTIL ALL VAPORS ARE
GONE: KEEP AREA VENTILATED - DO NOT SMOKE - EXTINGUISH ALL FLAMES,
PILOT LIGHTS, AND HEATERS - TURN OFF STOVES, ELECTRICAL TOOLS AND
APPLIANCES, AND ANY OTHER SOURCES OF IGNITION. CONSULT NFPA CODE.
USE APPROVED BONDING AND GROUNDING PROCEDURES. KEEP CONTAINERS
CLOSED WITH COMPLETE AND APPROPRIATE LABELING. DO NOT TAKE
INTERNALLY. KEEP OUT OF REACH OF CHILDREN. (OTHER INFORMATION)

===== Disposal Considerations =====

Waste Disposal Methods:WASTE FROM PRODUCT MAY BE HAZARDOUS AS DEFINED
UNDER RCRA 40 CFR 261. WASTE MUST BE TREATED FOR IGNITABILITY TO
DETERM APPLICABLE EPA HAZARDOUS WASTE NUMBERS. DO NOT
INCINERATE.
DEPRESSURIZE CONTAINER . DISPOSE OF IN ACCORDANCE WITH FEDERAL,
STATE AND LOCAL REGULATIONS REGARDING POLLUTION.

===== Regulatory Information =====

SARA Title III Information:SARA 313: ETHYL BENZENE, XYLENE, METHYL
ISOBUTYL KETONE.
Federal Regulatory Information:CERCLA: XYLENE, METHYL ISOBUTYL KETONE.

===== Other Information =====

Disclaimer (provided with this information by the compiling agency)

es):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.