

ELF ATOKEM NORTH AMERICA TURCO PRODUCTS, INC. -- TURCO 5469 -- 8010-00-181-7568

=====
Product Identification
=====

Product ID:TURCO 5469

MSDS Date:07/19/1996

FSC:8010

NIIN:00-181-7568

MSDS Number: CGXJW

=== Responsible Party ===

Company Name:ELF ATOKEM NORTH AMERICA TURCO PRODUCTS, INC.

Address:2375 STATE ROAD

City:CORNWELLS HEIGHTS

State:PA

ZIP:19020

Country:US

Info Phone Num:202-245-3128

Emerge

ncy Phone Num:202-483-7616 800-424-9300 CHEMTREC

CAGE:02BJ0

=== Contractor Identification ===

Company Name:ELF ATOCHEM NORTH AMERICA INC

Address:2375 STATE ROAD

Box:City:BENSALEM

State:PA

ZIP:19020

Country:US

Phone:215-245-3128

CAGE:02BJ0

=====
Composition/Information on Ingredients
=====

Ingred Name:PHENOL (SARA 302/313) (CERCLA)

CAS:108-95-2

RTECS #:SJ3327000

Fraction by Wt: 15.0%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:5 PPM

ACGIH TLV:5 PPM

EPA Rpt Qty:1000 LBS

DOT Rpt

Qty:1000 LBS

Ingred Name:SODIUM CHROMATE (SARA 313) (CERCLA)

CAS:7775-11-3

RTECS #:GB2955000

Fraction by Wt: 100F MAY DEVELOP INTERNAL
PRESSURE AND RUPTURE.

===== Accidental Release Measures =====

Spill Release Procedures:CONTAIN. STOP LEAK AT SOURCE. VENTILATE. PUMP INTO DRUM FOR DISPOSAL. ABSORB LIQUID ON INERT ABSORBENT & PUT IN DISPOSAL DRUMS. WASH W/WATER. COLLECT WASHINGS & PUT IN DISPOSAL DRUMS. KEEP FROM WATERWAYS.

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN COOL AREA AWAY FROM SUN, RAIN, STANDING WATER. USE CARE WHEN OPENING CONTAINER.
Other Precautions:VAPORS HEAVIER THAN AIR, MAY TRAVEL TO IGNIT SOURCES. PERSON ENTERING SUCH AREAS MUST USE RESP PROTECTION/SAFETY LINE. DIRECT CONTACT W/ALUMINUM OR OTHER CHLORINATED SOLVENTS MAY RESULT IN UNCONTROLLED CHEMICAL REACTION, POSSIBLY EXPLOSION.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:IF TLV EXCEEDED USE NIOSH APPROVED POSITIVE PRESSURE SCBA, HOSE MASK OR AIR-LINE MASK W/FULL FACE PIECE. IF RESPIRATORS ARE USED, FORMAL TRAINING/SCREENING PROGRAM MUST BE INITIATED.

Ventilation:SUFFICIENT MECHANICAL TO KEEP CONCENTRATIONS BELOW TLV.

Protective Gloves:NEOPRENE OR OTHER IMPERVIOUS

Eye Protection:FACE SHIELD OR GOGGLES

Other Protective Equipment:GLOVES, BOOTS, APRON MADE OF NEOPRENE OR OTHER IMPERVIOUS MATERIALS.

Work Hygienic Practices:

CONTACT WEARERS SHOULD USE VAPOR-PROOF WELL-FITTING GOGGLES. WASH W/SOAP & WATER BEFORE EATING/SMOKING.

Supplemental Safety and Health

REMOVE CONTAMINATED CLOTHES. WASH SEPARATELY BEFORE REUSE. DISCARD SHOES.

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:ABOUT 105F

Vapor Pres:1.0 AIR=1

Spec Gravity:1.14

VOC Pounds/Gallon:198

pH:3.1

Evaporation Rate & Reference: