

LHB INDUSTRIES -- SO-SURE LIGHT GRAY PRIMER (0234-382)

=====  
MSDS Safety Information  
=====

FSC: 8010  
NIIN: 00-616-9181  
MSDS Date: 10/02/1997  
MSDS Num: CGXMK  
Product ID: SO-SURE LIGHT GRAY PRIMER (0234-382)  
MFN: 04  
Responsible Party  
Cage: 0FTT5  
Name: LHB INDUSTRIES  
Address: 8833 FLEISCHER PLACE  
City: ST. LOUI  
S MO 63134  
Info Phone Number: 314-522-3141  
Emergency Phone Number: 800-424-9300 CHEMTREC/ 314-522-3141  
Preparer's Name: ROBIN C. GANNON  
Published: Y

=====  
Preparer Co. when other than Responsible Party Co.  
=====

Cage: 0FTT5  
Name: LHB INDUSTRIES  
Address: 8833 FLEISCHER PLACE  
City: ST. LOUIS MO 63134

=====  
Contractor Summary  
=====

Cage: 0FTT5  
Name: LHB INDUSTRIES  
Address: 8833 FLEISCHER PLACE  
City: ST. LOUIS MO 63134  
Phone: 314-522-3141

=====  
Item Description Information  
=====

Item Manager: GSA  
Item Name: PRIMER COATING  
Specification Number: A-A-1551  
Unit of Issue: PT  
UI Container Qty: 0

=====  
Ingredients  
=====

=====

Cas: 108-88-3  
RTECS #: XS5250000  
Name: TOLUENE (SARA 313) (CERCLA)  
% Wt: 11.99  
Other REC Limits: NONE RECOMMENDED  
OSHA PEL: 200 PPM  
ACGIH TLV: 100 PPM  
EPA Rpt Qty: 1000 LBS  
DOT Rpt Qty: 1000 LBS

-----

Cas: 74-98-6  
RTECS #: TX2275000  
Name: PROPANE  
% Wt: 16.88  
Other REC Limits: NONE RECOMMENDED  
OSHA PEL: 1000 PPM  
ACGIH TLV: 1000 PPM

-----

Cas: 67-64-1  
RTECS #: AL3150000  
Name: ACETONE (SARA 313) (CERCLA)  
% Wt: 11.99  
Other REC Li  
mits: NONE RECOMMENDED  
OSHA PEL: 1000 PPM  
ACGIH TLV: 750 PPM  
EPA Rpt Qty: 5000 LBS  
DOT Rpt Qty: 5000 LBS

-----

Cas: 8032-32-4  
RTECS #: OI6180000  
Name: VM&P NAPHTHA  
% Wt: 16.77  
Other REC Limits: NONE RECOMMENDED  
OSHA PEL: 300 PPM  
ACGIH TLV: 300 PPM

-----

Cas: 106-97-8  
RTECS #: EJ4200000  
Name: N-BUTANE  
% Wt: 7.43  
Other REC Limits: NONE RECOMMENDED  
OSHA PEL: 800 PPM  
ACGIH TLV: 800 PPM

-----

Cas: 75-28-5  
RTECS #: TZ430000

0  
Name: 2-METHYL PROPANE  
% Wt: 1.64  
Other REC Limits: NONE RECOMMENDED  
OSHA PEL: NOT ESTABLISHED  
ACGIH TLV: 800 PPM

-----  
Cas: 8052-41-3  
RTECS #: WJ8925000  
Name: STODDARD SOLVENT  
% Wt: 4.51  
Other REC Limits: NONE RECOMMENDED  
OSHA PEL: 500 PPM  
ACGIH TLV: 100 PPM

=====  
Health Hazards Data  
=====

Route Of Entry Inds - Inhalation: YES  
Skin: YES  
Ingestion: YES  
Carcinogenicity I  
nds - NTP: NO  
IARC: NO  
OSHA: NO  
Effects of Exposure: EYE: IRRIT. SKIN: IRRIT. INHAL: RESPIRATORY TRACT AND  
THROAT IRRIT, HEADACHE, NAUSEA, VOMIT, HARMFUL, FATAL, BRAIN/NS DAMAGE,  
ANESTHETIC, LIGHTHEADED, STAGGERING GAIT, GIDDY, NAUSEA. INGEST: HARMFUL.  
Medical Cond Aggravated By Exposure: RESPIRATORY AILMENTS  
First Aid: EYE: FLUSH W/WATER FOR 15 MINUTES. SKIN: WASH W/SOAP & WATER.  
WASH CLOTHES BEFORE REUSE. INHAL: REMOVE TO FRESH AIR. ARTIFICIAL RESPIRATION  
IF NEEDED. INGEST: DONT IN  
DUCE VOMIT. IN ALL CASES, GET IMME D MED AID.

=====  
Handling and Disposal  
=====

Spill Release Procedures: REMOVE IGNIT SOURCES. VENTILATE AREA. MOP SPILL  
W/INERT ABSORBENT. AVOID BREATHING VAPORS.  
Waste Disposal Methods: DISPOSE OF IN ACCORDANCE W/FEDERAL, STATE AND LOCAL  
REGULATIONS. DONT PUNCTURE, INCINERATE OR STORE >120F. EXPOSURE TO HEAT OR  
SUN MAY CAUSE CAN TO BURST. DISCARD EMPTY C

AN IN TRASH PICK-UP. DONT PLAC E  
IN HOME TRASH COMPACTOR.

Handling And Storage Precautions: KEEP OUT OF REACH OF CHILDREN. CAUTION:  
CONTENTS UNDER PRESSURE. DONT STORE >120F.

Other Precautions: USE W/GOOD VENTILATION. READ ENTIRE LABEL BEFORE USING.  
FOLLOW ALL LABEL DIRECTIONS.

=====  
Fire and Explosion Hazard Information  
=====

Flash Point Text: -156F,-104C

Autoignition Temp Text: 674F

Lo

wer Limits: 1.8

Upper Limits: 9.5

Extinguishing Media: CARBON DIOXIDE, DRY CHEMICAL, FOAM, SAND, WATER SPRAY.

Fire Fighting Procedures: WATER MAY BE INEFFCTIVE. USE WATER TO KEEP CONTAINERS  
COOL. USE SCBA. USE SHIELDING TO PROTECT AGAINST BURSTING, RUPTURING OR  
VENTING OF CONTAINERS.

Unusual Fire/Explosion Hazard: DONT SPRAY NEAR OPEN FLAME. AT TEMPS >120F  
CONTAINERS MAY VENT, RUPTURE OR BURST. AEROSOL CONTAINERS: DONT EXPOSE TO  
TEMPS >120F.

=====  
Control Measures  
=====

Respiratory Protection: NONE BELOW TLV. USE NIOSH/MSHA APPROVED MASK ABOVE TLV.

Ventilation: LOCAL EXHAUST PREFERRED. MECHANICAL (GENERAL) ACCEPTABLE AT POINT  
OF MIST OR SPRAY RELEASE.

Protective Gloves: REQUIRED

Eye Protection: CHEMICAL SPLASH GOGGLES

Other Protective Equipment: IMPERVIOUS CLOTHES TO PROTECT SKIN, EYEWASH  
STATION.

Work Hygienic Practices: USE GOOD PERSONAL HYGIENE. DONT EAT, DRINK OR S  
MOKE  
WHILE USING PRODUCT.

=====  
Physical/Chemical Properties  
=====

B.P. Text: NA

M.P/F.P Text: NA

Decomp Text: NA

Vapor Pres: 60 @ 68F

Vapor Density: >1.5

Spec Gravity: 0.801 (AEROSOL)

PH: NA

VOC Grams/Liter: 494

Viscosity: NA

Solubility in Water: INSOLUBLE

Appearance and Odor: GRAY PAINT

Corrosion Rate: NA

=====  
Reactivity Data  
=====

=====  
Stability Indicator: YES  
Stability Condition To Avoid: EXTREME HEAT  
Materials To Avoid: NA  
Hazardous Decomposition Products: CARBON MONOXIDE  
Hazardous Polymerization Indicator: NO  
Conditions To Avoid Polymerization: NA  
=====

=====  
Toxicological Information  
=====

=====  
Ecological Information  
=====

=====  
MSDS Transport Information  
=====

=====  
Regulatory Information  
=====

=====  
Other Information  
=====

Other Information: VOC = 494 G/L  
=====

=====  
Transportation Information  
=====

Responsible Party Code: 0FTT5  
Trans ID NO: 79876  
Product ID: SO-SURE LIGHT GRAY PRIMER (0234-382)  
MSDS Prepared Date: 10/02/1997  
Review Date: 04/21/1998  
MFN: 4  
Multiple KIT Number: 0  
Review IND: Y  
Unit Of Issue: PT  
Container QTY: 0  
=====

=====  
Detail DOT Information  
=====

DOT PSN Code:

DTJ  
Symbols: D  
DOT Proper Shipping Name: CONSUMER COMMODITY  
Hazard Class: ORM-D  
Label: NONE  
Non Bulk Pack: 156,306  
Bulk Pack: NONE  
Max Qty Pass: 30KGGROSS  
Max Qty Cargo: 30KGGROSS  
Vessel Stow Req: A

=====  
Detail IMO Information  
=====

IMO PSN Code: AKH  
IMO Proper Shipping Name: AEROSOLS/AEROSOL PRODUCT ?  
IMDG Page Number: SEE 9022  
UN Number: 1950  
UN Hazard Class: 9?  
IMO Packaging Group: -  
Subsidia  
ry Risk Label: -  
EMS Number: 2-13

=====  
Detail IATA Information  
=====

IATA PSN Code: ALS  
IATA UN ID Num: 1950  
IATA Proper Shipping Name: AEROSOLS, FLAMMABLE  
IATA PSN Modifier: (EACH NOT EXCEEDING 1 L CAPACITY)  
IATA UN Class: 2.1  
IATA Label: FLAMMABLE GAS  
Packing Note Passenger: 203  
Max Quant Pass: 75KG  
Max Quant Cargo: 150KG  
Packaging Note Cargo: 203

=====  
Detail AFI Information  
=====

AFI PSN Code: ALR  
AFI Symbols: \*  
AFI Proper Shipping Name: AEROSOLS, FLAMMABLE, N.O.S.  
AFI PSN Modifier: (EACH NOT EXCEEDING 1L CAPACITY)  
AFI Hazard Class: 2.1  
AFI UN ID NUM: UN1950  
Special Provisions: P4  
Back Pack Reference: A6.3

=====  
HAZCOM Label  
=====

Product ID: SO-SURE LIGHT GRAY PRIMER (0234-382)  
Cage

: 0FTT5

Company Name: LHB INDUSTRIES

Street: 8833 FLEISCHER PLACE

City: ST. LOUIS MO

Zipcode: 63134

Health Emergency Phone: 800-424-9300 CHEMTREC/ 314-522-3141

Label Required IND: Y

Date Of Label Review: 10/12/1999

Status Code: A

Origination Code: G

Hazard And Precautions: EYE: IRRIT. SKIN: IRRIT. INHAL: RESPIRATORY TRACT AND THROAT IRRIT, HEADACHE, NAUSEA, VOMIT, HARMFUL, FATAL, BRAIN/NS DAMAGE, ANESTHETIC, LIGHTHEADED, STAGGERING GAIT, GIDDY, NAUSEA. INGEST: HARMFUL.

=====

=====

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever expressly or implied warrants, states, or intends said information to have any application, use or viability by or to any person or persons outside the Department of Defense nor any person or persons contracting with any instrumentality of the United States of America and disclaims all liability for such use. Any person utilizing this instruction who is not a military or civilian employee of the United States of America should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation regardless of similarity to a corresponding Department of Defense or other government situation.