

LONE STAR INDUSTRIES INC -- PORTLAND CEMENT

=====  
MSDS Safety Information  
=====

FSC: 5610  
NIIN: 00-242-3792  
MSDS Date: 08/10/1994  
MSDS Num: CHKFN  
Product ID: PORTLAND CEMENT  
MFN: 01  
Responsible Party  
Cage: LONES  
Name: LONE STAR INDUSTRIES INC  
Address: 8902 VINCENNES CIRCLE SUITE A  
Box: 681250  
City:  
INDIANAPOLIS IN 46268-1250  
Info Phone Number: 800-782-7236  
Emergency Phone Number: 317-653-6766  
Published: Y

=====  
Contractor Summary  
=====

Cage: LONES  
Name: LONE STAR INDUSTRIES INC  
Box: 681250  
City: INDIANAPOLIS IN 46268-1250  
Phone: 713-875-5005  
Cage: LSTAR  
Name: LONE STAR INDUSTRIES INC  
Address: UNKNOWN  
Box: UNKNOWN  
City: UNKNOWN NK 00000  
Phone: UNKNOWN

=====  
Item Description Information  
=====

Item Manager: GSA  
Item Name: CEMENT,PORTLAND  
Unit of Issue: BG  
Quantitative Expression: 00000000094LB  
UI Container Qty: 0

=====  
Ingredients  
=====

Cas: 12168-85-3  
Name: TRICALCIUM SILICATE; (3CAO.SIO\*2)  
OSHA PEL: N/K (FP N)  
ACGIH TLV: N/K (FP N)

-----  
Cas: 10034-77-2  
Name:

DICALCIUM SILICATE; (2CAO.SIO\*2)

OSHA PEL: N/K (FP N)

ACGIH TLV: N/K (FP N)

-----

Cas: 12042-78-3

Name: TRICALCIUM ALUMINATE; (3CAO.AL\*2O\*3)

OSHA PEL: N/K (FP N)

ACGIH TLV: N/K (FP N)

-----

Cas: 12068-35-8

Name: TETRACALCIUM ALUMINOFERRATE; (CALCIUM ALUMINOFERRITE, A SOLID SOLUTION)

OSHA PEL: N/K (FP N)

ACGIH TLV: N/K (FP N)

-----

Cas: 13397-24-5

RTECS #: MG2360000

Name: GYPSUM; (CASO\*4-2H\*2O)

OSHA PEL: N/K (FP N)

ACGIH

TLV: N/K (FP N)

-----

Name: HYDRATED LIME

OSHA PEL: N/K (FP N)

ACGIH TLV: N/K (FP N)

-----

Cas: 1305-78-8

RTECS #: EW3100000

Name: CALCIUM OXIDE; (CAO)

OSHA PEL: 5 MG/M3

ACGIH TLV: 2 MG/M3

-----

Cas: 1309-48-4

RTECS #: OM3850000

Name: MAGNESIUM OXIDE; (MGO)

OSHA PEL: 15 MG/M3 PARTICULATE

ACGIH TLV: 10 MG/M3 FUME

-----

Cas: 7757-82-6

RTECS #: WE1650000

Name: SODIUM SULFATE; (NA\*2SO\*4)

OSHA PEL: N/K

(FP N)  
ACGIH TLV: N/K (FP N)

-----  
Cas: 7778-80-5  
RTECS #: TT5900000  
Name: POTASSIUM SULFATE; (K\*2SO\*4)  
OSHA PEL: N/K (FP N)  
ACGIH TLV: N/K (FP N)

-----  
Name: PORTLAND CEMENT MAY CONTAIN INGREDIENT 12 - 14.  
OSHA PEL: N/K (FP N)  
ACGIH TLV: N/K (FP N)

-----  
Name: INSOLUBLE MATTER; (INSOLUBLE RESIDUE)  
% Wt: 0.75  
OSHA PEL: N/K (FP N)  
ACGIH TLV: N/K (FP N)

-----  
Cas: 60676-86-0  
RTECS #: VV7328000  
Name: S  
ILICA, CRYSTALLINE-FUSED; (FREE CRYSTALLINE SILICA)  
% Wt: 0.1  
OSHA PEL: N/K (FP N)  
ACGIH TLV: N/K (FP N)

-----  
Cas: 7440-47-3  
RTECS #: GB4200000  
Name: CHROMIUM (SARA 313) (CERCLA)  
% Wt: TRACE  
OSHA PEL: 1 MG/M3  
ACGIH TLV: 0.5 MG/M3  
EPA Rpt Qty: 1 LB  
DOT Rpt Qty: 1 LB

=====  
Health Hazards Data  
=====

LD50 LC50 Mixture: NONE SPECIFIED BY MANUFACTURER.

Route Of Entry Inds - In

halation: YES

Skin: YES

Ingestion: YES

Carcinogenicity Inds - NTP: NO

IARC: YES

OSHA: NO

Effects of Exposure: ACUTE:WET PORTLAND CEMENT LIME BLEND, ESPECIALLY AS  
INGREDIENT IN PLASTIC (UNHARDENED) CONCRETE, MORTAR OR SLURRIES, CAN DRY SKIN  
AND CAUSE SEVERE ALKALI BURNS. PORTLAND/LIME DUST CAN IRRITATE EYES AN D  
UPPER RESPIRATORY SYSTEM. CHRONIC:PORTLAND CEMENT LIME BLEND DUST CAN CAUSE  
INFLAMMATION OF LINING (EFTS OF OVEREXP)

Explanation Of Carcinogenicity: CRYSTALLINE SILICA-FUSED:IARC

MONOGRAPHS,

SUPPLEMENT, VOL 7, PG 341, 1987:GROUP 2A.

Signs And Symptions Of Overexposure: HLTH HAZ:TISSUE OF INTERIOR OF NOSE AND INFLAMMATION OF CORNEA. INDIVIDUALS WHO ARE ALLERGIC TO CHROMIUM MAY DEVELOP AN ALLERGIC DERMATITIS. FREE CRYSTALLINE SILICA CAN CAUSE CANCER. EXPOSURE TO PORTL AND/LIME CEMENT CAN AFFECT THE SKIN, EYES AND MUCOUS MEMBRANES.

Medical Cond Aggravated By Exposure: NONE SPECIFIED BY MANUFACTURER.

First Aid: INGEST:CALL MD IMMEDIATELY (FP N). INHAL:REMOVE TO FRESH AIR.

SUPPORT BREATHING (GIVE O\*2/ARTF RESP) (FP N). EYES:IRRIGATE (FLOOD) IMMEDIATELY & REPEATEDLY W/CLEAN WATER FOR AT LEAST 15 MINUTES. GET P ROMPT MEDICAL ATTENTION. SKIN:WASH EXPOSED AREAS W/SOAP & WATER. APPLY STERILE DRESSINGS. GET PROMPT MEDICAL ATTENTION.

=====  
Handling and Disposal  
=====

Spill Release Procedures: IF PORTLAND CEMENT LIME BLEND IS SPILLED, IT CAN BE CLEAN ED UP USING DRY METHODS THAT DO NOT DISPERSE DUST INTO THE AIR. AVOID BREATHING DUST. EMERGENCY PROCEDURES ARE NOT REQUIRED.

Neutralizing Agent: NONE SPECIFIED BY MANUFACTURER.

Waste Disposal Methods: DISPOSAL MUST BE I/A/W FEDERAL, STATE & LOCAL REGULATIONS (FP N). PORTLAND CEMENT LIME BLEND CAN BE TREATED AS A COMMON WASTE FOR DISPOSAL, OR RETURNED TO CONTAINER FOR LATER USE IF IT IS NOT CONTAMIN ATED OR WET.

Handling And Storage Precautions: NONE SPECIFIED BY MANUFACTURER.

Other P recautions: NONE SPECIFIED BY MANUFACTURER.

=====  
Fire and Explosion Hazard Information  
=====

Extinguishing Media: MEDIA SUITABLE FOR SURROUNDING FIRE (FP N).

Fire Fighting Procedures: USE NIOSH APPROVED SCBA & FULL PROTECTIVE EQUIPMENT (FP N).

Unusual Fire/Explosion Hazard: PORTLAND CEMENT LIME BLEND IS NON-COMBUSTIBLE & NOT EXPLOSIVE. THEREFORE THERE ARE NO FLAMMABLE OR EXPLOSIVE LI MITS NOR UNUSUAL FIRE & EXPLOSION HAZARDS.

=====  
Control Measures  
=====

Respiratory Protection: IN DUSTY ENVIRONMENTS, THE USE OF A NIOSH APPROVED RESPIRATOR IS RECOMMENDED.

Ventilation: LOCAL EXHAUST CAN BE USED, IF NECESSARY, TO CONTROL AIRBORNE DUST LEVELS.

Protective Gloves: IMPERVIOUS GLOVES.

Eye Protection: ANSI APPROVED CHEM WORKERS GOGGS (FP N).

Other Protective Equipment: ANSI

APPROVED EYE WASH FOUNTAIN & DELUGE SHOWER (FP  
N). USE OF BARRIER CREAMS, BOOTS & CLTHG TO PROT SKIN FROM (SUPDAT)  
Work Hygienic Practices: FOLLOWING WORK W/PORTLAND CEMENT LIME BLEND, WORKERS  
SHOULD SHOWER W/SOAP & WATER.  
Supplemental Safety and Health: MATLS TO AVOID:REACT IN WET MORTAR OR CONCRETE,  
LIBERATING HYDROGEN GAS. OTHER PROT EQUIP:CONTACT W/WET PORTLAND CEMENT IS  
RECOMMENDED.

=====  
Physical/Chemical Properties  
=====

=====  
Spec Gravity: 2.98-3.05  
Solubility in Water: SLIGHT (0.1-1%)  
Appearance and Odor: GRAY COLORED POWDER W/NO ODOR.  
=====

Reactivity Data  
=====

Stability Indicator: YES  
Stability Condition To Avoid: KEEP PORTLAND CEMENT LIME BLEND DRY UNTIL USED TO  
PRESERVE PRODUCT UTILITY.  
Materials To Avoid: PORTLAND CEMENT LIME BLEND IS INCOMPAT W/ALUMINUM POWDER &  
OTH  
ER ALKALI & ALKALINE EARTH ELEMENTS WHICH CAN (SUPP DATA)  
Hazardous Decomposition Products: HYDROGEN GAS.  
Hazardous Polymerization Indicator: NO  
Conditions To Avoid Polymerization: NOT RELEVANT  
=====

Toxicological Information  
=====

Ecological Information  
=====

MSDS Transport Information  
=====

Regulatory Information  
=====

Other Information  
=====

Transportation Information  
=====

=====  
Responsible Party Cage: LONES  
Trans ID NO: 59906  
Product ID: PORTLAND CEMENT  
MSDS Prepared Date: 08/10/1994  
Review Date: 10/19/1998  
MFN: 1  
Multiple KIT Number: 0  
Review IND: Y  
Unit Of Issue: BG  
Container QTY: 0

=====  
Detail DOT Information  
=====

DOT PSN Code: ZZZ  
DOT Proper Shipping Name: NOT REGULATED BY THIS MODE OF TRANSPORTATION  
=====

=====  
Detail IMO Information  
=====

IMO PSN Code: ZZZ  
IMO Proper Shipping Name: NOT REGULATED FOR THIS MODE OF TRANSPORTATION  
=====

=====  
Detail IATA Information  
=====

IATA PSN Code: ZZZ  
IATA Proper Shipping Name: NOT REGULATED BY THIS MODE OF TRANSPORTATION  
=====

=====  
Detail AFI Information  
=====

=====  
AFI PSN Code: ZZZ  
AFI Proper Shipping Name: NOT REGULATED BY THIS MODE OF TRANSPORTATION  
=====

=====  
HAZCOM Label  
=====

Product ID: PORTLAND CEMENT  
Cage: LONES  
Assigned IND: Y  
Company Name: LONE STAR INDUSTRIES INC  
PO Box: 681250  
City: INDIANAPOLIS IN  
Zipcode: 46268-1250  
Health Emergency Phone: 317-653-6766  
Label Required IND: Y  
Date Of Label Review: 07/01/1998

Status Code: C

Label Date: 07/01/1998

Origination

Chronic Hazard IND: Y

Eye Protection IND: YES

Skin Protection IND: YES

Signal Word: WARNING

Respiratory Protection IND: YES

Health Hazard: Moderate

Contact Hazard: Moderate

Fire Hazard: None

Reactivity Hazard: None

Hazard And Precautions: ACUTE:WET PORTLAND CEMENT LIME BLEND, ESPECIALLY AS INGREDIENT IN PLASTIC (UNHARDENED) CONCRETE, MORTAR OR SLURRIES, CAN DRY SKIN AND CAUSE SEVERE ALKALI BURNS. PORTLAND/LIME DUST CAN IRRITATE EYES AND

UPPER RESPIRATORY SYSTEM. CHRONIC:CANCER HAZARD. CONTAINS CRYSTALLINE SILICA WHICH IS LISTED AS AN ANIMAL LUNG CARCINOGEN (FP N). PORTLAND CEMENT LIME BLEND DUST CAN CAUSE INFLAMMATION OF LINING TISSUE OF INTERIOR OF NOSE AND INFLAMMATION OF CORNEA. MAY CAUSE ALLERGIC DERMATITIS.

=====  
Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense.

The United States of America in no manner whatsoever expressly or implied warrants, states, or intends said information to have any application, use or viability by or to any person or persons outside the Department of Defense nor any person or persons contracting with any instrumentality of the United States of America and disclaims all liability for such use. Any person utilizing this instruction who is not a military or civilian employee of the United States of America should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation regardless of similarity to a corresponding Department of Defense or other government situation.